
ZORYA-MINI

~340° omnidirectional decorative beam

SPECIFICATION:

Ø 24.0 mm **Dimensions** Height 14.2 mm glue, tape Fastening **ROHS** compliant yes 🕕



MATERIALS:

Type Material Colour **Finish** Component **ZORYA-MINI** Single lens PC clear


ORDERING INFORMATION:

» Box size: 476 x 273 x 292 mm

Component Qty in box MOQ MPQ Box weight (kg)

C15419_ZORYA-MINI 2448 272 136 7.3

PRODUCT DATASHEET C15419_ZORYA-MINI



See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.




OPTICAL RESULTS (SIMULATED):

CREE &

LED XM-L2 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 163.0° / 163.0° Efficiency 94 % Peak intensity 0.1 cd/lm LEDs/each optic

White


Light colour Required components:



CREE &

LED XP-E2 FWHM / FWTM 145.0° / 145.0° Efficiency 94 % Peak intensity 0.1 cd/lm LEDs/each optic 1 White Light colour

Required components:




LUMILEDS

LED LUXEON 7070 FWHM / FWTM 297.0° / 358.0°

Efficiency 82 % Peak intensity 0.1 cd/lm LEDs/each optic 1 Light colour White

Required components:




MUMILEDS

LED LUXEON IR Domed 150 (L1I0-0xxx150000000)

FWHM / FWTM 216.0° / 240.0° Efficiency 75 % Peak intensity 0.1 cd/lm LEDs/each optic White Light colour

Required components:



Published: 15/09/2020



OPTICAL RESULTS (SIMULATED):




LED NF2x757G $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 270.0° / 353.0°

Efficiency 93 % Peak intensity 0.1 cd/lm 4

LEDs/each optic Light colour White

Required components:




WNICHIA

LED NF2x757G FWHM / FWTM 199.0° / 348.0°

Efficiency 93 % Peak intensity 0.1 cd/lm LEDs/each optic 9 White Light colour

Required components:



OSRAM Opto Semiconductors

LED Duris S10 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 125.0° / 125.0°

Efficiency 94 % Peak intensity 0.1 cd/lm LEDs/each optic 1 Light colour White

Required components:

