

OLGA-RS

~9° spot beam with flange. Optimized for high-power 3535 size LED packages.

SPECIFICATION:

Dimensions Ø 29.7 mm
Height 18.4 mm
ROHS compliant yes ①



MATERIALS:

ComponentTypeMaterialColourFinishOLGA-RSSingle lensPMMAclear


ORDERING INFORMATION:

Component Qty in box MOQ MPQ Box weight (kg)

C16671_OLGA-RS 792 132 66 7.3 » Box size: 476 x 273 x 292 mm




PRODUCT DATASHEET C16671_OLGA-RS




See also our general installation guide: www.ledil.com/installation_guide



OPTICAL RESULTS (MEASURED):






CITIZEN LED CLU7B2 FWHM / FWTM 9.0° / 31.0° Efficiency 84 % Peak intensity 10.3 cd/lm


Required components:

LEDs/each optic 1
Light colour White
Required components:



CITIZEN


LED CLU7L3
FWHM / FWTM 7.0° / 29.0°
Efficiency 89 %
Peak intensity 13.3 cd/lm
LEDs/each optic 1
Light colour White



CITIZEN

Required components:


LED CLU7R3
FWHM / FWTM 12.0° / 41.0°
Efficiency 87 %
Peak intensity 6.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



Published: 14/01/2019



OPTICAL RESULTS (MEASURED):






OPTICAL RESULTS (MEASURED):

OSRAM

LED OSCONIQ P 3737 (3W version)

FWHM / FWTM 10.0° / 25.0° Efficiency 85 % Peak intensity 14.5 cd/lm LEDs/each optic

Light colour White Required components:




OSRAM

LED OSLON Square CSSRM2/CSSRM3

FWHM / FWTM 7.0° / 17.0° Efficiency 86 % Peak intensity 26.6 cd/lm LEDs/each optic 1 White Light colour Required components:






SAMSUNG

LED LH351D $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 12.0° / 26.0° Efficiency 86 % Peak intensity 12.1 cd/lm

LEDs/each optic Light colour White Required components:





Published: 14/01/2019




OPTICAL RESULTS (SIMULATED):



LED V3 HD Gen 8
FWHM / FWTM 14.0° / 26.0°
Efficiency 96 %
Peak intensity 13 cd/lm
LEDs/each optic 1
Light colour White


Required components:



bridgelux

LED V4 HD Gen 7
FWHM / FWTM 16.0° / 31.0°
Efficiency 96 %
Peak intensity 9.1 cd/lm
LEDs/each optic 1
Light colour White


Required components:



bridgelux


LED V6 HD Gen 7
FWHM / FWTM 18.0° / 46.0°
Efficiency 93 %
Peak intensity 5.1 cd/lm
LEDs/each optic 1
Light colour White

Required components:



CITIZEN

LED CLU7A2/7A3
FWHM / FWTM 12.0° / 27.0°
Efficiency 91 %
Peak intensity 13 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OPTICAL RESULTS (SIMULATED):

White

CREE &


Light colour

LED CMA1303 FWHM / FWTM 16.0° / 30.0°

Efficiency 95 %

Peak intensity 9.5 cd/lm LEDs/each optic 1

Required components:




CREE -

LED CXA/B 13xx FWHM / FWTM 18.0° / 45.0°

Efficiency 89 %
Peak intensity 4.9 cd/lm
LEDs/each optic 1

Light colour White

Required components:




CREE +

LED XHP35 HI

FWHM / FWTM 10.0° / 20.0° Efficiency 96 %

Peak intensity 23.2 cd/lm
LEDs/each optic 1
Light colour White

Required components:




LUMINUS

LED CXM-3

FWHM / FWTM 12.0° / 26.0°
Efficiency 96 %
Peak intensity 14 cd/lm
LEDs/each optic 1
Light colour White

Required components:





OPTICAL RESULTS (SIMULATED):



LED CXM-4

14.0° / 38.0°

FWHM / FWTM Efficiency

96 %

Peak intensity


8.3 cd/lm

LEDs/each optic

Light colour

White

Required components:



XICATO

LED

XOB 6 mm

FWHM / FWTM

18.0° / 46.0°

Efficiency

94 %

Peak intensity


LEDs/each optic

5.5 cd/lm

Light colour

1 White

Required components:



Published: 14/01/2019