

CA0022

Technical Datasheet



Technical Specifications	
Part No.	CA0022
Type	Shielded cable
Number/Type of Conductors	6 insulated multi-strand wire bundles (internal)
Conductor Gauge	22AWG (tin plated copper)
Voltage Rating	300V (max)
Temperature Rating	-20°C to 90°C
Length	610mm (2ft)
Termination	Glenair connector (P/N 807-215-06ZNU6-6PYB) at one end, flying leads on the other end
Shield Termination	To connector shell (internal)
Diameter	At Connector: 15.2mm (0.6") At Core: 5.8mm (0.23")
Weight	~0.45kg (1.0lb)
Jacket & Over Mold Material	Polyurethane. Homogeneous bond between cable & over mold
Color	Black
Markings	Cable part number, description & serial number printed on cable sleeve Connectors marked with alphabetic pin designators


Features

- Over molded connector at one end
- Mates with Glenair series 807-198, 907-216, 807-217 receptacle connector
- Cable shielding terminated at each connector shell to provide effective noise shielding

Applications

- Charge/Discharge cable for UBBL06 (LI-145), UBBL06-01 (LI-175) and UBBL08 (LI-80)

Maximum Dimensions in mm [inches]



CONTACT TABLE

CONTACT No	CONDUCTOR
1	RED
2	BLACK
3	BROWN
4	YELLOW
5	ORANGE
6	GREEN

