

### STRADA-SQ-C

Beam for area and street lighting such as parks and pedestrian walkways. Version with location pins. Assembly with installation tape.

#### **SPECIFICATION:**

25.0 x 25.0 mm **Dimensions** 9.9 mm Height Fastening tape, pin yes 🕕 ROHS compliant



#### **MATERIALS:**


Material Colour **Finish** Component **Type** STRADA-SQ-C Single lens **PMMA** clear **ROSE-TAPE** Tape Acrylic foam black

#### **ORDERING INFORMATION:**

Component Qty in box MOQ MPQ Box weight (kg) 2058 294 CA16031\_STRADA-SQ-C Single lens 98 8.1

» Box size: 476 x 273 x 292 mm

# PRODUCT DATASHEET CA16031\_STRADA-SQ-C



See also our general installation guide: www.ledil.com/installation\_guide



### **OPTICAL RESULTS (SIMULATED):**

# CREE &

LED XHP70

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 120.0° / 138.0°

Efficiency 96 % Peak intensity 0.3 cd/lm

LEDs/each optic

Light colour White

Required components:



LED XM-L2


FWHM / FWTM 119.0° / 139.0°

Efficiency 96 % Peak intensity 0.3 cd/lm

LEDs/each optic 1

White Light colour

Required components:



# CREE +


LED XT-E

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 122.0° / 146.0°

Efficiency 95 % Peak intensity 0.3 cd/lm

LEDs/each optic 1 Light colour White

Required components:




## **MUMILEDS**

LED LUXEON 5050 Square LES

FWHM / FWTM 116.0° / 138.0°

Efficiency 96 % Peak intensity 0.3 cd/lm LEDs/each optic White Light colour

Required components:



Published: 15/07/2019



### **OPTICAL RESULTS (SIMULATED):**



LED LUXEON 7070

FWHM / FWTM 115.0° / 138.0°


Efficiency 88 %
Peak intensity 0.3 cd/lm

LEDs/each optic 1

Light colour White

Required components:

Protective plate, glass




### **MUMILEDS**

LED LUXEON M/MX FWHM / FWTM 119.0° / 138.0°

Efficiency 95 %
Peak intensity 0.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:



## **MUMILEDS**

LED LUXEON MZ FWHM / FWTM 116.0° / 138.0°

Efficiency 96 %
Peak intensity 0.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:

