

MODEL: CMS-251452-28SP | **DESCRIPTION:** SPEAKER**FEATURES**

- 8 ohm
- 2 W rated
- solder tabs

**SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
input power			2.0	3.0	W
impedance	at 1,500 Hz	6.8	8	9.2	Ω
resonant frequency (Fo)		216	270	324	Hz
frequency response		150		20,000	Hz
sound pressure level	at 1.0 W, 50 cm, avg at 0.6, 0.8, 1.0, 1.2 kHz	79	82	85	dB
distortion	at 1.0 kHz, 1.0 W			5	%
buzz, rattle, etc.	must be normal at sine wave			2.83	V
polarity	cone moves forward w/ positive dc current to "+" terminal				
dimensions	28 x 28 x 10.8				mm
magnet	Nd-Fe-B				
frame material	PBT + 10% GF				
cone material	foam				
terminal	solder terminals				
weight			15.4		g
operating temperature		-20		55	$^{\circ}\text{C}$
storage temperature		-25		60	$^{\circ}\text{C}$
hand soldering	for maximum 2 seconds	360		380	$^{\circ}\text{C}$
RoHS	yes				

Notes: 1. All specifications measured at 15-35 $^{\circ}\text{C}$, humidity at 25-75%, unless otherwise noted.

RESPONSE CURVES

Frequency Response Curve

Test Conditions: 2.83 V / 50 cm
Magn dB re 20.0 uPa.

