

LOS-D

~14° diffused spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.

SPECIFICATION:

Dimensions	Ø 21.6 mm
Height	14.3 mm
Fastening	glue, pin
ROHS compliant	yes 🕕



MATERIALS:

Component	Туре	Material	Colour	Finish
LXP2-D	Single lens	PMMA	clear	
LEILA-HLD-OSL	Holder	PC	white	

ORDERING INFORMATION:


» Box size: 480 x 280 x 300 mm

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP12413_LOS-D	Single lens	1680	0	112	9.1





OPTICAL RESULTS (MEASURED):






OPTICAL RESULTS (MEASURED):



LED OSLON SSL 150 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 11.0° / 24.0° Efficiency 87 % Peak intensity 12.7 cd/lm LEDs/each optic Light colour White



OSRAM Opto Semiconductors

Required components:

LED OSLON SSL 80 FWHM / FWTM 10.0° / 24.0° Efficiency 93 % Peak intensity 12.9 cd/lm LEDs/each optic 1 Light colour White Required components:



OPTICAL RESULTS (SIMULATED):

