

## Features

### General Features:

#### Architecture:

- PC/104-Plus compliant

#### Processor Availability:

- Intel® Pentium® M 1.4GHz, 2MB L2 cache, 400MHz FSB

#### Chipset:

- Intel® i855GME

#### System Memory:

- 512MB DDR, 266MHz (PC2100), soldered onboard

#### Supported Operating Systems:

- WinCE®, WinXPE® and Linux®

#### BIOS Flash:

- 1MB Flash EPROM

#### Interfaces:

- IDE ATA 100 Controller
- Serial ports:
  - 1x RS-232
  - 1x RS-232/422/485
- 8x USB 2.0 ports
- 10/100 Mbps Ethernet (Intel® 82562 chipset)
- Graphic controller with analog VGA and Flat Panel LVDS interface
- AC97 audio interface
- Keyboard and Mouse

#### Bus:

- PC/104-Plus (PCI)
- PC/104 (ISA)

#### Watchdog:

- 2-255 seconds / minutes

#### Power Supply:

- Single +5V DC

### RoHS:

- Fully RoHS (2002/95/CE) Compliant



The CPU-1482 is an embedded RoHS compliant board based on two modules: a mezzanine CPU module combined with a PC/104-Plus form factor carrier.

The mezzanine CPU module features the Intel® Pentium® M 1.4GHz (having 2MB L2 cache and 400MHz FSB) processor and its Intel® i855GME chipset. The system comes with 512MB DDR, 266MHz (PC2100), soldered onboard. No active cooling is required to operate within the standard and extended temperature ranges. The carrier implements all the connections to the external world, including 8 USB 2.0 ports, 1 Fast Ethernet interface (10/100Mbps), 2 Serial ports, Analog VGA and Flat Panel LVDS outputs, 1 AC97 interface, Keyboard and Mouse connectors and an IDE controller that supports IDE Flash device (Disk-On-Module, Compact Flash and Flash Disk). The carrier also performs the connections for the ISA and PCI bus enabling the CPU-1482 to stack on top of a PC/104-Plus system. The carrier provides support for Watchdog management and Real Time Clock (external backup battery) and can be customized to match specific customer needs.

The BIOS for the module is embedded and is located in a 1MB Flash EPROM, it is fully re-programmable onboard. The set-up parameters are saved in Flash to allow the module to operate without a battery.

# CPU-1482

## Embedded Enhanced BIOS

- Standard Phoenix BIOS
- Boot Watchdog Management
- Set-Up in Flash in order to avoid Set-Up corruption in field
- Remote console redirection: allows a system with no keyboard and no video hardware to transmit video and keyboard data to a host system via the serial port
- Etherboot support: allows the system to boot up from a LAN connection for diskless operation

## Power Management

- Temperature monitor with hardware thermal management circuit
- Power fail Reset (safe operation between 4.75V and 5.25V)

## About Eurotech

Eurotech delivers embedded computer systems for high capability and low power applications, networking and wearable computing solutions, and application framework middleware for multimedia, industrial, transportation, medical, and wireless applications. Eurotech platforms allow OEM and enterprise customers to focus on their core revenue-generating products and services and get to market quickly.

## Physical Characteristics

DIMENSIONS	90 x 96 mm (3.6" X 3.8")
HEIGHT	18.6 mm (0.7")
POWER SUPPLY	Single +5V DC +/- 5%
POWER CONSUMPTION	14.5W typical
OPERATING TEMPERATURE	0 ~ + 60 °C (standard) -40 ~ + 85 °C (extended)
HUMIDITY	Up to 95% non-condensing

## Accessories

- RJ45 Ethernet adapter
- AC97 adapter
- Digital Flat Panel LVDS receiver
- USB adapters
- Cable Set Kit
- Development Kit

## Options

- Extended operating temperature range
- Custom carrier
- Conformal coating
- Custom Connectors

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.

ETH\_CPU-1482\_DS251108

### Americas

**EUROTECH Inc**  
e-mail: sales-us@eurotech.com  
tel: +1 301.490.4007  
toll free: +1 888.941.2224

### Western Europe

**EUROTECH UK**  
e-mail: sales-uk@eurotech.com  
tel: +44 (0) 1223 403.410

**EUROTECH France**  
e-mail: sales-fr@eurotech.com  
tel: +33 04.72.89.00.90

### Central & Southern Europe

**EUROTECH Italy**  
e-mail: sales-it@eurotech.com  
tel: +39 0433.485.411

### Northern & Eastern Europe

**EUROTECH Finland**  
e-mail: sales-fi@eurotech.com  
tel: +358 9.477.888.0