



- **Flexible Deployment – CoM or SBC**
- **Multi-Core Configurations**
- **Ultra Low Power**
- **HD Multimedia Playback Support**
- **Rugged and Efficient**
- **IoT Native**
- **Long Life-Cycle**

Features

Multi-Core Configurations - The CPU-301-16 offers configurations using single core, dual core or quad core technology to give to device manufacturers the right amount of processing power for their application

CoM or SBC - The CPU-301-16 is available in two versions: as Computer on Module (CoM), to be coupled to a carrier board, and as a standalone Single Board Computer (SBC)

Ultra Low Power - Thanks to Eurotech proprietary power management, the CPU-301-16 can typically operate at 1-2W or less, making it ideal for battery-operated devices and power-constrained uses

HD Multimedia Playback - For applications like kiosk, digital signage, and point of sale, the CPU-301-16 can run up to four independent displays at 1080p

Rugged and Efficient - With optional support for industrial temperature range and enhanced vibration tolerance, at 67x85mm the CPU-301-16 fits into very small enclosures, with little or no need for heat dissipation in low power configurations

IoT Native - Provides native support for IoT, including IoT middleware and access to Eurotech IoT Integration Platform

Long Life-Cycle - With options for extended lifecycle, any design using the CPU-301-16 will have proven supply and support for many years to come

Description

Delivering a full range of capabilities in a low-power and compact design, the CPU-301-16 is the embedded platform of choice for a wide range of applications, such as retail kiosk displays, medical equipment, and control panels for fitness equipment.

The CPU-301-16 uses leading-edge NXP i.MX6 technology to deliver significant functionality into a form factor that allows for efficient packaging and design. Being extremely power efficient, the CPU-301-16 greatly simplifies heat management, allowing fanless designs for most applications.

The CPU-301-16 is available in two versions: as a stand-alone Single Board Computer (no need for a carrier board: just add a power source, the cables and an enclosure to make a smart device) and as a traditional Computer on Module, where the native interfaces are exposed and expanded through a carrier board.

The board support package (BSP) from Eurotech enables the capabilities of the i.MX6 processor, providing an application-ready embedded platform that makes it easy to exploit the full feature set of the module. The CPU-301-16 extends the Eurotech family of products that make IoT applications possible.

With Everyware Software Framework (ESF) and the Everyware Cloud Client loaded on the CPU-301-16, any device using this platform is Everyware Cloud-enabled and ready to be part of the Internet of Things. To learn how the CPU-301-16 can speed time to market and simplify development for sophisticated devices, contact the Eurotech sales team to order a development kit.

Specifications

PROCESSOR	CPU	NXP i.MX6Solo (Single Core ARM Cortex-A9, up to 1.0 GHz) – NXP i.MX6DualLite (Dual Core ARM Cortex-A9, up to 1.0GHz) – NXP i.MX6Dual (Dual Core ARM Cortex-A9, up to 1.2GHz) – NXP i.MX6Quad (Quad Core ARM Cortex-A9, up to 1.2GHz)
MEMORY	RAM	Up to 4GB DDR3L Soldered-down
STORAGE	Embedded	Up to 64GB eMMC Soldered-down
	SATA	1x SATA 2.0 (i.MX6Dual and i.MX6Quad Only)
	Other	On Board Flash Expansion: 1x microSD slot, up to 64GB – Off Board Flash Expansion: 8bit SD port
STAND ALONE SBC I/O INTERFACES	Ethernet	1x 10/100/1000Mbps, with Integrated PHY
	USB	1x USB 2.0, OTG
	Serial	1x RS-232 (2 wire)
	Digital I/O	5x GPIO, 3.3V
	Video	1x HDMI
	I2C	Yes
CoM MODE I/O INTERFACES	Ethernet	1x 10/100/1000Mbps with Integrated PHY, IEEE1588 Support
	USB	2x USB 2.0 (1x Host, 1x OTG)
	Serial	4x UART
	CAN bus	2x CAN bus 2.0
	Digital I/O	21x GPIO, 3.3V (with support for an 8x8 keyboard matrix)
	Video	2x LVDS, 1x RGB, 1x HDMI – Camera Interfaces: MIPI Camera, CMOS Camera (Optional)
	Audio	S/PDIF Audio CODEC Interface
	PCI Express	1x PCIe x1
	I2C	2x I2C bus
POWER	SPI	2x SPI bus
	Input	3.3VDC
	Consumption	1-2W Typ. (5W Max)
	Management	Eurotech Power Management: Sleep/Run/Selective Power Down/Scaling
ENVIRONMENT	Operating Temp	Extended: - 40 to +85°C – Commercial: 0 to +70°C
	Storage Temp	- 40 to +85°C
CERTIFICATIONS	Environmental	RoHS2, REACH
MECHANICAL	Dimensions	67x85mm (LxW)
	CoM Connector	2x Tyco Series, 220 Pin
SOFTWARE	OS	Support for Linux Windows Embedded Compact 7

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.