


**CTW-716312**

**CTW-71638**

Designed for torquing F connectors to a preset torque of 30 in-lb (3.4 N-m), these torque wrenches are perfect for use in high-density locations. Featuring the following:

- Ideal for use in high density locations such as headends.
- Handle has audible click sound that lets you know when the connector is fully torqued to 30 in-lb.
- Turn clockwise to tighten the connector and counterclockwise to remove.
- Preset calibration to 30 in-lb (3.4 N-m) to meet most manufacturers' recommended torque requirements for their F connectors so no adjustments are needed.
- 8" shaft provides easy access to connectors in tight locations
- 12" shaft provides extra length in hard to reach locations.
- Handle has ergonomic rubberized grip for increased comfort and improved leverage.
- CTW-71638 includes: CTW-7168 - 8" Shaft, CTW-H - Handle.
- CTW-716312 includes: CTW-71612 - 12" Shaft, CTW-H - Handle.
- CTW-7163812 includes: CTW-7168 - 8" Shaft, CTW-71612 - 12" Shaft, CTW-H - Handle.

SPECIFICATIONS	CTW-7163812	CTW-71638	CTW-716312	CTW-7168	CTW-71612	CTW-H
<b>PARTS</b>	8" Shaft, 12" Shaft & Handle	8" Shaft & Handle	12" Shaft & Handle	8" Shaft	12" Shaft	Handle
<b>SHAFT LENGTH</b>	8" (20.32 cm) 12" (30.48 cm)	8" (20.32 cm)	12" (30.48 cm)	8" (20.32 cm)	12" (30.48 cm)	N/A
<b>ASSEMBLED LENGTH</b>	8.625" (21.91 cm) 13" (33.0 cm)	8.625" (21.91 cm)	13" (33.0 cm)	N/A	N/A	N/A
<b>SHAFT MATERIAL</b>	Chrome Vanadium Steel	Chrome Vanadium Steel	Chrome Vanadium Steel	Chrome Vanadium Steel	Chrome Vanadium Steel	N/A
<b>WEIGHT</b>	0.428 lb (194 g)	0.304 lb (138 g)	0.326 lb (148 g)	0.090 lb (41 g)	0.117 lb (53 g)	0.212 lb (96 g)
<b>UPC NO.</b>	811490018723	811490018433	811490018426	811490018440	811490018419	811490018402

**MADE FOR LIFE®**