



SUMMARY

CY8CTMA1036/768/460

Automotive TrueTouch[®] Multi-Touch All-Points Touchscreen Controller

Features

- **Automotive Electronics Council (AEC) Q100 qualified**
- **Multi-touch capacitive touchscreen and touchpad controller**
 - 32-bit ARM Cortex CPU
 - Register configurable
 - Noise suppression technologies for display and EMI
 - On-chip 10-V TX supply for higher signal-to-noise ratio (SNR)
 - External display synchronization
 - Water rejection and wet finger tracking
 - Large object rejection
 - Automatic baseline tracking to environmental changes
 - Low-power look-for-touch mode
 - Field upgrades via bootloader
 - Android™ driver support
 - Cypress manufacturing test kit (MTK)
 - Touchscreen sensor self-test and ID reporting
- **System performance**
 - Screen sizes up to 10.1-inch diagonal
 - 5.5-mm sensor pitch, 4:3 aspect ratio
 - Up to 65 sense pins
 - 1036 intersections, 4:3 aspect ratio (37 × 28)
 - Reports up to 10 fingers
 - Small finger support down to 5 mm
 - Large finger support up to 22 mm
 - Refresh rate up to 80 Hz; other rates configurable
 - Fast first-touch response (≤ 37.5 ms for a 10.1-inch panel)
- **Power (configuration dependent)**
 - 1.71-V to 5.5-V digital and I/O supply
 - 2.60-V to 5.5-V analog supply
 - 71-mW average power while sensing
 - 45- μ W typical deep-sleep power
- **Sensor and system design (configuration dependent)**
 - Supports a variety of touchscreen sensors and stackups
 - Manhattan and diamond patterns
 - Sensor-on-lens (SOL)
 - Plastic (PET) and glass sensor substrates
 - LCD and AMOLED displays
 - Single on cell flexible printed circuit (FPC) routing enabled by flexible TX/RX configurations
- **I²C and SPI interface options**
 - I²C slave at all standard bit rates
 - 100 kbps, 400 kbps, 1 Mbps, and 3.4 Mbps
 - SPI slave bit rates up to 8 Mbps
- **Package options**
 - 100-pin TQFP, 14 × 14 × 1.4 mm, 0.5-mm pin-pitch
- **Temperature ranges**
 - Automotive-A: -40 °C to 85 °C
 - Automotive-S: -40 °C to 105 °C

Ordering Information

Table 1 lists the CY8CTMA1036/768/460 TrueTouch touchscreen controllers. For information on other TrueTouch families, visit <http://www.cypress.com/truetouch>.

Table 1. Device Ordering Information

Family	Marketing Part Number	Number of Sense Pins	Number of fingers	Capsense Buttons	Water Rejection	Object Detect and Reject	Glove Support	Gestures	10-V TX	External Display Sync	Package	Package Size	Silicon ID
Low cost	CY8CTMA460AA-13	48	10	✓	✓	✓	✓	-	-	-	100 TQFP	14 × 14 × 1.4 mm	0x01832390
	CY8CTMA460AS-13	48	10	✓	✓	✓	✓	-	-	-	100 TQFP	14 × 14 × 1.4 mm	0x01842390
	CY8CTMA768AA-13	56	10	✓	✓	✓	✓	-	-	-	100 TQFP	14 × 14 × 1.4 mm	0x01752390
	CY8CTMA768AS-13	56	10	✓	✓	✓	✓	-	-	-	100 TQFP	14 × 14 × 1.4 mm	0x01762390
	CY8CTMA1036AA-13	65	10	✓	✓	✓	✓	-	-	-	100 TQFP	14 × 14 × 1.4 mm	0x01772390
	CY8CTMA1036AS-13	65	10	✓	✓	✓	✓	-	-	-	100 TQFP	14 × 14 × 1.4 mm	0x01782390
Gestures	CY8CTMA460AA-23	48	10	✓	✓	✓	✓	✓	-	-	100 TQFP	14 × 14 × 1.4 mm	0x01852390
	CY8CTMA460AS-23	48	10	✓	✓	✓	✓	✓	-	-	100 TQFP	14 × 14 × 1.4 mm	0x01862390
	CY8CTMA768AA-23	56	10	✓	✓	✓	✓	✓	-	-	100 TQFP	14 × 14 × 1.4 mm	0x01792390
	CY8CTMA768AS-23	56	10	✓	✓	✓	✓	✓	-	-	100 TQFP	14 × 14 × 1.4 mm	0x017A2390
	CY8CTMA1036AA-23	65	10	✓	✓	✓	✓	✓	-	-	100 TQFP	14 × 14 × 1.4 mm	0x017B2390
	CY8CTMA1036AS-23	65	10	✓	✓	✓	✓	✓	-	-	100 TQFP	14 × 14 × 1.4 mm	0x017C2390
Base	CY8CTMA460AA-33	48	10	✓	✓	✓	✓	✓	✓	✓	100 TQFP	14 × 14 × 1.4 mm	0x01872390
	CY8CTMA460AS-33	48	10	✓	✓	✓	✓	✓	✓	✓	100 TQFP	14 × 14 × 1.4 mm	0x01882390
	CY8CTMA768AA-33	56	10	✓	✓	✓	✓	✓	✓	✓	100 TQFP	14 × 14 × 1.4 mm	0x017D2390
	CY8CTMA768AS-33	56	10	✓	✓	✓	✓	✓	✓	✓	100 TQFP	14 × 14 × 1.4 mm	0x017E2390
	CY8CTMA1036AA-33	65	10	✓	✓	✓	✓	✓	✓	✓	100 TQFP	14 × 14 × 1.4 mm	0x017F2390
	CY8CTMA1036AS-33	65	10	✓	✓	✓	✓	✓	✓	✓	100 TQFP	14 × 14 × 1.4 mm	0x01802390
Custom	CY8CTMA1036AA-00	65	10	✓	✓	✓	✓	✓	✓	✓	100 TQFP	14 × 14 × 1.4 mm	0x01812390
	CY8CTMA1036AS-00	65	10	✓	✓	✓	✓	✓	✓	✓	100 TQFP	14 × 14 × 1.4 mm	0x01822390

Ordering Code Definitions

