

High Efficiency Standard Rectifier


| 1~ Rectifier | |
|--------------|---------|
| V_{RRM} | = 800 V |
| I_{DAV} | = 124 A |
| I_{FSM} | = 400 A |

1~ Rectifier Bridge


Part number


DLA100B800LB

Marking on Product: DLA100B800LB



Backside: isolated

 E72873



Features / Advantages:

- Planar passivated chips
- Very low leakage current
- Very low forward voltage drop
- Improved thermal behaviour

Applications:

- Diode Bridge for main rectification

Package: SMPD

- Isolation Voltage: 3000 V~
- Industry convenient outline
- RoHS compliant
- Epoxy meets UL 94V-0
- Soldering pins for PCB mounting
- Backside: DCB ceramic
- Reduced weight
- Advanced power cycling

Disclaimer Notice


Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.



| Rectifier | | | | Ratings | | | |
|------------|----------------------------------------------|-----------------------------------|-------------------------|---------|------|------------------|--|
| Symbol | Definition | Conditions | min. | typ. | max. | Unit | |
| V_{RSM} | max. non-repetitive reverse blocking voltage | $T_{VJ} = 25^{\circ}C$ | | | 800 | V | |
| V_{RRM} | max. repetitive reverse blocking voltage | $T_{VJ} = 25^{\circ}C$ | | | 800 | V | |
| I_R | reverse current | $V_R = 800 V$ | $T_{VJ} = 25^{\circ}C$ | | 10 | μA | |
| | | $V_R = 800 V$ | $T_{VJ} = 150^{\circ}C$ | | 0.1 | mA | |
| V_F | forward voltage drop | $I_F = 50 A$ | $T_{VJ} = 25^{\circ}C$ | | 1.23 | V | |
| | | $I_F = 100 A$ | | | 1.45 | V | |
| | | $I_F = 50 A$ | $T_{VJ} = 150^{\circ}C$ | | 1.15 | V | |
| | | $I_F = 100 A$ | | | 1.44 | V | |
| I_{DAV} | bridge output current | $T_C = 135^{\circ}C$ 180° sine | $T_{VJ} = 175^{\circ}C$ | | 124 | A | |
| V_{F0} | threshold voltage | } for power loss calculation only | $T_{VJ} = 175^{\circ}C$ | | 0.75 | V | |
| r_F | slope resistance | | | | 4.2 | m Ω | |
| R_{thJC} | thermal resistance junction to case | | | | 1 | K/W | |
| R_{thCH} | thermal resistance case to heatsink | | | 0.40 | | K/W | |
| P_{tot} | total power dissipation | | $T_C = 25^{\circ}C$ | | 150 | W | |
| I_{FSM} | max. forward surge current | t = 10 ms; (50 Hz), sine | $T_{VJ} = 45^{\circ}C$ | | 400 | A | |
| | | t = 8,3 ms; (60 Hz), sine | $V_R = 0 V$ | | 430 | A | |
| | | t = 10 ms; (50 Hz), sine | $T_{VJ} = 150^{\circ}C$ | | 340 | A | |
| | | t = 8,3 ms; (60 Hz), sine | $V_R = 0 V$ | | 365 | A | |
| I^2t | value for fusing | t = 10 ms; (50 Hz), sine | $T_{VJ} = 45^{\circ}C$ | | 800 | A ² s | |
| | | t = 8,3 ms; (60 Hz), sine | $V_R = 0 V$ | | 770 | A ² s | |
| | | t = 10 ms; (50 Hz), sine | $T_{VJ} = 150^{\circ}C$ | | 580 | A ² s | |
| | | t = 8,3 ms; (60 Hz), sine | $V_R = 0 V$ | | 555 | A ² s | |
| C_J | junction capacitance | $V_R = 400 V; f = 1 MHz$ | $T_{VJ} = 25^{\circ}C$ | | 13 | pF | |



| Package SMPD | | Ratings | | | | |
|----------------|--------------------------------------------------------------|----------------------|------|------|------|------|
| Symbol | Definition | Conditions | min. | typ. | max. | Unit |
| I_{RMS} | RMS current | per terminal | | | 100 | A |
| T_{VJ} | virtual junction temperature | | -55 | | 175 | °C |
| T_{op} | operation temperature | | -55 | | 150 | °C |
| T_{stg} | storage temperature | | -55 | | 150 | °C |
| Weight | | | | 8.5 | | g |
| F_C | mounting force with clip | | 40 | | 130 | N |
| $d_{Spp/ App}$ | creepage distance on surface / striking distance through air | terminal to terminal | 1.6 | | | mm |
| $d_{Spb/ Apb}$ | | terminal to backside | 4.0 | | | mm |
| V_{ISOL} | isolation voltage | t = 1 second | 3000 | | | V |
| | | t = 1 minute | 2500 | | | V |



Part description

- D = Diode
- L = Low Voltage Standard Rectifier
- A = (up to 1200V)
- 100 = Current Rating [A]
- B = 1- Rectifier Bridge
- 800 = Reverse Voltage [V]
- LB = SMPD-B

| Ordering | Ordering Number | Marking on Product | Delivery Mode | Quantity | Code No. |
|-------------|------------------|--------------------|---------------|----------|----------|
| Standard | DLA100B800LB-TUB | DLA100B800LB | Tube | 20 | 514614 |
| Alternative | DLA100B800LB-TRR | DLA100B800LB | Tape & Reel | 200 | 514621 |

Equivalent Circuits for Simulation

* on die level

$T_{VJ} = 175\text{ °C}$





Rectifier

| | | | |
|--------------|--------------------|------|----|
| $V_{0\ max}$ | threshold voltage | 0.51 | V |
| $R_{0\ max}$ | slope resistance * | 1.3 | mΩ |



Outlines SMPD

A (8 : 1)



- Notes:
- 1) protusion may add 0.2 mm max. on each side
 - 2) additional max. 0.05 mm per side by punching misalignment or overlap of dam bar or bending compression
 - 3) DCB area 10 to 50 μm convex; position of DCB area in relation to plastic rim: $\pm 25 \mu\text{m}$ (measured 2 mm from Cu rim)
 - 4) terminal plating: 0.2 - 1 μm Ni + 10 - 25 μm Sn (gal v.) cutting edges may be partially free of plating

