



## DS1100

# 5-Tap Economy Timing Element (Delay Line)

### GENERAL DESCRIPTION

The DS1100 series delay lines have five equally spaced taps providing delays from 4ns to 500ns. These devices are offered in surface-mount packages to save PCB area. Low cost and superior reliability over hybrid technology is achieved by the combination of a 100% silicon delay line and industry-standard  $\mu$ MAX and SO packaging. The DS1100 5-tap silicon delay line reproduces the input-logic state at the output after a fixed delay as specified by the extension of the part number after the dash. The DS1100 is designed to reproduce both leading and trailing edges with equal precision. Each tap can drive up to 10 74LS loads.

Maxim can customize standard products to meet special needs.

### FEATURES

- All-Silicon Timing Circuit
- Five Taps Equally Spaced
- 5V Operation
- Delays are Stable and Precise
- Both Leading- and Trailing-Edge Accuracy
- Improved Replacement for DS1000
- Low-Power CMOS
- TTL/CMOS-Compatible
- Vapor-Phase, IR, and Wave Solderable
- Custom Delays Available
- Fast-Turn Prototypes
- Delays Specified Over Both Commercial and Industrial Temperature Ranges

### PIN ASSIGNMENT



DS1100Z SO (150 mils)  
DS1100U  $\mu$ MAX®

### PIN DESCRIPTION

|                 |                     |
|-----------------|---------------------|
| TAP 1 to TAP 5  | - TAP Output Number |
| V <sub>CC</sub> | - +5V               |
| GND             | - Ground            |
| IN              | - Input             |

## ABSOLUTE MAXIMUM RATINGS

|   |                 |
|---|-----------------|
| Voltage Range on Any Pin Relative to Ground ..... | -0.5V to +6.0V  |
| Short-Circuit Output Current .....                | 50mA for 1s     |
| Operating Temperature Range .....                 | -40°C to +85°C  |
| Storage Temperature Range .....                   | -55°C to +125°C |
| Lead Temperature (soldering, 10s).....            | +300°C          |
| Soldering Temperature (reflow)                    |                 |
| Lead(Pb)-free.....                                | +260°C          |
| Containing lead(Pb) .....                         | +240°C          |

*This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operation sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods of time may affect device reliability.*

## DC ELECTRICAL CHARACTERISTICS

( $V_{CC} = 5.0V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ , unless otherwise noted.)

| PARAMETER                 | SYMBOL   | CONDITIONS                                       | MIN  | TYP  | MAX            | UNITS   | NOTES |
|---------------------------|----------|--|------|------|----------------|---------|-------|
| Supply Voltage            | $V_{CC}$ |  | 4.75 | 5.00 | 5.25           | V       | 5     |
| High-Level Input Voltage  | $V_{IH}$ |  | 2.2  |      | $V_{CC} + 0.3$ | V       | 5     |
| Low-Level Input Voltage   | $V_{IL}$ |  | -0.3 |      | 0.8            | V       | 5     |
| Input-Leakage Current     | $I_I$    | $0.0V \leq V_I \leq V_{CC}$                      | -1.0 |      | 1.0            | $\mu A$ |       |
| Active Current            | $I_{CC}$ | $V_{CC} = \text{Max}; \text{Freq} = 1\text{MHz}$ |      | 30   | 50             | mA      | 6, 8  |
| High-Level Output Current | $I_{OH}$ | $V_{CC} = \text{Min}; V_{OH} = 4$                |      |      | -1             | mA      |       |
| Low-Level Output Current  | $I_{OL}$ | $V_{CC} = \text{Min}; V_{OL} = 0.5$              | 12   |      |                | mA      |       |

## AC ELECTRICAL CHARACTERISTICS

( $V_{CC} = 5.0V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ , unless otherwise noted.)

| PARAMETER   | SYMBOL             | CONDITIONS     | MIN                    | TYP     | MAX | UNITS   | NOTES         |
|---|--------------------|----------------|------------------------|---------|-----|---------|---------------|
| Input Pulse Width   | $t_{WI}$           |                | 20% of Tap 5 $t_{PLH}$ |         |     | ns      | 9             |
| Input-to-Tap Delay Tolerance (Delays $\leq 40\text{ns}$ ) | $t_{PLH}, t_{PHL}$ | +25°C 5V       | -2                     | Table 1 | +2  | ns      | 1, 3, 4, 7    |
|   |                    | 0°C to +70°C   | -3                     | Table 1 | +3  | ns      | 1, 2, 3, 4, 7 |
|   |                    | -40°C to +85°C | -4                     | Table 1 | +4  | ns      | 1, 2, 3, 4, 7 |
| Input-to-Tap Delay Tolerance (Delays $> 40\text{ns}$ )    | $t_{PLH}, t_{PHL}$ | +25°C 5V       | -5                     | Table 1 | +5  | %       | 1, 3, 4, 7    |
|   |                    | 0°C to +70°C   | -8                     | Table 1 | +8  | %       | 1, 2, 3, 4, 7 |
|   |                    | -40°C to +85°C | -13                    | Table 1 | +13 | %       | 1, 2, 3, 4, 7 |
| Power-Up Time   | $t_{PU}$           |                |                        |         | 200 | $\mu s$ |               |
| Input Period  | Period             |                | $2(t_{WI})$            |         |     | ns      | 9             |

## CAPACITANCE

( $T_A = +25^\circ C$ , unless otherwise noted.)

| PARAMETER         | SYMBOL   | CONDITIONS | MIN | TYP | MAX | UNITS | NOTES |
|-------------------|----------|------------|-----|-----|-----|-------|-------|
| Input Capacitance | $C_{IN}$ |            |     | 5   | 10  | pF    |       |



## TERMINOLOGY

**Period:** The time elapsed between the leading edge of the first pulse and the leading edge of the following pulse.

**$t_{WI}$  (Pulse Width):** The elapsed time on the pulse between the 1.5V point on the leading edge and the 1.5V point on the trailing edge, or the 1.5V point on the trailing edge and the 1.5V point on the leading edge.

**$t_{RISE}$  (Input Rise Time):** The elapsed time between the 20% and the 80% point on the leading edge of the input pulse.

**$t_{FALL}$  (Input Fall Time):** The elapsed time between the 80% and the 20% point on the trailing edge of the input pulse.

**$t_{PLH}$  (Time Delay, Rising):** The elapsed time between the 1.5V point on the leading edge of the input pulse and the 1.5V point on the leading edge of any tap output pulse.

**$t_{PHL}$  (Time Delay, Falling):** The elapsed time between the 1.5V point on the trailing edge of the input pulse and the 1.5V point on the trailing edge of any tap output pulse.

## TEST SETUP DESCRIPTION

Figure 3 illustrates the hardware configuration used for measuring the timing parameters on the DS1100. The input waveform is produced by a precision-pulse generator under software control. Time delays are measured by a time interval counter (20ps resolution) connected between the input and each tap. Each tap is selected and connected to the counter by a VHF switch control unit. All measurements are fully automated, with each instrument controlled by a central computer over an IEEE 488 bus.

## TEST CONDITIONS INPUT

|                              |  |
|------------------------------|--|
| Ambient Temperature:         | +25°C ±3°C                                 |
| Supply Voltage ( $V_{CC}$ ): | 5.0V ±0.1V                                 |
| Input Pulse:                 | High = 3.0V ±0.1V<br>Low = 0.0V ±0.1V      |
| Source Impedance:            | 50Ω max                                    |
| Rise and Fall Time:          | 3.0ns max (measured between 0.6V and 2.4V) |
| Pulse Width:                 | 500ns (1μs for -500 version)               |
| Period:                      | 1μs (2μs for -500 version)                 |

## OUTPUT:

Each output is loaded with the equivalent of one 74F04 input gate. Delay is measured at the 1.5V level on the rising and falling edge.

**Note:** Above conditions are for test only and do not restrict the operation of the device under other data sheet conditions.

Figure 3. TEST CIRCUIT



Table 1. DS1100 PART NUMBER DELAY

| PART<br>DS1100-xxx | NOMINAL DELAYS (ns) |       |       |       |       |
|--------------------|---------------------|-------|-------|-------|-------|
|                    | TAP 1               | TAP 2 | TAP 3 | TAP 4 | TAP 5 |
| -20                | 4                   | 8     | 12    | 16    | 20    |
| -25                | 5                   | 10    | 15    | 20    | 25    |
| -30                | 6                   | 12    | 18    | 24    | 30    |
| -35                | 7                   | 14    | 21    | 28    | 35    |
| -40                | 8                   | 16    | 24    | 32    | 40    |
| -45                | 9                   | 18    | 27    | 36    | 45    |
| -50                | 10                  | 20    | 30    | 40    | 50    |
| -60                | 12                  | 24    | 36    | 48    | 60    |
| -75                | 15                  | 30    | 45    | 60    | 75    |
| -100               | 20                  | 40    | 60    | 80    | 100   |
| -125               | 25                  | 50    | 75    | 100   | 125   |
| -150               | 30                  | 60    | 90    | 120   | 150   |
| -175               | 35                  | 70    | 105   | 140   | 175   |
| -200               | 40                  | 80    | 120   | 160   | 200   |
| -250               | 50                  | 100   | 150   | 200   | 250   |
| -300               | 60                  | 120   | 180   | 240   | 300   |
| -500               | 100                 | 200   | 300   | 400   | 500   |

**ORDERING INFORMATION**

| PART            | TEMP RANGE     | PIN-PACKAGE |
|-----------------|----------------|-------------|
| DS1100Z-xxx     | -40°C to +85°C | 8 SO        |
| DS1100Z-xxx/T&R | -40°C to +85°C | 8 SO        |
| DS1100Z-xxx+    | -40°C to +85°C | 8 SO        |
| DS1100Z-xxx+T   | -40°C to +85°C | 8 SO        |
| DS1100U-xxx     | -40°C to +85°C | 8 $\mu$ MAX |
| DS1100U-xxx/T&R | -40°C to +85°C | 8 $\mu$ MAX |
| DS1100U-xxx+    | -40°C to +85°C | 8 $\mu$ MAX |
| DS1100U-xxx+T   | -40°C to +85°C | 8 $\mu$ MAX |

xxx Denotes total time delay (ns) (see Table 1).

+Denotes a lead(Pb)-free/RoHS-compliant package.

T&R and T = Tape and reel.

**PACKAGE INFORMATION**

For the latest package outline information and land patterns (footprints), go to [www.maxim-ic.com/packages](http://www.maxim-ic.com/packages). Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

| PACKAGE TYPE    | PACKAGE CODE | OUTLINE NO.             | LAND PATTERN NO.        |
|-----------------|--------------|-------------------------|-------------------------|
| 8 SO (150 mils) | S8+4         | <a href="#">21-0041</a> | <a href="#">90-0096</a> |
| 8 $\mu$ MAX     | U8+1         | <a href="#">21-0036</a> | <a href="#">90-0092</a> |