

Note: This datasheet may be out of date. Please download the latest datasheet of DXW21BN2511N# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DXW21BN2511N%23

"#" indicates a package specification code.

DXW21BN2511N#


In Production RoHS REACH

< List of part numbers with package codes > DXW21BN2511NB DXW21BN2511NK DXW21BN2511NL



Appearance & Shape







For general



Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	500
К	330mm Embossed Tape	10000
L	180mm Embossed Tape	2000



Features

- 1. Ultra Miniature Wire Wound Transformer (2.0×1.2×1.2mm)
- 2. Low Insertion Loss
- 3. Wideband Frequency Range
- 4. Surface Mount

Applications

TV tuners, Cable TV tuners and Communication application that require unbalance mode to balance mode conversion.

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





DXW21BN2511N#

Note: This datasheet may be out of date. Please download the latest datasheet of DXW21BN2511N# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DXW21BN2511N%23

"#" indicates a package specification code.



Specifications

Operating Temperature Range	-40°C to 85°C	
Frequency Range	13.56MHz	
Insertion Loss	1.0dB max.(at Freq. Range)	
Size Code (in mm)	2012	
Size Code (in inch)	0805	
Length	2mm	
Length Tolerance	±0.2mm	
Width	1.2mm	
Width Tolerance	±0.2mm	
Thickness	1.2mm	
Thickness Tolerance	±0.2mm	
Rated Voltage	20Vdc	
Withstanding Voltage	50Vdc	
Rated Current	250mA	
Port Impedance	25Ω - 25Ω	
CMRR(min.)	40dB	
DC Resistance(max.)	0.5Ω	
Insulation Resistance(min.)	10ΜΩ	
Mass(typ.)	0.011g	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.