

Datasheet revision 1.2

Specifications

www.chipquik.com

48" Metal Power Strip with 12 Outlets, Surge Protected

Specifications		
Power Strip Measurement:	L48" x W1.653" x H1.496" (1219 x 42 x 38mm)*	
Outlets:	12	
Outlet Color:	White	
Outlet Orientation:	Horizontal	
Plug / Receptacle Type:	NEMA 5-15P / 5-15R	
Outlet Spacing:	3-3/4" (95mm) (center to center)	
Power Cord:	6' (1.83m) 14/3 AWG, SJT Heavy Duty	
Voltage Input/Output:	110-125V 60Hz	
Current Input:	15A	
Full Load:	1875VA	
On/Off Switch:	Yes (lighted)	
Circuit Breaker:	Resettable (built in the switch)	
Surge Protection:	Up to 400 Joules	
Lines Protected:	(L-N) (L-G) (N-G)	
Response time:	Less than 5 nanosecond	
Noise Filter:	EMI/RFI	
Mounting on Back:	Yes	
Mounting Tabs:	On both ends (5/8")	
Mounting Clips:	3/4" (19mm) Spring Steel Clips included	
Indicator:	N/A	

Notes

* Measurement is approximate. For installation purposes: The length of the power strip does not include the mounting tabs (approx. 0.624"/15.8mm on both ends), if any; the width does not include the size of screws (min. 0.064"/1.6mm on each side); the height does not include the receptacles (about 0.208"/5.3mm above the surface of the strip).

For use in countries and regions with 110-125V 60Hz only. Not intended for use in or around wet or potentially wet areas.