

2A ER4 industrial disconnect switches

UL/cULus Listed
NEMA 4X (enclosure)

ER4 industrial disconnect switches provide a robust UL98 rated design to withstand long-term corrosive and harsh environments.

The complete line includes both fused and non-fused rotary disconnect switches from 30A to 800A, providing flexibility and convenience for point-of-use configuration.

Applications:

- Built to serve as a main disconnect or provide branch circuit protection in a variety of applications in heavy industrial environments

Features:

- UL98 Listed for general purpose, main disconnect or branch circuit protection up to 600 VAC/DC
- Multiple field installed accessories enhance the enclosed disconnect switches to fit the desired application
- Lockout/tagout – up to three ¼" padlocks can be installed on external handles for added safety

Certifications and compliances:

- UL98 Listed – File No. E182262, Guide WIAX, WIAX7
- cULus Listed to CSA Standard 22.2, No. 14
- cULus Listed to CSA Standard 22.2, No. 4
- Conforms with IEC 60947-3
- CE compliant
- RoHS compliant
- NEMA 4X (enclosure)
- Non-metallic enclosure flammability rating – polycarbonate: UL 94-5VA-0; fiberglass: UL 94-5V



Electrical ratings:

- Voltage – 600 VAC; 250-600 VDC
- Amperage – 16A-800A
- Short circuit current ratings – UL98: 35kA-200kA; UL508: 10kA-65kA
- Operating temperature – -20°C to +70°C

Ordering information:

Part number example
ER4X-60J3PB



Fused disconnects:

| Amperage | Fuse type | Enclosure type | |
|----------|-----------|----------------|---------------------|
| | | 4X plastic | 304 stainless steel |
| 30 | J | ER4P-30J3PB | ER4X-30J3PB |
| 60 | J | ER4P-60J3PB | ER4X-60J3PB |
| 100 | J | ER4P-100J3PB | ER4X-100J3PB |
| 200 | J | ER4P-200J3PB | ER4X-200J3PB |
| 400 | J | ER4P-400J3PB | ER4X-400J3PB |
| 600 | J | ER4P-600J3PB | ER4X-600J3PB |
| 800 | L | ER4P-800L3PB | ER4X-800L3PB |

All catalog numbers provided with integral or installed lugs and black selector handle.

Accessories (ordered separately):

| Cat. # | Description |
|------------------------|--|
| BAC05 ^B | Aux. contact, (1) NO type, 10A, 600 VAC |
| BAC06 ^B | Aux. contact, (1) NC type, 10A, 600 VAC |
| TSH8-3TB ^C | Terminal shroud, 200A switch rating, 3-pole |
| TSH9-3TB ^C | Terminal shroud, 400A switch rating, 3-pole |
| TSH10-3TB ^C | Terminal shroud, 600A-800A switch rating, 3-pole |

^A Class L fuses for 800A disconnect switch only.

^B For 30A-800A switches: maximum number of contacts per switch: (4) 30A to 200A; (8) 400A to 800A.

^C For 200A-800A switches: includes terminal shroud for line side or load side.

^D Two units per switch maximum.

^E For one auxiliary contact, install either BAC03 or BAC11. For two auxiliary contacts, install BAC03 + BAC04, or BAC11 + BAC12.

Non-fused disconnects:

| Amperage | Enclosure type | |
|----------|----------------|---------------------|
| | 4X plastic | 304 stainless steel |
| 30 | ER4P-30N3PB | ER4X-30N3PB |
| 60 | ER4P-60N3PB | ER4X-60N3PB |
| 100 | ER4P-100N3PB | ER4X-100N3PB |
| 200 | ER4P-200N3PB | ER4X-200N3PB |
| 400 | ER4P-400N3PB | ER4X-400N3PB |
| 600 | ER4P-600N3PB | ER4X-600N3PB |
| 800 | ER4P-800N3PB | ER4X-800N3PB |

All catalog numbers provided with integral or installed lugs and black selector handle.

Accessories (ordered separately):

| Cat. # | Description |
|--------------------|--|
| BAC01 ^D | Aux. contact, 30A-100A, (1) NO type, (1) NC type, 10A, 240 VAC |
| BAC02 ^D | Aux. contact, 30A-100A, (2) NO type, 10A, 240 VAC |
| BAC03 ^E | Aux. contact, 220A-800A, (1) NO type, (1) NC type, 10.1A, 125-250 VAC |
| BAC04 ^E | Aux. contact, 220A-800A, (1) NO type, (1) NC type, 10.1A, 125-250 VAC |
| BAC11 ^E | Aux. contact, 220A-800A, (1) NO type, (1) NC type, 1A, 125 VAC |
| BAC12 ^E | Aux. contact, 220A-800A, (1) NO type, (1) NC type, 1A, 125 VAC |
| TSH3-3TB | Terminal shroud, 30A-100A switch rating, line side and load side, 3-pole |
| TSH4-3T | Terminal shroud, 200A switch rating, line side, 3-pole |
| TSH4-3B | Terminal shroud, 200A switch rating, load side, 3-pole |
| TSH5-3T | Terminal shroud, 400A switch rating, line side, 3-pole |
| TSH5-3B | Terminal shroud, 400A switch rating, load side, 3-pole |
| TSH6-3B | Terminal shroud, 600A switch rating, line side or load side, 3-pole |
| TSH7-3TB | Terminal shroud, 800A switch rating, line side or load side, 3-pole |