

Evaluation board for ISOSD61L isolated sigma-delta converter.



Features

- Low voltage differential signaling
- 6 kV galvanic isolation
- 30 kV/ μ s high common-mode transient immunity
- 16-bit resolution, no missing codes
- \pm 320 mV full scale differential input signal range
- Up to 25 MHz external clock input
- High SNR (86 dB) and bandwidth (49 kHz)
- -40°C to $+125^{\circ}\text{C}$ extended industrial temperature range
- Coaxial and header pins available for flexible access to the inputs and outputs
- LVDS digital I/O (ISOSD61L) with on-board termination resistors
- Additional pads for the connection of a shunt current sensor

Description

The EVALST-ISOSD61L is a full-featured evaluation board designed to allow the user to evaluate all the features of the ISOSD61L isolated analog-to-digital converter (ADC).

The ISOSD61L device is a 1-bit sigma-delta modulator with an output buffer separated from the input interface circuitry by a galvanic isolation barrier. The isolation barrier provides galvanic isolation of up to 6000 V_{PEAK} . When used in combination with a digital filter, the ISOSD61L device can be used to achieve 16-bit analog-to-digital (A/D) conversion with no missing codes.

Product status link

[EVALST-ISOSD61L](#)

Revision history

Table 1. Document revision history

Date	Version	Changes
11-Jan-2021	1	Initial release.
15-Jan-2021	2	Title updated.



Contents

Revision history	2
Contents	3