



PE3

(PCIe, TLC, Enterprise)

Product Datasheet

Enterprise Series

PCIe Gen 3 x 4 – 32Gb/s

Commercial Temperature Grade 0°C - 70°C

PE3 Series – PCIe Enterprise Solid State Drive

Product Specification

■ Capacity – PE3 Streaming

- U.2: 960GB~7680GB
- M.2: 240GB~3840GB

■ Capacity – PE3 Pro

- U.2: 960GB~3840GB
- M.2: 480GB~1920GB

■ Capacity – PE3 Max

- U.2: 480GB~1920GB
- M.2: 480GB~960GB

■ Capacity – PE3 Boot

- M.2: 240GB~480GB

■ Components

- Controller: Marvell 88SS1092
- Flash: 3D TLC
- DRAM: LPDDR3 / DDR4

■ Compliance

- PCIe Gen 3 x 4
- Surprise insertion / surprise removal (SISR) and hot-plug capable (U.2 form factor only)
- NCQ: Up to 32 Queue Depth

■ Performance (up to) *

- Sequential Read: 3,200 MB/s
- Sequential Write: 2,000 MB/s
- Random Read: 340,000 IOPS
- Random Write: 30,000 IOPS

■ Power Management

- Auto idle
- PCIe link power management
- Temperature monitoring and throttling

■ Security

- Security erase

■ Reliability

- Advanced LDPC error correction
- Global static and dynamic wear leveling
- UBER: 1 sector per 10^{17} bits read
- MTBF: 2.0 Million Hours

■ Endurance (up to)

- PE3 Streaming: 0.6 DWPD @ 5 Years
(Sequential workload: 2 DWPD @ 5 Years)
- PE3 Pro: 1.5 DWPD @ 5 Years
- PE3 Max: > 5 DWPD @ 5 Years
- PE3 Boot: 1 DWPD @ 5 Years

■ Data Retention

- JESD47 Compliant

■ Compatibility

- Windows 10/8.1/7
- Windows Server 2016/2012 R2/2012
- CentOS, Fedora, FreeBSD, openSUSE, Red Hat, Ubuntu
- VMware ESXi, Citrix, KVM

■ Mechanical Form Factor

- U.2 : 100.5mm x 69.85mm x 7mm
- M.2: 80 mm x 22 mm x 3.6 mm

■ Power Consumption (TYP)

- Active: < 9.0W
- Idle: < 1.5W

■ Environment

- Operating temperature: 0°C ~ 70°C
- Storage temperature: -40°C ~ 85°C

■ Shock & Vibration

- Operating:
50G (11ms duration, half sine wave)
- Non-Operating:
1500G (0.5ms duration, half sine wave)
- Vibration: 10G (Peak, 10~2000Hz)

■ Warranty

- 5 year

Specifications subject to change without notice.

*(1) Actual performance may vary based on hardware, software, and overall system configuration.

(2) Sequential performance is measured with 128KB transfer size, QD 32 and 4KB align with IO Meter.

(3) Random performance is sustained performance measured with 4K/8K transfer size, QD 32 and 4KB align with IO Meter.