


Start > Search=F232200* > F232200

F232200

F232200 : 2 Way 2.8 mm injector and pressure sensor compatible with wire caps



Assistant Add to Favorites Email Datasheet Print Datasheet

FCI Brings You More

Contact our sales/technical support Sample request Price request

Customer Drawing

Specifications

- Direct Link**
- Cross reference
 - RoHS/LF P/N Search
 - Customer drawing search
 - 3D model search
 - Application tooling
- Services**
- Contact us
 - Distributor list
 - Price request
 - Order samples
- Documentation**
- Free search
 - Search by category

General	Mechanical	Physical	Terminal 1 Type	Environmental	Other Features
General					
Application	Component to Wire Injector-Sensor Engine Compartment Connectors				
Ways	2				
Coding version	Black				
Product Type	Housing				
Coding	Yes				
Features	Accepting cable or wire guiding cap mountable by simple snap-on Suitable for all High Pressure Injector Systems 2 W Female Injector Connector High Vibration Design by Compressed interfacial Seal Suitable for Common Rail				
Hybrid	No				
Main Terminal family	DCS-2				
Main Terminal size	2.8 mm				
Sealed	Yes				
Terminal Size	2.8				
Mechanical					
Connector mating force	< 60 N				
Physical					
Color	Black				
Material	PBT				
Temperature (Range)	-40°C to +125°C				
Terminal 1 Type					
Terminal type 1	DCS-2 Female 2.8 mm Terminal				
Ways for Terminal Type 1	2				
Contact insertion force for Terminal Type 1	< 15 N				
Contact Pitch for Terminal Type 1	5 mm				
Retention force (Contact) for Terminal Type 1	> 100N				
Environmental					
IMDS	Yes				
Other Features					
Market	Passenger Vehicles				
Type	Female				
Part Situation	Active				
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.				