

ROSE

21.6 x 21.6 mm single lenses preassembled in durable holders with an adhesive tape

ROSE is a versatile family of single 21.6 x 21.6 mm lenses consisting of ROSE, ROSE-MRK and ROSE-UV subfamilies. All subfamilies have the same dimensions and come preassembled in lightweight and durable holders with a fastening tape that makes their installation fast and easy.


ROSE

Variant made from PC for up to 5050 size LED packages



PRODUCTS:


RES-RS



Dimensions: 21.6 mm x 21.6 mm Height: 12.90 mm ~11° spot beam for LUXEON Rebel.

Assembly with white holder.


CA10569_OSS-2-M



Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm

~30° medium beam optimized for Osram Golden Dragon+. Assembly with white holder.

FA10299_OSS-RS




Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm

~11° spot beam optimized for Osram Golden Dragon+. Assembly with white holder.




PRODUCTS:

RES-O



Dimensions: 21.6 mm x 21.6 mm Height: 12.90 mm ~45° + 15° oval beam for LUXEON Rebel. Assembly with white holder.


CA10561_OSS-2-RS



Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm


~11° spot beam optimized for Osram Golden Dragon+. Assembly with white holder.

CA13617_G2-OSS-2-WWW



Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm ~80° very wide beam optimized for Osram Golden Dragon+. G2 assembly

RES-SS



Dimensions: 21.6 mm x 21.6 mm Height: 12.90 mm

~15° smooth spot beam optimized for LUXEON Rebel. Assembly with white holder.


CA10560_OSS-2-SS

Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm

PMMA lens with ~15° smooth spot beam optimized for Osram Golden Dragon+. Assembly with white holder.

CA13614_G2-OSS-2-M

with light, white holder.




Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm

~25° medium beam optimized for Osram Golden Dragon+. G2 assembly with light, white holder.



PRODUCTS:


RES-D



Dimensions: 21.6 mm x 21.6 mm Height: 12.90 mm

~16° diffused spot beam optimized for LUXEON Rebel. Assembly with white holder.


FA10344_NIS83-MX-W



Dimensions: 21.6 mm x 21.6 mm Height: 13.50 mm

~50° wide beam optimized for Nichia NS6x83. Assembly with white holder.


CA13613_G2-OSS-2-RS



Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm

~11° spot beam optimized for Osram Golden Dragon+. G2 assembly with light, white holder.


RES-M



Dimensions: 21.6 mm x 21.6 mm Height: 12.90 mm


~30° medium beam optimized for LUXEON Rebel. Assembly with white holder.

FA10342_OSS-W



Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm ~50° wide beam optimized for Osram Golden Dragon+. Assembly with white holder.

CA13612_G2-OSS-2-SS




Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm ~15° smooth spot beam optimized for Osram Golden Dragon+. G2 assembly with light, white holder.




PRODUCTS:

FA10708_CXP-W



Dimensions: 21.6 mm x 21.6 mm Height: 13.15 mm ~50° wide beam optimized for CREE XP-E. Assembly with black holder.


FA10340_NIS83-MX-O



Dimensions: 21.6 mm x 21.6 mm Height: 13.50 mm ~45° x 15° oval beam optimized for


Nichia NS6x83. Assembly with 13.5 mm high white holder.

FA11911_CXM-M



Dimensions: 21.6 mm x 21.6 mm Height: 12.90 mm ~30° medium beam optimized for CREE XM-L. Assembly with white holder.


FA10676_CMC-M



Dimensions: 21.6 mm x 21.6 mm Height: 13.80 mm ~30° medium beam optimized for CREE

MC-E. Assembly with black holder.


FA10339_NIS83-MX-M



Dimensions: 21.6 mm x 21.6 mm Height: 13.50 mm

~30° medium beam optimized for Nichia NS6x83. Assembly with white holder and installation tape.

FA11909_CXM-RS




Dimensions: 21.6 mm x 21.6 mm Height: 12.90 mm ~11° spot beam optimized for CREE XM-L. Assembly with white holder.



PRODUCTS:

FA10669_CXP-O




Dimensions: 21.6 mm x 21.6 mm Height: 13.15 mm ~45° + 15° oval beam optimized for CREE XP-E. Assembly with black holder.

FA10336_NIS83-MX-RS




~11° spot beam optimized for Nichia NS6x83. Assembly with white holder and installation tape.

FA11908_CXM-SS




Dimensions: 21.6 mm x 21.6 mm Height: 12.90 mm ~15° smooth spot beam optimized for CREE XM-L. Assembly with white holder.

FA10668_CXP-RS



Dimensions: 21.6 mm x 21.6 mm Height: 13.15 mm ~11° spot beam optimized for CREE XP-E. Assembly with black holder.


FA10327_OSS-SS



Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm ~15° smooth spot beam optimized for

Osram Golden Dragon+. Assembly with white holder and installation tape.

FA11145_OSS-O-90




Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm

~13° + 45° oval beam optimized for Osram Golden Dragon+. Variant with beam direction rotated 90°. Assembly with white holder.




PRODUCTS:

FA10667_CXP-SS



Dimensions: 21.6 mm x 21.6 mm Height: 13.15 mm ~15° smooth spot beam optimized for CREE XP-E. Assembly with black holder.


FA10302_OSS-O



Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm


~45° + 15° oval beam optimized for Osram Golden Dragon+. Assembly with white holder.

FA10903_NIS83-MX-WW




Dimensions: 21.6 mm x 21.6 mm Height: 13.50 mm ~60° wide beam optimized for Nichia NS6x83. Assembly with white holder.

FA10665_CXP-M



Dimensions: 21.6 mm x 21.6 mm Height: 13.15 mm ~30° medium beam optimized for CREE XP-E. Assembly with black holder.

FA10301_OSS-M



Dimensions: 21.6 mm x 21.6 mm Height: 13.90 mm ~30° medium beam optimized for Osram Golden Dragon+. Assembly with white holder.