

SEANNA-A

~2.3° spot beam. Assembly with holder.

SPECIFICATION:

Dimensions Ø 155.2 mm
Height 82 mm
Fastening pin, screw
ROHS compliant yes ①



MATERIALS:


Component	Туре	Material	Colour	Finish
SEANNA-FRES	Single lens	PMMA	clear	
SEANNA-A	Single lens	PMMA	clear	
SEANNA-HLD-B-BOTTOMRING	Holder	PA66GF30	black	
SEANNA-HLD-B-TOPRING	Holder	PA66GF30	black	
SEANNA-HLD-B	Holder	PA66GF30	black	
SEANNA-SCREW	Accessory	Stainless steel	clear	

ORDERING INFORMATION:

Component	Qty	in box MOQ	MPQ	Box weight (kg)
FCP13895_SEANNA-A » Box size:	Single lens	20	2	6.5




PRODUCT DATASHEET FCP13895_SEANNA-A



See also our general installation guide: www.ledil.com/installation_guide




OPTICAL RESULTS (MEASURED):






OPTICAL RESULTS (MEASURED):






CREE 1 LED

LED MK-R
FWHM / FWTM 4.0° / 10.4°
Efficiency 91 %
Peak intensity 82 cd/lm
LEDs/each optic 1
Light colour White
Required components:



CREE & LED

LED XB-D
FWHM / FWTM 1.3° / 3.2°
Efficiency 87 %
Peak intensity 698 cd/lm
LEDs/each optic 1
Light colour White
Required components:




CREE \$ LED

LED XHP35 HD
FWHM / FWTM 2.4° / 4.2°
Efficiency 89 %
Peak intensity 257 cd/lm
LEDs/each optic 1
Light colour White
Required components:

CREE - LED

LED XHP35 HI
FWHM / FWTM 1.6° / 3.6°
Efficiency 83 %
Peak intensity 496 cd/lm
LEDs/each optic 1
Light colour White
Required components:







 LED
 XHP35.2 HD


 FWHM / FWTM
 2.0° / 6.0°

 Efficiency
 89 %

 Peak intensity
 161.9 cd/lm

LEDs/each optic 1
Light colour White


Required components:



CREE + LED

LED XHP35.2 HI
FWHM / FWTM 2.0° / 4.0°
Efficiency 89 %
Peak intensity 161 cd/lm
LEDs/each optic 1
Light colour White


Required components:



CREE + LED

LED XHP50
FWHM / FWTM 3.3° / 6.7°
Efficiency 87 %
Peak intensity 122 cd/lm
LEDs/each optic 1
Light colour White

Required components:



CREE - LED

 LED
 XHP50.2


 FWHM / FWTM
 2.7° / 6.8°

 Efficiency
 84 %

 Peak intensity
 128.7 cd/lm

 LEDs/each optic
 1

Light colour White Required components:





Peak intensity


Light colour

LEDs/each optic

Required components:

275 cd/lm

White







 LED
 XM-L3


 FWHM / FWTM
 2.0° / 6.0°

 Efficiency
 90 %

Peak intensity 196.2 cd/lm

LEDs/each optic 1
Light colour White

Required components:




CREE - LED

LED XP-E FWHM / FWTM 1.2° / 2.9°

Efficiency 92 % Peak intensity 955 cd/lm

LEDs/each optic 1
Light colour White

Required components:



CREE + LED


 LED
 XP-E2

 FWHM / FWTM
 2.0° / 6.0°

 Efficiency
 85 %

Peak intensity 211.5 cd/lm

LEDs/each optic 1
Light colour Blue
Required components:



CREE - LED


 LED
 XP-G

 FWHM / FWTM
 1.4° / 3.4°

 Efficiency
 90 %

 Peak intensity
 578 cd/lm

LEDs/each optic 1
Light colour White
Required components:








Peak intensity 628 cd/lm
LEDs/each optic 1
Light colour White

Required components:



CREE + LED

 LED
 XP-G2 HE


 FWHM / FWTM
 2.0° / 4.0°

 Efficiency
 89 %

 Peak intensity
 286.5 cd/lm

LEDs/each optic 1
Light colour White

Required components:



CREE 1 LED


 LED
 XP-G3

 FWHM / FWTM
 2.0° / 4.0°

 Efficiency
 88 %

 Peak intensity
 246.2 cd/lm

LEDs/each optic 1
Light colour White
Required components:



CREE - LED


 LED
 XP-P

 FWHM / FWTM
 2.0° / 6.0°

 Efficiency
 84 %

 Peak intensity
 246.8 cd/lm


LEDs/each optic 1
Light colour White
Required components:





CREE . LED

LED XQ-E HD
FWHM / FWTM 1.1° / 2.5°
Efficiency 92 %
Peak intensity 1460 cd/lm
LEDs/each optic 1
Light colour White




CREE & LED

Required components:

LED XQ-E HI
FWHM / FWTM 1.2° / 2.0°
Efficiency 90 %
Peak intensity 1300 cd/lm
LEDs/each optic 1
Light colour White
Required components:

CREE \$ LED


LED XT-E
FWHM / FWTM 1.4° / 3.5°
Efficiency 88 %
Peak intensity 519 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED ENGIN

Required components:

LED LZ4 (00xW00)
FWHM / FWTM 3.3° / 8.2°
Efficiency 91 %
Peak intensity 136 cd/lm
LEDs/each optic 1
Light colour White












LED LUXEON CZ
FWHM / FWTM 1.3° / 3.4°
Efficiency 94 %
Peak intensity 564 cd/lm
LEDs/each optic 1

Light colour PC Amber

Required components:




MUMILEDS

LED LUXEON HL2X
FWHM / FWTM 2.0° / 4.0°
Efficiency 89 %
Peak intensity 317.8 cd/lm
LEDs/each optic 1

LEDs/each optic 1
Light colour White


Required components:



DESCRIPTION LUMILEDS

LED LUXEON M/MX
FWHM / FWTM 3.6° / 9.0°
Efficiency 89 %
Peak intensity 99 cd/lm
LEDs/each optic 1
Light colour White

Required components:



DESCRIPTION LUMILEDS

LED LUXEON MZ
FWHM / FWTM 2.2° / 6.0°
Efficiency 84 %
Peak intensity 151 cd/lm
LEDs/each optic 1
Light colour White
Required components:





 LED
 LUXEON Rebel


 FWHM / FWTM
 1.3° / 3.2°

 Efficiency
 90 %

 Peak intensity
 704 cd/lm

LEDs/each optic 1
Light colour White

Required components:




LUMILEDS

LED LUXEON Rebel ES

FWHM / FWTM 1.6° / 3.6°
Efficiency 90 %
Peak intensity 530 cd/lm
LEDs/each optic 1
Light colour White

Required components:



LUMILEDS

 LED
 LUXEON Rubix


 FWHM / FWTM
 2.0° / 4.0°

 Efficiency
 88 %

 Peak intensity
 290.2 cd/lm

LEDs/each optic 1
Light colour White

Required components:



MILEDS


 LED
 LUXEON Rubix

 FWHM / FWTM
 2.0° / 6.0°

 Efficiency
 85 %

 Peak intensity
 196.2 cd/lm

LEDs/each optic 1
Light colour Red
Required components:








LED LUXEON Rubix
FWHM / FWTM 2.0° / 6.0°
Efficiency 83 %
Peak intensity 157.7 cd/lm

LEDs/each optic 1
Light colour Green


Required components:



MUMILEDS

LED LUXEON Rubix
FWHM / FWTM 2.0° / 6.0°
Efficiency 83 %
Peak intensity 141.9 cd/lm

LEDs/each optic 1
Light colour Blue
Required components:



LUMILEDS

 LED
 LUXEON \$1000


 FWHM / FWTM
 3.8° / 8.0°

 Efficiency
 88 %

 Peak intensity
 100 cd/lm

 LEDs/each optic
 1

Light colour White Required components:



DESCRIPTION LUMILEDS


 LED
 LUXEON V2

 FWHM / FWTM
 2.0° / 4.0°

 Efficiency
 88 %

 Peak intensity
 250.1 cd/lm

LEDs/each optic 1
Light colour White
Required components:







 LED
 SBT-90


 FWHM / FWTM
 2.0° / 6.0°

 Efficiency
 76 %

Peak intensity 175.9 cd/lm LEDs/each optic 1

Light colour White

Required components:



ELUMINUS

 LED
 SBT-90


 FWHM / FWTM
 2.3° / 4.8°

 Efficiency
 90 %

 Peak intensity
 253 cd/lm

LEDs/each optic 1
Light colour White

Required components:



WNICHIA

 LED
 NV4WB35AM


 FWHM / FWTM
 2.0° / 4.0°

 Efficiency
 90 %

 Peak intensity
 185.5 cd/lm

LEDs/each optic 1
Light colour White


Required components:



WNICHIA

LED NVSW219F
FWHM / FWTM 2.0° / 4.0°
Efficiency 89 %
Peak intensity 296 cd/lm
LEDs/each optic 1
Light colour White

Required components:








LED NVSW519A FWHM / FWTM 2.0° / 4.0° Efficiency 89 % Peak intensity 251.6 cd/lm LEDs/each optic

Light colour White

Required components:




WNICHIA

LED NVSW719AC FWHM / FWTM 2.0° / 6.0° Efficiency 85 % Peak intensity 207.3 cd/lm

LEDs/each optic 1 White Light colour

Required components:



OSRAM Opto Semiconductor


LED

OSCONIQ C 2424

FWHM / FWTM 2.0° / 4.0° Efficiency 90 % Peak intensity 241.6 cd/lm

LEDs/each optic Light colour White

Required components:



OSRAM

LED OSCONIQ P 3737 (2W version)

FWHM / FWTM 2.0° / 4.0° Efficiency 89 % Peak intensity 258.2 cd/lm

LEDs/each optic White Light colour Required components:




OSRAM

LED OSCONIQ P 3737 (3W version)

FWHM / FWTM 2.0° / 4.0° Efficiency 90 % Peak intensity 232.3 cd/lm

LEDs/each optic Light colour White

Required components:




OSRAM

LED OSCONIQ P 7070

FWHM / FWTM 3.5° / 7.1° Efficiency 91 % Peak intensity 122.2 cd/lm

LEDs/each optic 1 White Light colour

Required components:




OSRAM Opto Semiconductor

LED OSLON Boost HX (KW CULPM1.TG)

FWHM / FWTM 2.0° / 6.0° Efficiency 92 % Peak intensity 176.8 cd/lm

LEDs/each optic Light colour White

Required components:




OSRAM

LED OSLON Square PC

FWHM / FWTM 1.5° / 3.6° 89 % Efficiency Peak intensity 550 cd/lm LEDs/each optic White Light colour

Required components:





OSRAM

LED OSRAM OSTAR Projection Compact (KW CSLPM1.TG)


 FWHM / FWTM
 2.0° / 4.0°

 Efficiency
 90 %

 Peak intensity
 229.3 cd/lm

LEDs/each optic 1
Light colour White

Required components:



SAMSUNG

 LED
 LH351B


 FWHM / FWTM
 2.0° / 4.0°

 Efficiency
 90 %

 Peak intensity
 279.4 cd/lm

LEDs/each optic 1
Light colour White

Required components:



SAMSUNG

 LED
 LH351C


 FWHM / FWTM
 2.0° / 4.0°

 Efficiency
 91 %

 Peak intensity
 279.2 cd/lm

LEDs/each optic 1
Light colour White

Required components:



SAMSUNG

 LED
 LH351D

 FWHM / FWTM
 2.0° / 4.0°

 Efficiency
 91 %

 Peak intensity
 235.3 cd/lm

LEDs/each optic 1
Light colour White

Required components:

