

FLORENTINA-2X2-RS

~10° spot beam

SPECIFICATION:

Dimensions	89.6 x 89.6 mm
Height	22.2 mm
Fastening	pin, screw
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
ROSE-B-B-RS	Single lens	PC	clear	
FLORENTINA-2X2-HLD	Holder	PC	black	

ORDERING INFORMATION:









Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCP14965_FLORENTINA-2X2-RS	Single lens	88	24	8	4.3
» Box size: 476 x 273 x 292 mm					





See also our general installation guide: www.ledil.com/installation_guide



OPTICAL RESULTS (MEASURED):

<p>COMET ELECTRONICS</p> <p>LED EASY-T FLUX 2x2 FLR XG xxx G7</p> <p>FWHM / FWTM 11.0° / 25.0°</p> <p>Efficiency 86 %</p> <p>Peak intensity 13 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>CREE LEDs</p> <p>LED XHP35 HD</p> <p>FWHM / FWTM 17.0° / 33.0°</p> <p>Efficiency 83 %</p> <p>Peak intensity 6.8 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: C14734_FLORENTINA-2X2-SHD</p>		
<p>CREE LEDs</p> <p>LED XHP35 HD</p> <p>FWHM / FWTM 17.0° / 33.0°</p> <p>Efficiency 85 %</p> <p>Peak intensity 6.8 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: C14960_FLORENTINA-2X2-SHD-WHT</p>		
<p>CREE LEDs</p> <p>LED XHP35 HD</p> <p>FWHM / FWTM 17.0° / 32.0°</p> <p>Efficiency 86 %</p> <p>Peak intensity 7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		



OPTICAL RESULTS (MEASURED):




LED XP-L HD
 FWHM / FWTM 16.0° / 27.0°
 Efficiency 82 %
 Peak intensity 8.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14734_FLORENTINA-2X2-SHD





LED XP-L HD
 FWHM / FWTM 16.0° / 27.0°
 Efficiency 83 %
 Peak intensity 8.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14960_FLORENTINA-2X2-SHD-WHT



LED LUXEON TX
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 86 %
 Peak intensity 17.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14960_FLORENTINA-2X2-SHD-WHT



LED LUXEON TX
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 85 %
 Peak intensity 17.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14734_FLORENTINA-2X2-SHD





OPTICAL RESULTS (MEASURED):

OSRAM

Opto Semiconductors



LED OSLON Square EC
 FWHM / FWTM 10.0° / 21.0°
 Efficiency 85 %
 Peak intensity 18.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14960_FLORENTINA-2X2-SHD-WHT



OSRAM

Opto Semiconductors

LED OSLON Square EC
 FWHM / FWTM 10.0° / 21.0°
 Efficiency 84 %
 Peak intensity 18.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14734_FLORENTINA-2X2-SHD



SAMSUNG

LED HiLOM SC16 (LH181B)
 FWHM / FWTM 21.0° / 48.0°
 Efficiency 60 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14734_FLORENTINA-2X2-SHD

