HellermannTyton

Specification Sheet

Part Number: FERM36S



Removable front and rear covers provide easy access to cables Slide-out tray with easy-to-grip raised edge

Cable management spools for effective slack management

Optional splice trays to assist with cable splicing

Panel positioning for easier patch cords access

Round edge plastic fiber saddles for easier patch-cord routing

Meet ANSI/TIA/EIA 568-C standards

Rack Mount Fiber Enclosure-Unloaded, Accepts 6 LGX Adapter Panels, 2U, Black, 1/pkg

Article Number	855-49201
Туре	FERM36S
Color	Black (BK)
Quantity Per	box
Product Description	HellermannTyton's rack mount fiber enclosures are the ideal direct termination and splice solution of LAN applications capable of supporting up to 72 fibers. While offering easy-to-use front slide-out trays for effortless access to connections, enclosures are equipped with cable management and cable routing accessories to limit bend radius and add strain relief control. HellermannTyton's Rack Mount Fiber Enclosures easily fit into 19" or 23" racks.

Short Description	Rack Mount Fiber Enclosure-Unloaded, Accepts 6 LGX Adapter Panels, 2U, Black, 1/pkg
Global Part Name	FERM36S
Technical Description	Rack Mount Fiber Enclosure-Unloaded, Accepts 6 Adapter Panels for Fiber Counts 36/48, 2U, BK
Port Count	24 48 96
Length L (Imperial)	12.14
Length L (Metric)	308.4
Variant	Rack mount
Width W (Imperial)	17.0
Width W (Metric)	431.8
Height H (Imperial)	3.50
Height H (Metric)	88.90
Depth D (Imperial)	12.14
Depth D (Metric)	308.36