



# FlexiForce™ Load Concentrators

These peel-and-stick, delrin load concentrators are used to evenly distribute force across a FlexiForce sensor's sensing region, helping you optimize sensor linearity and repeatability.

<b>Material</b>	Delrin® Acetal Plastic
<b>Texture</b>	Smooth
<b>Thickness</b>	0.31"
<b>Hardness</b>	Rockwell R120-R122
<b>Hardness Rating</b>	Hard
<b>Temperature Range</b>	-20° to 180° F
<b>Color</b>	Black
<b>Backing Tape</b>	3M 9482PC

FlexiForce load concentrators are available in 10-packs with a peel-and-stick coating. There are two diameters:

## FLXLC-A

7.1 mm diameter (0.28 in.)  
0.7 mm thickness (0.03 in.)

## FLXLC-B

19.1 mm diameter (0.75")  
0.7 mm thickness (0.03 in.)



 **PURCHASE TODAY ONLINE AT [WWW.TEKSCAN.COM/STORE](http://WWW.TEKSCAN.COM/STORE)**



©Tekscan Inc., 2022. All rights reserved. Tekscan, the Tekscan logo, and FlexiForce are trademarks or registered trademarks of Tekscan, Inc.

+1.617.464.4283 | 1.800.248.3669 | [info@tekscan.com](mailto:info@tekscan.com) | [Tekscan.com/FlexiForce](http://Tekscan.com/FlexiForce)