

## SUMMARY

### # Wires

Low voltage	2
High voltage	2
Fiber optic	2

Series	3K
Termination type	Hybrid contacts
IP rating	68 when mated
AWG wire size	24.00 - 20.00
Cable Ø	8.90 - 9.50 mm
Status	active
Matching parts	<a href="#">PUW.3K.93C.YSEC96</a>



Image is for illustrative purpose only

### Download

[Request a quote](#)

[Catalog](#)

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model	FU*: Straight plug 'Y' new design, cable collet adapter and long shell for fitting a bend relief with cap (with enhanced screen efficiency)
Keying	5 keys (alpha=95, beta=115, gamma=20, delta=30, plug: female LV, male HV, female FO contacts)
Housing Material	Special housing (see notes for details)
Weight	98.93 g

### Performance

Configuration	3K.93C : 2 FO Type F2, 2 HV + 2 LV
Insulator	
Rated Current	10 Amps

### Specifications


Fiber Optic Contact: Type F2  
Vtest power/signal (AC): 2250V , 1000V  
Working voltage power/signal(AC): 600V , 42V  
Cable type: SMPTE 311M or EBU R100

### Others

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Endurance (Shell): 20000 mating cycles  
 Temp (min / max): -40°C / +80°C  
 Humidity (max): <=95% [at 60 deg C / 140 F]  
 Vibration: 15 g [10 Hz - 2000 Hz]  
 Shock Resistance: 100 g [ 6 ms]  
 Climatical Category: 50/175/21  
 Shielding (min): 95 dB (10 MHz)  
 Shielding (min): 80 dB (1 GHz)

## DRAWINGS



### Dimensions

	A	L	M
mm.	19.5	94	74
in.	0,77	3,70	2,91

## RECOMMENDED BY LEMO

### Tools

Crimp settings:                   AWG/Selector = 14-16-18 20-22-24/7-6-5 6-5-5  
 Positionner:                       [DCE.91.093.BVC](#)  
 Positionner 2:                    [DCE.91.133.BVCM](#)  
 Extractor:                         [DCC.09.05B.LAG](#)

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*