



E502650

Features

- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix Designates Compliant. See Ordering Information)
- Low Forward Voltage Drop, High Current Capability
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1

**15 Amp Low VF
Glass Passivated
Bridge Rectifier
600 - 800 Volts**

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Typical Thermal Resistance: 0.8°C/W Junction to case With Heatsink
- Typical Thermal Resistance: 22°C/W Junction to Ambient Without Heatsink

Mechanical Data


- Mounting Torque: 5in-lbs

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
GBJ1506L	GBJ1506L	600V	420V	600V
GBJ1508L	GBJ1508L	800V	560V	800V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	15A	$T_C = 110^\circ C$
Peak Forward Surge Current	I_{FSM}	380A	8.3ms, Half Sine
Maximum Instantaneous Forward Voltage	V_F	0.92V	$I_{FM} = 7.5A; T_J = 25^\circ C$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	5µA 150µA	$T_J = 25^\circ C$ $T_J = 125^\circ C$
Rating for Fusing	I^2t	599 A ² s	t<8.3ms

Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7a.



DIM	DIMENSIONS				NOTE	
	INCHES		MM			
	MIN	MAX	MIN	MAX		
A	1.170	1.190	29.70	30.30		
B	0.780	0.800	19.70	20.30		
C	0.670	0.710	17.00	18.00		
D	0.190	0.190	4.70	4.90		
E	0.430	0.440	10.80	11.20		
F	0.090	0.110	2.30	2.70		
G	0.120	0.130	3.10	3.40		
H	0.130	0.150	3.40	3.80		
I	0.170	0.190	4.40	4.80		
J	0.100	0.110	2.50	2.90		
K	0.020	0.030	0.60	0.80		
L	0.080	0.090	2.00	2.40		
M	0.040	0.040	0.90	1.10		
N	0.390	0.400	9.80	10.20		
O	0.290	0.300	7.30	7.70		
P	0.150	0.170	3.80	4.20		

Curve Characteristics

Fig. 1 - Forward Current Derating Curve




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 4 - Typical Reverse Leakage Characteristics

