

# Ceramic High Pass Filter

## HFCG-2100+

50Ω      2200 to 6000 MHz



CASE STYLE: GE0805C-2

### The Big Deal

- Small size 2.0 mm x 1.25 mm
- High Power handling
- High rejection
- Ceramic construction

### Product Overview

The HFCG-2100+ LTCC High Pass Filter is constructed with 11 layers in order to achieve a miniature size and high repeatability of performance. Wrap-around terminations minimize variations in performance due to parasitics. Covering 2200-6000 MHz, these units offer low insertion loss and good rejection.

### Key Features

Feature	Advantages
Small Size (2.0 mm x 1.25 mm)	Allows for high layout density of circuit boards, while minimizing effects of parasitic.
Wrap around termination	Provides excellent solderability and easy visual inspection capability.
LTCC construction	Provides a rugged package that is well suited for tough environments including high humidity and high temperature extremes.

#### Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.  
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.  
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



# Ceramic High Pass Filter

50Ω 2200 to 6000 MHz

## HFCG-2100+



CASE STYLE: GE0805C-2

**+RoHS Compliant**

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Features

- Small size
- Temperature stable
- LTCC construction
- Excellent power handling, 3W

### Applications


- Transmitters / Receivers
- Global positioning system(GPS)
- Satellite broadcast applications
- Wireless local area Network

### Electrical Specifications<sup>(1,2)</sup> at 25°C

Parameter		F#	Frequency (MHz)	Min.	Typ.	Max.	Unit
Stop Band	Rejection Loss	DC-F1	DC-1050	40	50	-	dB
		DC-F2	DC-1320	22	33	-	dB
	Freq. Cut-Off	F3	2100	-	3.0	-	dB
	VSWR	DC-F2	DC-1320	-	20	-	:1
Pass Band	Insertion Loss	F4-F7	2200-6000	-	2.0	-	dB
		F5-F6	2500-5000	-	1.0	1.8	dB
	VSWR	F5-F6	2500-5000	-	1.6	-	:1

(1) In Application where DC voltage is present at either input or output ports, coupling capacitors are required.  
 (2) Measured on Mini-Circuits Characterization Test Board TB-1090+.

### Functional Schematic




### Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power Input*	3W Max.




\*Passband rating, derate linearly to 1.5W at 85°C ambient  
 Permanent damage may occur if any of these limits are exceeded.

### Typical Frequency Response



### Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)
10	90.29	119.46
250	73.97	78.73
700	61.85	55.19
950	63.25	48.04
1050	51.11	45.31
1320	33.69	37.01
1380	30.65	35.35
1600	20.59	25.99
1700	16.35	20.50
1900	8.52	9.15
2100	3.07	2.99
2110	2.90	2.84
2200	1.80	1.90
2300	1.21	1.41
2500	0.84	1.17
3000	0.58	1.10
3040	0.56	1.09
5000	0.50	1.39
5600	0.76	1.77
6000	0.97	0.00



#### Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.  
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.  
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



[www.minicircuits.com](http://www.minicircuits.com) P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. OR  
 M170934  
 HFCG-2100+  
 EDU3268  
 URJ  
 190306  
 Page 2 of 3