

# IDS-3315

## 15" XGA Front IP65 Industrial Monitor

NEW



### Features

- Front IP65 for waterproof and dustproof
- 15" XGA LCD panel with LED backlight for 20% power saving and environmental protection
- -20 ~ +60 °C wide range operating temperature
- 5-wire resistive and P-cap touchscreen solution or tempered smudge resistant protected glass
- Multiple signal interfaces with HDMI, VGA & DVI
- Standard integrated frame
- Versatile mounting methods for rear mounting and VESA mounting
- Anti-Reflective treatment (optional)
- Ultra high brightness solution of 1200 cd/m<sup>2</sup> for outdoor applications

### Introduction


The Advantech IDS-3315 Embedded Industrial Panel Mount Monitor series offers flexible options for LCD, touchscreen, signal interface and chassis mounting. The series provides not only IP65 ingress rating at the front surface, but also with standard integrated frame design, supporting rear and VESA mounting which brings the benefits of easy installation and provides flexibility for different applications.

### Specifications

Display	Model	IDS-3315
	Size	15" LED panel
	Resolution	1024 x 768 (XGA)
	Viewing Angle	88°/88° (H), 88°/88° (V)
	Brightness	500 / 1200 (cd/m <sup>2</sup> before glass/touch screen)
	Color Support	16.7M/262K
	Contrast Ratio	2500:1
	Response Time	16 [msec]
	Backlight Life (hrs)	50,000 hrs
Touchscreen	Touchscreen Type	5-Wire Resistive Touchscreen / Projected Capacitive Touchscreen
	Surface Hardness	3H / Mohs 5
	Durability	10 million touches / -
	Transparency	80% / 89 ± 3%
Environment	Operating Temperature	-20 ~ 60° C (-4 ~ 140° F)
	Storage Temperature	-30 ~ 70° C (-22 ~ 158° F)
	Humidity	5 ~ 95% @ 40° C, non-condensing
	Vibration	5-500 Hz, 0.026G <sup>2</sup> /Hz, 2.16Grms, X, Y, Z 1 hour per axis
System	I/O	VGA x 1, DVI x 1, HDMI x 1, 12V DC Jack x 1, USB x 1, RS232 x 1 (RS232 and USB are reserved for the connection to enable touch usage only)
	OSD	Keys: Power on/off, Menu/Enter, Left/Up, Right/Down, Exit/Auto, Source Menu Functions: Brightness, Contrast, Screen Setting, Color Temp, OSD Language, Reset, Auto Adjust
	Power	60 W power adapter, with AC 100 ~ 240 V input and DC +12 V @ 5 A output
	EMC Compliance	CE/FCC/CCC

## Dimensions

Unit: mm



## Ordering Information

Model Name	Description
IDS-3315G-50XGA1	15" XGA 500 cd/m <sup>2</sup> Front IP65 Monitor
IDS-3315R-50XGA1	15" XGA 500 cd/m <sup>2</sup> Front IP65 Monitor with Res. Touch
IDS-3315P-50XGA1	15" XGA 500 cd/m <sup>2</sup> Front IP65 Monitor with P-Cap Touch
IDS-3315G-1KXGA1	15" XGA 1200 cd/m <sup>2</sup> Front IP65 Monitor
IDS-3315R-1KXGA1	15" XGA 1200 cd/m <sup>2</sup> Front IP65 Monitor with Res. Touch
IDS-3315P-1KXGA1	15" XGA 1200 cd/m <sup>2</sup> Front IP65 Monitor with P-Cap Touch

## Packing List

Part Number	Description
1700002215	1 x M cable USB-A(M)/USB-A(M) 180 cm
1700021332-11	1 x VGA cable 15P(M) 180 cm
1962055040	8 x clamper
1935042520	8 x clamper screw M4_25L
1992610005	1 x cable clamp
1933030500	1 x cable clamp screw
1992602010	1 x cable tie

\* USB Cable is only included in IDS-3315R/P.

Note: Package contents are subject to change without prior notice

## Optional Items

Part Number	Description
1702002600	Power cord 3P (USA)
1700000596	Power cord 3P (China)
1700018705	Power cord 3P (EU)
96PSA-A60W12R1-1	Adapter AC100-240V 60W +12V/5A
1700000243-11	M cable DVI 19P(M)/DVI 19P(M) 191cm
1700091800	Cable 9P/9P 1.8M M/F (Touchscreen RS-232 cable)
1700027186-01	HDMI cable 1.5 meter
1700023591-01	HDMI cable 1.2 meter