


## Power Cord with angled Locking System C13



- Protects appliances that are vulnerable to vibration
- Connector cannot be accidentally pulled or vibrated out of the inlet
- Space availability/constraints
- Different angles for ease of access
- Space saving
- Release locking mechanism
- Prevents accidental disconnection



### Approvals & Compliances



### Technical Specifications

<b>Temperature range (operation and storage)</b>	-25°C to +70°C
<b>Connector (line side) and cables</b>	Please refer to Available combinations IL 13 table
<b>Connector (load side)</b>	IEC C13 according to IEC/EN 60320-2-2 with IEC Lock UL 498, CSA C22.2 no. 42, Protection Class I
<b>Flammability corresponding to</b>	Plugs: UL 94 V-2 or better; Cable: IEC 60332-1 Cat. F2
<b>High potential test voltage</b>	P-> PE 2000 VAC (1 min 50 Hz) P-> N 2000 VAC (1 min 50 Hz)
<b>Maximum continuous operating voltage</b>	250 VAC, 50/60 Hz
<b>Protection category</b>	IP 20 according IEC 60529
<b>Rated currents</b>	10 A for C13 plug

### Cable Selection Table IL 13

<b>IL 13P-R-C14-H05-3100-X*</b>	right angled IEC cable assembly with locking system for IEC C14 inlet
<b>IL 13P-L-EU1-H05-3100-X*</b>	left angled IEC cable assembly with locking system for IEC C14 inlet, EU version
<b>IL 13P-U-SE-H05-3100-X*</b>	up angled IEC cable assembly with locking system for IEC C14 inlet, stripped ends
<b>IL 13P-D-UK1-H05-3100-X*</b>	down angled IEC cable assembly with locking system for IEC C14 inlet, UK version

To compile a complete part number, please replace the X\* with the required length (please refer to table below for available length per cable type):

- X\* options = 200, 300 cm

### Available Combinations IL 13

To compile a complete part number exchange the letters (IL13P-yyy-zzz-aaa-bbb-c) with the data from the table below.

Load side IL13P IL13P (-R/-L/-D/-U)		Line side plug yyy	Cable type zzz	Cable core aaa	Rating	Cable length* bbb		Cable color c	Cert.		
<b>IL13P-R</b>	IEC C13 Female plug, right angled, lock	IEC C14, male, straight	C14	H05VV-F H05	3x1.00mm <sup>2</sup>	3100	250VAC 10A	100 cm 200 cm 300 cm	Black	-	CB KC KEMA SAA
		CEE 7/VII, right angled or straight	EU1								
		Stripped Ends BS1363, right angled fused 5A	SE UK1								
<b>IL13P-L</b>	IEC C13 Female plug, left angled, lock	IEC C14, male, straight	C14	H05VV-F H05	3x1.0mm <sup>2</sup>	3100	250VAC 10A	100 cm 200 cm 300 cm	Black	-	CB KC KEMA SAA
		CEE 7/VII, right angled or straight	EU1								
		Stripped Ends BS1363, right angled fused 5A	SE UK1								
<b>IL13P-D</b>	IEC C13 Female plug, down angled, lock	IEC C14, male, straight	C14	H05VV-F H05	3x1.0mm <sup>2</sup>	3100	250VAC 10A	100 cm 200 cm 300 cm	Black	-	CB KC KEMA SAA
		CEE 7/VII, right angled or straight	EU1								
		Stripped Ends BS1363, right angled fused 5A	SE UK1								
<b>IL13P-U</b>	IEC C13 Female plug, up angled, lock	IEC C14, male, straight	C14	H05VV-F H05	3x1.0mm <sup>2</sup>	3100	250VAC 10A	100 cm 200 cm 300 cm	Black	-	CB KC KEMA SAA
		CEE 7/VII, right angled or straight	EU1								
		Stripped Ends BS1363, right angled fused 5A	SE UK1								

\*feet values are calculated to the matching length in cm

