

# ILSEU series

## External Mount Hydrostatic Level Transmitter



- **Piezo-resistive sensor**
- **Accuracy  $\leq \pm 0.25\%$  FS BFSL**
- **Various outputs including Volts and mA.**
- **Level ranges from 0-48" (0-4ft) to 0-480" (0-40ft) water gauge (Custom ranges available on request)**

The external mount hydrostatic level transmitter, ILSEU, has a piezo-resistive silicon pressure sensor which is an oil-filled isolated diaphragm. The sensor and housing are made from stainless steel with a choice of internal O-ring seals to ensure the product is suitable for a wide range of applications.

The electronics incorporate a microprocessor based amplifier, requiring no adjusting and giving stable electronics, especially in high vibration/shock applications.

Every device is temperature compensated, calibrated and supplied with a traceable serial number and calibration data. \*

### Input Pressure Ranges

Nominal level, Gauge,	inchWG	40	100	200	280	400
Permissible Overpressure	inchWG	800	800	800	2000	2000

### Suitable applications

Environmental engineering	Container or chamber level
Rainwater harvesting	Automotive testing
Static tank level	Vehicle tank level
Laboratory testing	IBC, IBC Tote or pallet tank

### Performance

Accuracy (Non-Linearity & Hysteresis)	$\leq \pm 0.25\%$ / FS (BFSL)	
Setting Errors (offsets)	2-wire	Zero & Full Scale, $\leq \pm 0.5\%$ / FS
	3-wire	Zero & Full Scale, $\leq \pm 0.5\%$ / FS
Permissible Load	2-wire	$R_{max} = [(VS-VSmin)/0.02] \Omega$
	3-wire	$R_{min} = 10k\Omega$
Influence Effects	Supply	$< 0.005\%$ FS / 1V
	Load	0.05% FSO / $k\Omega$

### Material Specifications

Housing	303 Stainless Steel
"O" ring seals	Viton
Diaphragm	316L Stainless Steel
Media wetted parts	Housing & process connection, "O" ring seal, diaphragm

### Miscellaneous

Current consumption	2-wire - limits at 28mA 3-wire - typical 6mA
Weight	Approx 3.5oz (100g)
Installation position	Any, small zero shift when tilted through 90°
Operational Life	$> 100 \times 10^6$ cycles
Insulation resistance	$> 50M\Omega$ at 50Vdc

### Electrical Protection

Supply reverse polarity	No damage but also no function
Electromagnetic compatibility	CE Compliant

### Mechanical Stability

Shock	100g / 11s
Vibration	10g RMS (20 - 2000Hz)

### Temperatures & Thermal Effects

Media Temperature	-40°C to +125°C
Ambient Temperature	-20°C to +80°C
Storage temperature	-40°C to +125°C
Compensated temperature range	+20°C to +80°C
Thermal Zero Shift (TZS)	$\leq \pm 0.04\%$ /FS/°C
Thermal Span Shift (TSS)	$< -0.015\%$ /°C

\*Calibration data is supplied as a sticker affixed to the product packaging - do not discard

Cynergy3 Components Ltd.  
7 Cobham Road  
Ferndown Industrial Estate  
Wimborne, Dorset BH21 7PE  
Telephone +44 (0) 1202 897969  
Email:sales@cynergy3.com

ILSEU 2018

ISO9001 CERTIFIED



www.cynergy3.com

# ILSEU series

## External Mount Hydrostatic Level Transmitter

### Output Signal and Supply Voltage

Wire system	Output	Supply Volts	Connection	Pin No. (Large plug and socket)
2-wire	4-20mA	9-32Vdc	+ve Supply -ve Supply Ground	Pin 1 Pin 2 Earth pin
3-wire	0.5 - 4.5Vdc (non-ratiometric)	9-32 Vdc	+ve Supply -ve Supply +ve Output Ground	Pin 1 Pin 2 Pin 3 Earth Pin

Part No	Pressure Range	Output
ILSEU-Gi048-5	0-48" WG	4-20mA
ILSEU-Gi120-5	0-120" WG	4-20mA
ILSEU-Gi240-5	0-240" WG	4-20mA
ILSEU-Gi360-5	0-360" WG	4-20mA
ILSEU-Gi480-5	0-480" WG	4-20mA
ILSEU-Gi048-D	0-48" WG	0.5 to 4.5V 3Wire
ILSEU-Gi120-D	0-120" WG	0.5 to 4.5V 3Wire
ILSEU-Gi240-D	0-240" WG	0.5 to 4.5V 3Wire
ILSEU-Gi360-D	0-360" WG	0.5 to 4.5V 3Wire
ILSEU-Gi480-D	0-480" WG	0.5 to 4.5V 3Wire

Part No	Pressure Range	Output
ILSEU-G0100-5	0 - 1mWG	4-20mA
ILSEU-G0250-5	0 - 2.5mWG	4-20mA
ILSEU-G0500-5	0 - 5mWG	4-20mA
ILSEU-G0700-5	0 - 7mWG	4-20mA
ILSEU-G1000-5	0 - 10mWG	4-20mA
ILSEU-G0100-D	0 - 1mWG	0.5 to 4.5V 3Wire
ILSEU-G0250-D	0 - 2.5mWG	0.5 to 4.5V 3Wire
ILSEU-G0500-D	0 - 5mWG	0.5 to 4.5V 3Wire
ILSEU-G0700-D	0 - 7mWG	0.5 to 4.5V 3Wire
ILSEU-G1000-D	0 - 10mWG	0.5 to 4.5V 3Wire

(Custom ranges and outputs available on request)

