

ISL9008A

Low Noise LDO with Low I_Q, High PSRR



FN6300
Rev 5.00
June 27, 2014

ISL9008A is a high performance single low noise, high PSRR LDO that delivers a continuous 150mA of load current. It has a low standby current and is stable with 1μF of MLCC output capacitance with an ESR of up to 200mΩ.

The ISL9008A has a high PSRR of 65dB and output noise less than 45μV_{RMS}. When coupled with a no load quiescent current of 46μA (typical), and 0.5μA shutdown current, the ISL9008A is an ideal choice for portable wireless equipment.

The ISL9008A comes in several fixed voltage options with ±1.8% output voltage accuracy over-temperature, line and load. Other output voltage options may be available upon request.

Pinouts



Features

- High performance LDO with 150mA continuous output
- Excellent transient response to large current steps
- Excellent load regulation: <0.1% voltage change across full range of load current
- High PSRR: 65dB at 1kHz
- Wide input voltage capability: 2.3V to 6.5V
- Very low quiescent current: 46μA
- Low dropout voltage: typically 200mV at 150mA
- Low output noise: typically 45μV_{RMS} at 100μA (1.5V)
- Stable with 1μF to 4.7μF ceramic capacitors
- Shutdown pin turns off LDO with 1μA (max) standby current
- Soft-start limits input current surge during enable
- Current limit and overheat protection
- ±1.8% accuracy over all operating conditions
- 5 Ld SC-70 package or 6 Ld μTDFN package
- -40°C to +85°C operating temperature range
- Pb-free (RoHS compliant)

Applications

- PDAs, cell phones and smart phones
- Portable instruments, MP3 players
- Handheld devices including medical handhelds

Ordering Information

| PART NUMBER (Note 5, 6) | PART MARKING | V _O VOLTAGE (V) (Note 1) | TEMP. RANGE (°C) | PACKAGE (Pb-Free) | PKG. DWG. # |
|--|-----------------|--|---------------------|----------------------|-------------|
| ISL9008AIENZ-T (Notes 2, 3) | CBV | 3.3 | -40 to +85 | 5 Ld SC-70 | P5.049 |
| ISL9008AIEMZ-T (Notes 2, 3) | CBT | 3.0 | -40 to +85 | 5 Ld SC-70 | P5.049 |
| ISL9008AIEKZ-T (Notes 2, 3) | CBS | 2.85 | -40 to +85 | 5 Ld SC-70 | P5.049 |
| ISL9008AIEJZ-T (Notes 2, 3) | CBR | 2.8 | -40 to +85 | 5 Ld SC-70 | P5.049 |
| ISL9008AIEHZ-T (Notes 2, 3) | CBP | 2.75 | -40 to +85 | 5 Ld SC-70 | P5.049 |
| ISL9008AIEFZ-T (Notes 2, 3) | CBN | 2.5 | -40 to +85 | 5 Ld SC-70 | P5.049 |
| ISL9008AIETZ-T (Notes 2, 3) | CDW | 1.9 | -40 to +85 | 5 Ld SC-70 | P5.049 |
| ISL9008AIECZ-T (Notes 2, 3) | CBM | 1.8 | -40 to +85 | 5 Ld SC-70 | P5.049 |
| ISL9008AIEBZ-T (Notes 2, 3) | CBL | 1.5 | -40 to +85 | 5 Ld SC-70 | P5.049 |
| ISL9008AIRUBZ-T (Note 4) | P | 1.5 | -40 to +85 | 6 Ld μ TDFN | L6.1.6x1.6A |
| ISL9008AIRUCZ-T (Note 4) | Q | 1.8 | -40 to +85 | 6 Ld μ TDFN | L6.1.6x1.6A |
| ISL9008AIRUFZ-T (Note 4) | R | 2.5 | -40 to +85 | 6 Ld μ TDFN | L6.1.6x1.6A |
| ISL9008AIRUHZ-T (Note 4) | S | 2.75 | -40 to +85 | 6 Ld μ TDFN | L6.1.6x1.6A |
| ISL9008AIRUJZ-T (Note 4) | T | 2.8 | -40 to +85 | 6 Ld μ TDFN | L6.1.6x1.6A |
| ISL9008AIRUKZ-T (Note 4) | V | 2.85 | -40 to +85 | 6 Ld μ TDFN | L6.1.6x1.6A |
| ISL9008AIRUMZ-T (Note 4) | W | 3.0 | -40 to +85 | 6 Ld μ TDFN | L6.1.6x1.6A |
| ISL9008AIRUNZ-T (Note 4) | Y | 3.3 | -40 to +85 | 6 Ld μ TDFN | L6.1.6x1.6A |

NOTES:

- For other output voltages, contact Intersil Marketing.
- These Intersil Pb-free plastic packaged products employ special Pb-free material sets, molding compounds/die attach materials, and 100% matte tin plate plus anneal (e3 termination finish, which is RoHS compliant and compatible with both SnPb and Pb-free soldering operations). Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.
- The part marking is located on the bottom of the part.
- These Intersil Pb-free plastic packaged products employ special Pb-free material sets; molding compounds/die attach materials and NiPdAu plate - e4 termination finish, which is RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.
- Please refer to [TB347](#) for details on reel specifications.
- For Moisture Sensitivity Level (MSL), please see product information page for [ISL9008A](#). For more information on MSL, please see tech brief [TB363](#)

Absolute Maximum Ratings

| | |
|-----------------------------|----------------------------|
| Supply Voltage (V_{IN}) | +7.1V |
| V_O Pin | +3.6V |
| All Other Pins | -0.3V to ($V_{IN}+0.3V$) |

Recommended Operating Conditions

| | |
|-------------------------------------|----------------|
| Ambient Temperature Range (T_A) | -40°C to +85°C |
| Supply Voltage (V_{IN}) | 2.3 to 6.5V |

Thermal Information

| | |
|----------------------------------|---------------------------|
| Thermal Resistance | θ_{JA} (°C/W) |
| 5 Ld SC-70 Package (Note 7) | 231 |
| 6 Ld μ TDFN Package (Note 8) | 125 |
| Junction Temperature Range | -40°C to +125°C |
| Operating Temperature Range | -40°C to +85°C |
| Storage Temperature Range | -65°C to +150°C |
| Pb-free reflow profile | see TB493 |

CAUTION: Do not operate at or near the maximum ratings listed for extended periods of time. Exposure to such conditions may adversely impact product reliability and result in failures not covered by warranty.

NOTES:

- θ_{JA} is measured with the component mounted on a high effective thermal conductivity test board in free air. See Tech Brief [TB379](#) for details.
- θ_{JA} is measured in free air with the component mounted on a high effective thermal conductivity test board with "direct attach" features. See Tech Brief [TB379](#).

Electrical Specifications Unless otherwise noted, all parameters are established over the operational supply voltage and temperature range of the device as follows: $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$; $V_{IN} = (V_O + 0.5V)$ to 6.5V with a minimum V_{IN} of 2.3V; $C_{IN} = 1\mu\text{F}$; $C_O = 1\mu\text{F}$.

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN (Note 11) | TYP | MAX (Note 11) | UNITS |
|--|-----------|--|------------------|-----|------------------|------------------|
| DC CHARACTERISTICS | | | | | | |
| Supply Voltage | V_{IN} | | 2.3 | | 6.5 | V |
| Ground Current | I_{DD} | Quiescent condition: $I_O = 0\mu\text{A}$ | | 46 | 66 | μA |
| Shutdown Current | I_{DDS} | | | 0.5 | 1.2 | μA |
| UVLO Threshold | V_{UV+} | | 1.9 | 2.1 | 2.3 | V |
| | V_{UV-} | | 1.6 | 1.8 | 2.0 | V |
| Regulation Voltage Accuracy | | Initial accuracy at $V_{IN} = V_O + 0.5V$, $I_O = 10\text{mA}$, $T_J = +25^\circ\text{C}$ | -0.7 | | +0.7 | % |
| | | $V_{IN} = V_O + 0.5V$ to 6.5V, $I_O = 10\mu\text{A}$ to 150mA, $T_J = +25^\circ\text{C}$ | -0.8 | | +0.8 | % |
| | | $V_{IN} = V_O + 0.5V$ to 6.5V, $I_O = 10\mu\text{A}$ to 150mA, $T_J = -40^\circ\text{C}$ to $+125^\circ\text{C}$ | -1.8 | | +1.8 | % |
| Maximum Output Current | I_{MAX} | Continuous | 150 | | | mA |
| Internal Current Limit | I_{LIM} | | 175 | 265 | 355 | mA |
| Drop-out Voltage (Note 10) | V_{DO1} | $I_O = 150\text{mA}$; $V_O < 2.5V$ | | 300 | 500 | mV |
| | V_{DO2} | $I_O = 150\text{mA}$; $2.5V \leq V_O \leq 2.8V$ | | 250 | 400 | mV |
| | V_{DO3} | $I_O = 150\text{mA}$; $2.8V < V_O$ | | 200 | 325 | mV |
| Thermal Shutdown Temperature | T_{SD+} | | | 140 | | °C |
| | T_{SD-} | | | 110 | | °C |
| AC CHARACTERISTICS | | | | | | |
| Ripple Rejection (Note 9) | | $I_O = 10\text{mA}$, $V_{IN} = 2.8V(\text{min})$, $V_O = 1.8V$ | | | | |
| | | at 1kHz | | 65 | | dB |
| | | at 10kHz | | 45 | | dB |
| Output Noise Voltage (Note 9) | | $V_O = 1.5V$, $T_A = +25^\circ\text{C}$ | | | | |
| | | BW = 10Hz to 100kHz, $I_O = 100\mu\text{A}$ | | 45 | | μVRMS |
| | | BW = 10Hz to 100kHz, $I_O = 10\text{mA}$ | | 65 | | μVRMS |
| DEVICE START-UP CHARACTERISTICS | | | | | | |
| Device Enable Time | t_{EN} | Time from assertion of the ENx pin to when the output voltage reaches 95% of the $V_O(\text{nom})$ | | 250 | 500 | μs |

Electrical Specifications Unless otherwise noted, all parameters are established over the operational supply voltage and temperature range of the device as follows: TA = -40°C to +85°C; VIN = (VO + 0.5V) to 6.5V with a minimum VIN of 2.3V; CIN = 1µF; CO = 1µF.

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN (Note 11) | TYP | MAX (Note 11) | UNITS |
|-------------------------------|-----------------------------------|--|------------------|-----|-----------------------|-------|
| LDO Soft-start Ramp Rate | t _{SSR} | Slope of linear portion of LDO output voltage ramp during start-up | | 30 | 60 | µs/V |
| EN PIN CHARACTERISTICS | | | | | | |
| Input Low Voltage | V _{IL} | | -0.3 | | 0.4 | V |
| Input High Voltage | V _{IH} | | 1.4 | | V _{IN} + 0.3 | V |
| Input Leakage Current | I _{IL} , I _{IH} | | | | 0.1 | µA |
| Pin Capacitance | C _{PIN} | Informative | | 5 | | pF |

NOTES:

- 9. Limits established by characterization and are not production tested.
- 10. VOx = 0.98*VOx(NOM); Valid for VOx greater than 1.85V.
- 11. Parameters with MIN and/or MAX limits are 100% tested at +25°C, unless otherwise specified. Temperature limits established by characterization and are not production tested..

Typical Performance Curves




FIGURE 1. OUTPUT VOLTAGE vs INPUT VOLTAGE (3.3V OUTPUT)




FIGURE 2. OUTPUT VOLTAGE CHANGE (%) vs INPUT VOLTAGE (3.3V OUTPUT)

Typical Performance Curves (Continued)




FIGURE 3. OUTPUT VOLTAGE vs LOAD CURRENT




FIGURE 4. OUTPUT VOLTAGE vs TEMPERATURE




FIGURE 5. DROPOUT VOLTAGE vs INPUT VOLTAGE (3.3V OUTPUT)




FIGURE 6. DROPOUT VOLTAGE vs INPUT VOLTAGE (2.8V OUTPUT)




FIGURE 7. DROPOUT VOLTAGE vs LOAD CURRENT




FIGURE 8. DROPOUT VOLTAGE vs LOAD CURRENT

Typical Performance Curves (Continued)




FIGURE 9. GROUND CURRENT vs INPUT VOLTAGE




FIGURE 10. GROUND CURRENT vs LOAD




FIGURE 11. GROUND CURRENT vs TEMPERATURE




FIGURE 12. TURN ON/TURN OFF RESPONSE




FIGURE 13. LINE TRANSIENT RESPONSE, 3.3V OUTPUT




FIGURE 14. LINE TRANSIENT RESPONSE, 2.8V OUTPUT

Typical Performance Curves (Continued)




FIGURE 15. LOAD TRANSIENT RESPONSE




FIGURE 16. PSRR vs FREQUENCY






FIGURE 17. SPECTRAL NOISE DENSITY vs FREQUENCY


Pin Description

| 5 LD SC-70 PIN NUMBER | 6 LD µTDFN PIN NUMBER | PIN NAME | DESCRIPTION |
|--------------------------|--------------------------|----------|--|
| 5 | 1 | VO | LDO Output. Connect a 1µF capacitor of value to GND |
| 2 | 2 | GND | GND is the connection to system ground. Connect to PCB Ground plane. |
| 4 | 3 and 5 | NC | No connect. |
| 3 | 4 | EN | Output Enable. When this signal goes high, the LDO is turned on. |
| 1 | 6 | VIN | Supply Voltage/LDO Input. Connect a 1µF capacitor to GND. |

Typical Application



Block Diagram



Functional Description

The ISL9008A contains all circuitry required to implement a high performance LDO. High performance is achieved through a circuit that delivers fast transient response to varying load conditions. In a quiescent condition, the ISL9008A adjusts its biasing to achieve the lowest standby current consumption.

The device also integrates current limit protection, smart thermal shutdown protection, and soft-start. Smart Thermal shutdown protects the device against overheating. Soft-start minimizes start-up input current surges without causing excessive device turn-on time.

Power Control

The ISL9008A has an enable pin, EN, to control power to the LDO output. When EN is low, the device is in shutdown mode. In this condition, all on-chip circuits are off, and the device draws minimum current, typically less than 0.3 μ A. When the EN pin goes high, the device first polls the output of the UVLO detector to ensure that the VIN voltage is at least 2.1V (typical). Once verified, the device initiates a start-up sequence. During the start-up sequence, trim settings are first read and latched. Then sequentially, the bandgap, reference voltage and current generation circuitry turn on. Once the references are stable, the LDO powers up.

During operation, whenever the VIN voltage drops below about 1.84V, the ISL9008A immediately disables the LDO output. When VIN rises back above 2.1V (assuming the EN pin is high), the device reinitiates its start-up sequence and LDO operation resumes automatically.

Reference Generation

The reference generation circuitry includes a trimmed bandgap, a trimmed voltage reference divider, a trimmed current reference generator, and an RC noise filter.

The bandgap generates a zero temperature coefficient (TC) voltage for the regulator reference and other voltage references required for current generation and over-temperature detection.

A current generator provides references required for adaptive biasing as well as references for LDO output current limit and thermal shutdown determination.

LDO Regulation and Programmable Output Divider

The LDO Regulator is implemented with a high-gain operational amplifier driving a PMOS pass transistor. The design of the ISL9008A provides a regulator that has low quiescent current, fast transient response, and overall stability across all operating and load current conditions. LDO stability is guaranteed for a 1 μ F to 4.7 μ F output capacitor that has a tolerance better than 20% and ESR less than 200m Ω . The design is performance-optimized for a 1 μ F capacitor. Unless limited by the application, use of an output capacitor value above 4.7 μ F is not recommended as LDO performance improvement is minimal.

Soft-start circuitry integrated into each LDO limits the initial ramp-up rate to about 30 μ s/V to minimize current surge. The ISL9008A provides short-circuit protection by limiting the output current to about 265mA (typ).

The LDO uses an independently trimmed 1V reference as its input. An internal resistor divider drops the LDO output voltage down to 1V. This is compared to the 1V reference for regulation. The resistor division ratio is programmed in the factory.

Overheat Detection

The bandgap outputs a proportional-to-temperature current that is indicative of the temperature of the silicon. This current is compared with references to determine if the device is in danger of damage due to overheating. When the die temperature reaches about +140 $^{\circ}$ C, the LDO momentarily shuts down until the die cools sufficiently. In the overheat condition, if the LDO sources more than 50mA it will be shut off. Once the die temperature falls back below about +110 $^{\circ}$ C, the disabled LDO is re-enabled and soft-start automatically takes place.

Exposed Thermal Pad

The ISL9008A with μ TDFN package has an exposed thermal pad at the bottom side of the package. The PCB layout should connect the exposed pad to some copper on the component layer for a good thermal conductivity. Since the copper area on the component layer is limited by the surrounding pins of the package, it is more effective to use some thermal vias to conduct the heat to other copper layers if possible.

Electrically, the copper and vias connecting to the exposed pad should be isolated from any other pin connection, they are strictly for thermal enhancement purpose.

**© Copyright Intersil Americas LLC 2006-2014. All Rights Reserved.
All trademarks and registered trademarks are the property of their respective owners.**



For additional products, see www.intersil.com/en/products.html

Intersil products are manufactured, assembled and tested utilizing ISO9001 quality systems as noted in the quality certifications found at www.intersil.com/en/support/qualandreliability.html


Intersil products are sold by description only. Intersil may modify the circuit design and/or specifications of products at any time without notice, provided that such modification does not, in Intersil's sole judgment, affect the form, fit or function of the product. Accordingly, the reader is cautioned to verify that datasheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com


Ultra Thin Dual Flat No-Lead Plastic Package (UTDFN)




TOP VIEW




BOTTOM VIEW



SIDE VIEW



DETAIL A



LAND PATTERN

L6.1.6x1.6A

6 LEAD ULTRA THIN DUAL FLAT NO-LEAD PLASTIC PACKAGE

| SYMBOL | MILLIMETERS | | | NOTES |
|--------|-------------|---------|------|-------|
| | MIN | NOMINAL | MAX | |
| A | 0.45 | 0.50 | 0.55 | - |
| A1 | - | - | 0.05 | - |
| A3 | 0.127 REF | | | - |
| b | 0.15 | 0.20 | 0.25 | - |
| D | 1.55 | 1.60 | 1.65 | 4 |
| D2 | 0.40 | 0.45 | 0.50 | - |
| E | 1.55 | 1.60 | 1.65 | 4 |
| E2 | 0.95 | 1.00 | 1.05 | - |
| e | 0.50 BSC | | | - |
| L | 0.25 | 0.30 | 0.35 | - |

Rev. 1 6/06

NOTES:

1. Dimensions are in mm. Angles in degrees.
2. Coplanarity applies to the exposed pad as well as the terminals. Coplanarity shall not exceed 0.08mm.
3. Warpage shall not exceed 0.10mm.
4. Package length/package width are considered as special characteristics.
5. JEDEC Reference MO-229.
6. For additional information, to assist with the PCB Land Pattern Design effort, see Intersil Technical Brief TB389.