


GenX3™ 600V IGBT

Ultra Low V_{sat} PT IGBT for up to 5kHz switching


IXGH72N60A3 IXGT72N60A3




V_{CES} = 600V
I_{C110} = 72A
V_{CE(sat)} ≤ 1.35V
t_{fi(typ)} = 250ns

| Symbol | Test Conditions | Maximum Ratings | |
|-------------------------------|--|-----------------------|-----------|
| V _{CES} | T _C = 25°C to 150°C | 600 | V |
| V _{CGR} | T _J = 25°C to 150°C, R _{GE} = 1MΩ | 600 | V |
| V _{GES} | Continuous | ± 20 | V |
| V _{GEM} | Transient | ± 30 | V |
| I _{C25} | T _C = 25°C (limited by leads) | 75 | A |
| I _{C110} | T _C = 110°C | 72 | A |
| I _{CM} | T _C = 25°C, 1ms | 400 | A |
| SSOA (RBSOA) | V _{GE} = 15V, T _{VJ} = 125°C, R _G = 3Ω Clamped inductive load @ ≤ 600V | I _{CM} = 150 | A |
| P _C | T _C = 25°C | 540 | W |
| T _J | | -55 ... +150 | °C |
| T _{JM} | | 150 | °C |
| T _{stg} | | -55 ... +150 | °C |
| T _L | 1.6mm (0.062 in.) from case for 10s | 300 | °C |
| T _{SOLD} | Plastic body for 10 seconds | 260 | °C |
| M _d | Mounting torque (TO-247) | 1.13/10 | Nm/lb.in. |
| Weight | TO-247 | 6 | g |
| | TO-268 | 4 | g |

TO-247 (IXGH)



TO-268 (IXGT)



G = Gate C = Collector
E = Emitter TAB = Collector

Features

- Optimized for low conduction losses
- Square RBSOA
- International standard packages

Advantages

- High power density
- Low gate drive requirement


Applications

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts
- Inrush Current Protection Circuits

| Symbol | Test Conditions (T _J = 25°C unless otherwise specified) | Characteristic Values | | |
|----------------------|--|-----------------------|------|-----------------|
| | | Min. | Typ. | Max. |
| BV _{CES} | I _C = 250μA, V _{GE} = 0V | 600 | | V |
| V _{GE(th)} | I _C = 250μA, V _{CE} = V _{GE} | 3.0 | | V |
| I _{CES} | V _{CE} = V _{CES} V _{GE} = 0V T _J = 125°C | | | 75 μA 750 μA |
| I _{GES} | V _{CE} = 0V, V _{GE} = ± 20V | | | ±100 nA |
| V _{CE(sat)} | I _C = 60A, V _{GE} = 15V, Note 1 | | | 1.35 V |


| Symbol | Test Conditions | Characteristic Values | | |
|--------------|--|-----------------------|------|--------------|
| | | Min. | Typ. | Max. |
| g_{fs} | $I_C = 60A, V_{CE} = 10V$, Note 1 | 48 | 76 | S |
| C_{ies} | $V_{CE} = 25V, V_{GE} = 0V, f = 1MHz$ | | 6600 | pF |
| C_{oes} | | | 360 | pF |
| C_{res} | | | 80 | pF |
| Q_g | $I_C = I_{C110}, V_{GE} = 15V, V_{CE} = 0.5 \cdot V_{CES}$ | | 230 | nC |
| Q_{ge} | | | 40 | nC |
| Q_{gc} | | | 78 | nC |
| $t_{d(on)}$ | Inductive load, $T_J = 25^\circ C$ $I_C = 50A, V_{GE} = 15V$ $V_{CE} = 480V, R_G = 3\Omega$ | | 31 | ns |
| t_{ri} | | | 34 | ns |
| E_{on} | | | 1.38 | mJ |
| $t_{d(off)}$ | | | 320 | ns |
| t_{fi} | | | 250 | ns |
| E_{off} | | | 3.5 | mJ |
| $t_{d(on)}$ | Inductive load, $T_J = 125^\circ C$ $I_C = 50A, V_{GE} = 15V$ $V_{CE} = 480V, R_G = 3\Omega$ | | 29 | ns |
| t_{ri} | | | 32 | ns |
| E_{on} | | | 2.6 | mJ |
| $t_{d(off)}$ | | | 510 | ns |
| t_{fi} | | | 375 | ns |
| E_{off} | | | 6.5 | mJ |
| R_{thJC} | | | 0.23 | $^\circ C/W$ |
| R_{thCS} | | 0.15 | | $^\circ C/W$ |

Note 1: Pulse test, $t \leq 300\mu s$, duty cycle, $d \leq 2\%$.

TO-247 AD Outline


Terminals: 1 - Gate 2 - Drain

| Dim. | Millimeter | | Inches | |
|----------------|------------|-------|--------|-------|
| | Min. | Max. | Min. | Max. |
| A | 4.7 | 5.3 | .185 | .209 |
| A ₁ | 2.2 | 2.54 | .087 | .102 |
| A ₂ | 2.2 | 2.6 | .059 | .098 |
| b | 1.0 | 1.4 | .040 | .055 |
| b ₁ | 1.65 | 2.13 | .065 | .084 |
| b ₂ | 2.87 | 3.12 | .113 | .123 |
| C | .4 | .8 | .016 | .031 |
| D | 20.80 | 21.46 | .819 | .845 |
| E | 15.75 | 16.26 | .610 | .640 |
| e | 5.20 | 5.72 | 0.205 | 0.225 |
| L | 19.81 | 20.32 | .780 | .800 |
| L ₁ | | 4.50 | | .177 |
| ∅P | 3.55 | 3.65 | .140 | .144 |
| Q | 5.89 | 6.40 | 0.232 | 0.252 |
| R | 4.32 | 5.49 | .170 | .216 |

TO-268 Outline


Terminals: 1 - Gate 2 - Drain

| SYM | INCHES | | MILLIMETERS | |
|-----|----------|------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | .193 | .201 | 4.90 | 5.10 |
| A1 | .106 | .114 | 2.70 | 2.90 |
| A2 | .001 | .010 | 0.02 | 0.25 |
| b | .045 | .057 | 1.15 | 1.45 |
| b2 | .075 | .083 | 1.90 | 2.10 |
| C | .016 | .026 | 0.40 | 0.65 |
| C2 | .057 | .063 | 1.45 | 1.60 |
| D | .543 | .551 | 13.80 | 14.00 |
| D1 | .488 | .500 | 12.40 | 12.70 |
| E | .624 | .632 | 15.85 | 16.05 |
| E1 | .524 | .535 | 13.30 | 13.60 |
| e | .215 BSC | | 5.45 BSC | |
| H | .736 | .752 | 18.70 | 19.10 |
| L | .094 | .106 | 2.40 | 2.70 |
| L1 | .047 | .055 | 1.20 | 1.40 |
| L2 | .039 | .045 | 1.00 | 1.15 |
| L3 | .010 BSC | | 0.25 BSC | |
| L4 | .150 | .161 | 3.80 | 4.10 |

IXYS reserves the right to change limits, test conditions and dimensions.

IXYS MOSFETs and IGBTs are covered 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2
 by one or more of the following U.S. patents: 4,850,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2
 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

Fig. 1. Output Characteristics @ 25°C




Fig. 2. Extended Output Characteristics @ 25°C




Fig. 3. Output Characteristics @ 125°C




Fig. 4. Dependence of $V_{CE(sat)}$ on Junction Temperature




Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage




Fig. 6. Input Admittance




Fig. 7. Transconductance




Fig. 8. Gate Charge




Fig. 9. Capacitance




Fig. 10. Reverse-Bias Safe Operating Area





Fig. 11. Maximum Transient Thermal Impedance



IXYS reserves the right to change limits, test conditions and dimensions.

Fig. 12. Inductive Switching Energy Loss vs. Gate Resistance




Fig. 13. Inductive Switching Energy Loss vs. Collector Current




Fig. 14. Inductive Switching Energy Loss vs. Junction Temperature




Fig. 15. Inductive Turn-off Switching Times vs. Gate Resistance




Fig. 16. Inductive Turn-off Switching Times vs. Collector Current




Fig. 17. Inductive Turn-off Switching Times vs. Junction Temperature

