Transformer for BCM6526

CEP710B

Descriptions

- Size (Max.):L×W×H 8.1×8.0×9.85mm
- Custom design is available.
- VDSL line transformer.
- Ideally used in VDSL/VDSL2 CO equipments.
- Approved by Broadcom (BCM6511/6526, BCM6516/6524) and Alcatel.
- RoHS Compliance
- Sumida Type name ：CEP710B

Dimensions (mm)



Land patterns (mm)



Schematic (Bottom View)



Remarks： Sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text.

Transformer for BCM6526

CEP710B

Electrical characteristics

Part No.	Item	Inductance (1-4)	Leakage Inductance (1-4)	Turns ratio (T/R) (1-4): (8-6)	Total Harmonic Distortion (THI)	Inter winding capacitance Cww (1-8)
J14215	Specifications	100μH ±10% within	Max. 1.35μH	2 : 1 (±1%)	Max. -80dB	Max.40pF
	Testing conditions	10kHz 0.1V Tie(2+3)	1MHz, 0.1V, Tie [(2+3), (5+6+7+8)]	100kHz, 0.1Vrms, Tie[(2+3), (5+7)]	100kHz 3.0Vrms	100kHz 0.1V Tie[(2+3), (5+7)]

Part No.	Item	Longitudinal Balance (LB)			D.C.R. (8-6)	D.C.R. (1-4)
J14215	Specifications	Min.44dB	Min.40dB	Min.30dB	Max.0.45Ω	Max.1.7Ω
	Testing conditions	12MHz, Tie (2+3), (5+7) Grounded	17MHz, Tie (2+3), (5+7) Grounded	30MHz, Tie (2+3), (5+7) Grounded	Tie (5+7)	Tie (2+3)

Part No.	Item	Hi-pot (1-2)	Hi-pot (1-8)
J14215	Specifications	Min.750Vrms	Min.1,875Vrms.
	Testing conditions	Max.0.5mA, 1sec.	Max.0.5mA, 1sec. Tie [(2+3), (5+7)]

For sales office information, please click here to visit our website.

Remarks : Sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text sample text.