Mallory Sonalert Products, Inc. Sales Outline Drawing				Part #: JT120-G-CSL  Revision: D		
						Conseilinations.
Specifications:						
Stack Number: LED Color:	GREEN					
Connection Wires:	Green and Brown					
LED Current Draw:	<190 mA					
Rated Voltage:	< 190 IIIA		120 VAC		ļ.	
Operating Voltage:			90-120 VAC			
Sound Level Category:	Loud	Loud	Loud		Loud	
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.5PPS)	Continuous for 5 sec then 0.1s beep until		
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wires; Purp wire connected to Green/Yell wire	w I black and t	Black and Gray wires: Orange and Purple	
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max.		40mA Max.	
Loudness @ 1m:		U.	80-85 dB(A) Typ.			
Frequency:	2000 ± 500 Hz					
Total Max Current:	<230mA with all LED's and sound unit working					
Operating Temperature:	-25° ~ +60°C					
Lens Color:	Opaque White					
Material:	ABS FR15U					
Mounting Method:	Stainless Steel Pole					
Weight Typical (g):	645					
NEMA 12:	Approved					
Options:			Please contact factory.			
3.7 [94.1]  GREEN		5.6 [422.0]	GA:	SKET	48"/ wine	
2.4 [6: 2.7 [68.3] TOP VIEW	1.81		#10 or 5mm screws for mounting 0.39 [9.9] 0.95 [24.3]	0.57 [ø14. for wires 2.04 [5	1.9]	
			ROWN WIRE TO POWER.			
SOUND OPERATION:			POWER FOR CONTINUOUS			
FOR MEDIUM PULSE, CONNECT GRAY & BLACK TO POWER AND ORANGE WIRE TO GREEN/YELLOW W FOR DOUBLE PULSE, CONNECT GRAY & BLACK TO POWER AND PURPLE WIRE TO GREEN/YELLOW W						
			BLACK TO POWER AND PUI ACK TO POWER AND ORANG			