



## RCA PHONO JACKS: KLP42X Series

### Stacked RCA Phono Jack PCB Mount

#### Product Features

Audio Applications for Computers and Multimedia  
 Gold Plating Available Upon Request  
 Various Color and Stacking Options Available  
 CSA/NRTL Certified File No. LR78160

#### Performance Specifications

##### Materials and Finish

##### Housing

PBT Thermoplastic, UL94V-0 Rated

##### Terminals

Brass, Tin Plated

##### Ground Pin

Brass, Nickel Plated

#### Electrical Characteristics

**Rated Current:** 0.3A

**Rated Voltage:** 16V DC

**Contact Resistance**

50 milliohms Max.

**Insulation Resistance**

100 Megohms Min. at 500V DC

**Dielectric Withstanding Voltage**

500V AC RMS for 1 Minute

#### Mechanical Characteristics

##### Insertion Force

0.3kg - 5.0kg

##### Extraction Force

0.3kg - 5.0kg

##### Durability

1000 Mating Cycles Min.

##### Operating Temperature

-20°C to +60°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

#### Generated Part Number

#### Part Number Builder

	-		
Series		Type	Color Option

#### Series

KLP42X - Stacked RCA Phono Jack

#### Type

62 - Triple Column, Double Row

#### Color Option

BY/R/YY - Black, Yellow / Red, Yellow / White, Yellow

RR/WW/YY - Red, Red / White, White / Yellow, Yellow

RW/R/WW - Red, White / Red, White / Red, White

RW/R/YY - Red, White / Red, White / Yellow, Yellow

WR/WR/WR - White, Red / White, Red / White, Red

WW/RR/YY - White, White / Red, Red / Yellow, Yellow

YY/YY/YY - Yellow, Yellow / Yellow, Yellow / Yellow, Yellow

#### Color Layout - X, Z / X1, Z1 / X2, Z2

Contact Kycon for other options

#### KLP42X-62-xx/xx/xx

Dimensions in mm

