



**RCA PHONO JACKS: KLPX Series**  
RCA Phono Jack PCB Mount

**Product Features**

Audio Applications for Computers and Multimedia  
Two Contact Cost Efficient Design  
Right Angle and Vertical Mount Available

**Performance Specifications**

**Materials and Finish**

**Housing**

PBT Thermoplastic, UL94V-0 Rated

**Terminals**

Brass, Tin Plated

**Electrical Characteristics**

**Contact Resistance**

30 milliohms Max.

**Insulation Resistance**

100 Megohms Min.at 500V DC

**Dielectric Withstanding Voltage**

500V AC RMS for 1 Minute

**Mechanical Characteristics**

**Insertion Force**

0.3kg - 3.0kg

**Extraction Force**

0.3kg - 3.0kg

**Durability**

5000 Mating Cycles Min.

**Operating Temperature**

-25°C to +80°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number



Part Number Builder

-     
 Series                      Type                      Color Option                      Plating Option

**Series**

KLPX - RCA Phono Jack

**Type**

0848-2 - Vertical Mount  
0848A-2 - Right Angle Mount

**Color Option**

B - Black  
R - Red  
W - White  
Y - Yellow

**Barrel Plating Option**

Blank - Nickel Plating

Contact Kycon for other options

**KLPX**

Dimensions in mm

