



## RCA PHONO JACKS: KLPX Series

RCA Phono Jack PCB Mount

### Product Features

Audio Applications for Computers and Multimedia  
Two Contact Cost Efficient Design  
Right Angle and Vertical Mount Available

### Performance Specifications

#### Materials and Finish

##### Housing

PBT Thermoplastic, UL94V-0 Rated

##### Terminals

Brass, Tin Plated

### Electrical Characteristics

#### Contact Resistance

30 milliohms Max.

#### Insulation Resistance

100 Megohms Min. at 500V DC

#### Dielectric Withstanding Voltage

500V AC RMS for 1 Minute

### Mechanical Characteristics

#### Insertion Force

0.3kg - 3.0kg

#### Extraction Force

0.3kg - 3.0kg

#### Durability

5000 Mating Cycles Min.

#### Operating Temperature

-25°C to +80°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

### Generated Part Number

#### Part Number Builder

<input type="text"/>	-	<input type="text"/>	<input type="text"/>	<input type="text"/>
Series		Type	Color Option	Plating Option

#### Series

KLPX - RCA Phono Jack

#### Type

0848-2 - Vertical Mount

0848A-2 - Right Angle Mount

#### Color Option

B - Black

R - Red

W - White

Y - Yellow

#### Barrel Plating Option

Blank - Nickel Plating

Contact Kycon for other options

### KLPX

Dimensions in mm

