



**DC POWER CONNECTORS: KPJX Series**  
Snap and Lock PCB Mount Receptacle

**Product Features**

Laptop Computers, Power Supplies and Other Portable Digital Equipment Applications  
 Snap & Lock Feature Helps to Prevent Accidental Disconnects  
 3 or 4 Pins Transmit Power, or One Pin Can Be Used For Signal Transmission  
 For Signal and DC Power Applications  
 CSA/NRTL Certified File No. LR78160  
 UL File No. E140125

**Performance Specifications**

**Materials and Finish**

**Shield:** Copper Alloy, Tin Plated  
**Body:** PBT, UL 94V-0 Rated  
**HT Body:** High Temperature Thermoplastic, UL 94V-0 Rated

**Electrical Characteristics**

**Contact Rating**

**3 Position:** Pin 1 and 2, 48V DC at 7.5A Max.,  
 Pin 3, 48V DC 1.0A Max.

**4 Position:** 48V DC 7.5A Max. For All Pins.

**Insulation Resistance:** 50 Megohms Min. at 250V DC

**Dielectric Withstanding Voltage:** 500V AC for 1 Minute

**Contact Resistance:** 30 milliohms Max.


**Mechanical Characteristics**

**Durability:** 1000 Cycles

2D Drawing	IGES	STEP	3D PDF
Check Stock	Solder Profile	Request a Sample	Send Us An Email
RoHS Compliant	REACH Compliant	UL Plastic	Certificate of Compliance

Generated Part Number

**Part Number Builder**



**Series**

KPJX - Right Angle Receptacle  
 KPJXHT - High Temperature, Right Angle Receptacle

**Number of Contacts**

3 Pin  
 4 Pin

**Contact Type**

S - Socket

**Shield Option**

Blank - Non-Shielded  
 S - Shielded

**Recommended to be used with Kycon KPPX Series Plugs**

Contact Kycon for Other Options

**KPJX-3S Series**  
 Dimensions in mm

