

Notice for TAIYO YUDEN Products

Please read this notice before using the TAIYO YUDEN products.

⚠ REMINDERS

Product Information in this Catalog

Product information in this catalog is as of March 2023. All of the contents specified herein and production status of the products listed in this catalog are subject to change without notice due to technical improvement of our products, etc. Therefore, please check for the latest information carefully before practical application or use of our products.

Please note that TAIYO YUDEN shall not be in any way responsible for any damages and defects in products or equipment incorporating our products, which are caused under the conditions other than those specified in this catalog or individual product specification sheets.

Approval of Product Specifications

Please contact TAIYO YUDEN for further details of product specifications as the individual product specification sheets are available. When using our products, please be sure to approve our product specifications or make a written agreement on the product specification with TAIYO YUDEN in advance.

Pre-Evaluation in the Actual Equipment and Conditions

Please conduct validation and verification of our products in actual conditions of mounting and operating environment before using our products.

Limited Application

1. Equipment Intended for Use

The products listed in this catalog are intended for general-purpose and standard use in general electronic equipment for consumer (e.g., AV equipment, OA equipment, home electric appliances, office equipment, information and communication equipment including, without limitation, mobile phone, and PC) and other equipment specified in this catalog or the individual product specification sheets, or the equipment approved separately by TAIYO YUDEN.

TAIYO YUDEN has the product series intended for use in the following equipment. Therefore, when using our products for these equipment, please check available applications specified in this catalog or the individual product specification sheets and use the corresponding products.

| Application | Product Series | | Quality Grade ^{*3} |
|-------------|--|---|-----------------------------|
| | Equipment ^{*1} | Category (Part Number Code ^{*2}) | |
| Automotive | Automotive Electronic Equipment (POWERTRAIN, SAFETY) | A | 1 |
| | Automotive Electronic Equipment (BODY & CHASSIS, INFOTAINMENT) | C | 2 |
| Industrial | Telecommunications Infrastructure and Industrial Equipment | B | 2 |
| Medical | Medical Devices classified as GHTF Class C (Japan Class III) | M | 2 |
| | Medical Devices classified as GHTF Classes A or B (Japan Classes I or II) | L | 3 |
| Consumer | General Electronic Equipment | S | 3 |
| | Only for Mobile Devices ^{*4} | E | 4 |

*Notes: 1. Based on the general specifications required for electronic components for such equipment, which are recognized by TAIYO YUDEN, the use of each product series for the equipment is recommended. Please be sure to contact TAIYO YUDEN before using our products for equipment other than those covered by the product series.

2. On each of our part number, the 2nd code from the left is a code indicating the "Category" as shown in the above table. For details, please check the explanatory materials regarding the part numbering system of each of our products.

3. Each product series is assigned a "Quality Grade" from 1 to 4 in order of higher quality. Please do not incorporate a product into any equipment with a higher Quality Grade than the Quality Grade of such product without the prior written consent of TAIYO YUDEN.

4. The applications covered by this product series are limited to mobile devices (smartphone, tablet PC, smartwatch, handheld game console, etc.) among general electronic equipment for consumer. The design, specifications and operating environment, etc. differ from those of the product series for "General Electronic Equipment" (Category: S), so please check the individual product specification sheets for details. The product series for "General Electronic Equipment" (Category: S) can also be used for mobile devices.

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (<http://www.ty-top.com/>).

2. Equipment Requiring Inquiry

Please be sure to contact TAIYO YUDEN for further information before using the products listed in this catalog for the following equipment (excluding intended equipment as specified in this catalog or the individual product specification sheets) which may cause loss of human life, bodily injury, serious property damage and/or serious public impact due to a failure or defect of the products and/or malfunction attributed thereto.

- (1) Transportation equipment (automotive powertrain control system, train control system, and ship control system, etc.)
- (2) Traffic signal equipment
- (3) Disaster prevention equipment, crime prevention equipment
- (4) Medical devices classified as GHTF Class C (Japan Class III)
- (5) Highly public information network equipment, data-processing equipment (telephone exchange, and base station, etc.)
- (6) Any other equipment requiring high levels of quality and/or reliability equal to the equipment listed above

3. Equipment Prohibited for Use

Please do not incorporate our products into the following equipment requiring extremely high levels of safety and/or reliability.

- (1) Aerospace equipment (artificial satellite, rocket, etc.)
- (2) Aviation equipment *1
- (3) Medical devices classified as GHTF Class D (Japan Class IV), implantable medical devices *2
- (4) Power generation control equipment (nuclear power, hydroelectric power, thermal power plant control system, etc.)
- (5) Undersea equipment (submarine repeating equipment, etc.)
- (6) Military equipment
- (7) Any other equipment requiring extremely high levels of safety and/or reliability equal to the equipment listed above

*Notes: 1. There is a possibility that our products can be used only for aviation equipment that does not directly affect the safe operation of aircraft (e.g., in-flight entertainment, cabin light, electric seat, cooking equipment) if such use meets requirements specified separately by TAIYO YUDEN. Please be sure to contact TAIYO YUDEN for further information before using our products for such aviation equipment.

2. Implantable medical devices contain not only internal unit which is implanted in a body, but also external unit which is connected to the internal unit.

4. Limitation of Liability

Please note that unless you obtain prior written consent of TAIYO YUDEN, TAIYO YUDEN shall not be in any way responsible for any damages incurred by you or third parties arising from use of the products listed in this catalog for any equipment that is not intended for use by TAIYO YUDEN, or any equipment requiring inquiry to TAIYO YUDEN or prohibited for use by TAIYO YUDEN as described above.

■ Safety Design

When using our products for high safety and/or reliability-required equipment or circuits, please fully perform safety and/or reliability evaluation. In addition, please install (i) systems equipped with a protection circuit and a protection device and/or (ii) systems equipped with a redundant circuit or other system to prevent an unsafe status in the event of a single fault for a failsafe design to ensure safety.

■ Intellectual Property Rights

Information contained in this catalog is intended to convey examples of typical performances and/or applications of our products and is not intended to make any warranty with respect to the intellectual property rights or any other related rights of TAIYO YUDEN or any third parties nor grant any license under such rights.

■ Limited Warranty

Please note that the scope of warranty for our products is limited to the delivered our products themselves conforming to the product specifications specified in the individual product specification sheets, and TAIYO YUDEN shall not be in any way responsible for any damages resulting from a failure or defect in our products. Notwithstanding the foregoing, if there is a written agreement (e.g., supply and purchase agreement, quality assurance agreement) signed by TAIYO YUDEN and your company, TAIYO YUDEN will warrant our products in accordance with such agreement, provided, however, that our products shall be used for general-purpose and standard use in the equipment specified in this catalog or the individual product specification sheets.

■ TAIYO YUDEN's Official Sales Channel

The contents of this catalog are applicable to our products which are purchased from our sales offices or authorized distributors (hereinafter "TAIYO YUDEN's official sales channel"). Please note that the contents of this catalog are not applicable to our products purchased from any seller other than TAIYO YUDEN's official sales channel.

■ Caution for Export

Some of our products listed in this catalog may require specific procedures for export according to "U.S. Export Administration Regulations", "Foreign Exchange and Foreign Trade Control Law" of Japan, and other applicable regulations. Should you have any questions on this matter, please contact our sales staff.

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (<http://www.ty-top.com/>).

Automotive Application Guide

We classify automotive electronic equipment into the following four application categories and set usable application categories for each of our products. Therefore, we have the corresponding product series (the 2nd code from the left side of the part number is “A” or “C”). When using our products for automotive electronic equipment, please be sure to check such application categories and use the corresponding product series accordingly. Should you have any questions on this matter, please contact us.

| Product Series (The 2nd Code from the Left Side of the Part Number) | Category | Automotive Electronic Equipment (Typical Example) |
|--|----------------|--|
| A | POWERTRAIN | <ul style="list-style-type: none"> • Engine ECU (Electronically Controlled Fuel Injector) • Cruise Control Unit • 4WS (4 Wheel Steering) • Transmission • Power Steering • HEV/PHV/EV Core Control (Battery, Inverter, DC-DC) • Automotive Locator (Car location information providing device), etc. |
| | SAFETY | <ul style="list-style-type: none"> • ABS (Anti-Lock Brake System) • ESC (Electronic Stability Control) • Airbag • ADAS (Equipment that directly controls running, turning and stopping), etc. |
| C | BODY & CHASSIS | <ul style="list-style-type: none"> • Wiper • Automatic Door • Power Window • Keyless Entry System • Electric Door Mirror • Automobile Digital Mirror • Interior Lighting • Automobile Air Conditioning System • TPMS (Tire Pressure Monitoring System) • Anti-Theft Device (Immobilizer) • ADAS (Sensor, Equipment that is not interlocked with safety equipment or powertrain), etc. |
| | INFOTAINMENT | <ul style="list-style-type: none"> • Car Infotainment System • ITS/Telematics System • Instrument Cluster Panel • Dashcam (genuine products for automotive manufacturer), etc. |

Wire-wound Ferrite Bead Inductors for Power Lines LCMC/LCMG series for Automotive Body & Chassis and Infotainment

Code in front of Series have been extracted from Part number, which describes the segment of products, such as kinds and characteristics.

AEC-Q200 Grade 3 (we conduct the evaluation at the test condition of Grade 3.)

*Operating environment Temp:-40~85°C

REFLOW

AEC-Q200

PART NUMBER

*Operating Temp. : -40~125°C (Including self-generated heat)

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|--|
| L | C | M | C | C | 3 | 2 | 1 | 6 | 1 | 1 | T | 8 | 0 | 0 | R | G | |
| ① | ② | ③ | ④ | ⑤ | ⑥ | ⑦ | ⑧ | | | | | | | | | | |

①Series

| Code (1)(2)(3)(4) | |
|----------------------|--|
| LCMC | Wire-wound Ferrite Bead Inductors for Power Lines for Automotive Body & Chassis and Infotainment |
| LCMG | Wire-wound Ferrite Bead Inductors for Power Lines for Automotive Body & Chassis and Infotainment |

(1) Product Group

| Code | |
|------|-----------|
| L | Inductors |

(2) Category

| Code | Recommended equipment | Quality Grade |
|------|---|---------------|
| C | Automotive Electronic Equipment (Body & Chassis, Infotainment) | 2 |

②Features

| Code | Feature |
|------|------------------|
| A | Standard (20MHz) |
| C | Wave-shaping |
| G | For GHz noise |

③Dimensions (L × W)

| Code | Type (inch) | Dimensions (L × W) [mm] |
|------|-------------|----------------------------|
| 1608 | 1608 (0603) | 1.6 × 0.8 |
| 2012 | 2012 (0805) | 2.0 × 1.25 |
| 2016 | 2016 (0806) | 2.0 × 1.6 |
| 3216 | 3216 (1206) | 3.2 × 1.6 |
| 3225 | 3225 (1210) | 3.2 × 2.5 |
| 4516 | 4516 (1806) | 4.5 × 1.6 |
| 4525 | 4525 (1810) | 4.5 × 2.5 |

④Dimensions (T)

| Code | Dimensions (T) [mm] |
|------|---------------------|
| 08 | 0.8 |
| | 0.85 |
| 11 | 1.1 |
| 16 | 1.6 |
| 25 | 2.5 |

(3) Type

| Code | |
|------|-------------------------|
| M | Ferrite Wire-wound bead |

(4) Features, Characteristics

| Code | |
|------|----------------|
| C | High current |
| G | High frequency |

⑤Packaging

| Code | Packaging |
|------|-----------|
| T | Taping |


⑥Nominal impedance

| Code (example) | Nominal impedance [Ω] |
|-------------------|-----------------------|
| 330 | 33 |
| 221 | 220 |
| 102 | 1000 |


⑦Impedance tolerance

| Code | Impedance tolerance |
|------|---------------------|
| R | ±25% |
| N | ±30% |

⑧Internal code

STANDARD EXTERNAL DIMENSIONS / STANDARD QUANTITY

Recommended Land Patterns
Surface Mounting

• Mounting and soldering conditions should be checked beforehand.



| Type | A | B | C |
|------|------|-----|------|
| 1608 | 1.0 | 1.0 | 1.0 |
| 2012 | 1.4 | 1.2 | 1.65 |
| 2016 | 1.4 | 1.2 | 2.0 |
| 3216 | 1.4 | 2.2 | 2.0 |
| 3225 | 1.4 | 2.2 | 2.9 |
| 4516 | 1.75 | 3.5 | 2.0 |
| 4525 | 1.75 | 3.5 | 2.9 |

Unit: mm

| Type | L | W | T | e | Standard quantity [pcs] | |
|---------------------|--------------------------|---------------------------|---------------------------|---------------------------|-------------------------|---------------|
| | | | | | Paper tape | Embossed tape |
| 160808 *1 (0603) | 1.6±0.2 (0.063±0.008) | 0.8±0.2 (0.031±0.008) | 0.8±0.2 (0.031±0.008) | 0.3±0.2 (0.012±0.008) | 4000 | — |
| 160808 *2 (0603) | 1.6±0.1 (0.063±0.004) | 0.8±0.1 (0.031±0.004) | 0.8±0.1 (0.031±0.004) | 0.3±0.15 (0.012±0.006) | 4000 | — |
| 201208 (0805) | 2.0±0.2 (0.079±0.008) | 1.25±0.2 (0.049±0.008) | 0.85±0.2 (0.033±0.008) | 0.5±0.3 (0.020±0.012) | 4000 | — |
| 201616 (0806) | 2.0±0.2 (0.079±0.008) | 1.6±0.2 (0.063±0.008) | 1.6±0.2 (0.063±0.008) | 0.5±0.3 (0.020±0.012) | — | 2000 |
| 321611 (1206) | 3.2±0.3 (0.126±0.012) | 1.6±0.2 (0.063±0.008) | 1.1±0.2 (0.043±0.008) | 0.5±0.3 (0.020±0.012) | — | 2000 |
| 321616 (1206) | 3.2±0.3 (0.126±0.012) | 1.6±0.2 (0.063±0.008) | 1.6±0.2 (0.063±0.008) | 0.5±0.3 (0.020±0.012) | — | 2000 |
| 322525 (1210) | 3.2±0.3 (0.126±0.012) | 2.5±0.3 (0.098±0.012) | 2.5±0.3 (0.098±0.012) | 0.5±0.3 (0.020±0.012) | — | 1000 |
| 451611 (1806) | 4.5±0.3 (0.177±0.012) | 1.6±0.2 (0.063±0.008) | 1.1±0.2 (0.043±0.008) | 0.5±0.3 (0.020±0.012) | — | 2000 |
| 451616 (1806) | 4.5±0.3 (0.177±0.012) | 1.6±0.2 (0.063±0.008) | 1.6±0.2 (0.063±0.008) | 0.5±0.3 (0.020±0.012) | — | 2000 |
| 452525 (1810) | 4.5±0.4 (0.177±0.016) | 2.5±0.3 (0.098±0.012) | 2.5±0.3 (0.098±0.012) | 0.9±0.6 (0.035±0.024) | — | 1000 |

*1 LCMC, *2 LCMG

Unit: mm (inch)

PART NUMBER

• All the Wire-wound Ferrite Bead Inductors for Power Lines of the catalog lineup are RoHS compliant.

Notes)

- The exchange of individual specifications is necessary depending on your application and/or circuit condition. Please contact TAIYO YUDEN's official sales channel.
- For Automotive (AEC-Q200 Qualified) products for BODY & CHASSIS, and INFOTAINMENT. Please check "Automotive Application Guide" for further details before using the products.

< AEC-Q200 : AEC-Q200 qualified >

All the Wire-wound Ferrite Bead Inductors for Power Lines for Automotive products are tested based on the test conditions and methods defined in AEC-Q200 by family item. Please consult with TAIYO YUDEN's official sales channel for the details of the product specifications and AEC-Q200 test results, etc., and please review and approve the product specifications before ordering.

Standard type

● 1608 (0603) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMCC160808T280NG | FB MJ1608HS280NTV | 28 | $\pm 30\%$ | 100 | 0.007 | 4.0 | 0.8 ± 0.2 |
| LCMCA160808T230NG | FB MJ1608HM230NTV | 23 | $\pm 30\%$ | 100 | 0.007 | 4.0 | 0.8 ± 0.2 |

● 2012 (0805) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMCC201208T250NG | FB MJ2125HS250NTV | 25 | $\pm 30\%$ | 100 | 0.004 | 6.0 | 0.85 ± 0.2 |
| LCMCC201208T420RG | FB MJ2125HS420-TV | 42 | $\pm 25\%$ | 100 | 0.008 | 4.0 | 0.85 ± 0.2 |
| LCMCA201208T210NG | FB MJ2125HM210NTV | 21 | $\pm 30\%$ | 100 | 0.004 | 6.0 | 0.85 ± 0.2 |
| LCMCA201208T330RG | FB MJ2125HM330-TV | 33 | $\pm 25\%$ | 100 | 0.008 | 4.0 | 0.85 ± 0.2 |
| LCMCG201208T8R0NG | FB MJ2125HL8R0NTV | 8 | $\pm 30\%$ | 100 | 0.008 | 4.0 | 0.85 ± 0.2 |

● 3216 (1206) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMCC321611T480NG | FB MJ3216HS480NTV | 48 | $\pm 30\%$ | 100 | 0.005 | 6.0 | 1.1 ± 0.2 |
| LCMCC321611T800RG | FB MJ3216HS800-TV | 80 | $\pm 25\%$ | 100 | 0.010 | 4.0 | 1.1 ± 0.2 |
| LCMCA321611T380NG | FB MJ3216HM380NTV | 38 | $\pm 30\%$ | 100 | 0.005 | 6.0 | 1.1 ± 0.2 |
| LCMCA321611T600RG | FB MJ3216HM600-TV | 60 | $\pm 25\%$ | 100 | 0.010 | 4.0 | 1.1 ± 0.2 |
| LCMCG321611T160NG | FB MJ3216HL160NTV | 16 | $\pm 30\%$ | 100 | 0.012 | 4.0 | 1.1 ± 0.2 |

● 4516 (1806) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMCC451611T720NG | FB MJ4516HS720NTV | 72 | $\pm 30\%$ | 100 | 0.007 | 6.0 | 1.1 ± 0.2 |
| LCMCC451611T111RG | FB MJ4516HS111-TV | 110 | $\pm 25\%$ | 100 | 0.014 | 4.0 | 1.1 ± 0.2 |
| LCMCA451611T560NG | FB MJ4516HM560NTV | 56 | $\pm 30\%$ | 100 | 0.007 | 6.0 | 1.1 ± 0.2 |
| LCMCA451611T900RG | FB MJ4516HM900-TV | 90 | $\pm 25\%$ | 100 | 0.014 | 4.0 | 1.1 ± 0.2 |
| LCMCG451611T230NG | FB MJ4516HL230NTV | 23 | $\pm 30\%$ | 100 | 0.014 | 3.5 | 1.1 ± 0.2 |

High impedance type (GHz Band)

● 1608 (0603) type

| New part number | Old part number (for reference) | Nominal impedance Measuring frequency 100 [MHz] | | Nominal impedance Measuring frequency 1 [GHz] | | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|--|------------|--|------------|--------------------------------------|-----------------------------|-------------------|
| | | (Ω) | tolerance | (Ω) | tolerance | | | |
| LCMGA160808T470RG | FB MH1608HM470-TV | 47 | $\pm 25\%$ | 75 | $\pm 40\%$ | 0.020 | 3.5 | 0.8 ± 0.1 |
| LCMGA160808T600RG | FB MH1608HM600-TV | 60 | $\pm 25\%$ | 100 | $\pm 40\%$ | 0.025 | 3.0 | 0.8 ± 0.1 |
| LCMGA160808T101RG | FB MH1608HM101-TV | 100 | $\pm 25\%$ | 170 | $\pm 40\%$ | 0.035 | 2.5 | 0.8 ± 0.1 |
| LCMGA160808T151RG | FB MH1608HM151-TV | 150 | $\pm 25\%$ | 270 | $\pm 40\%$ | 0.050 | 2.1 | 0.8 ± 0.1 |
| LCMGA160808T221RG | FB MH1608HM221-TV | 220 | $\pm 25\%$ | 370 | $\pm 40\%$ | 0.070 | 1.8 | 0.8 ± 0.1 |
| LCMGA160808T331RG | FB MH1608HM331-TV | 330 | $\pm 25\%$ | 520 | $\pm 40\%$ | 0.130 | 1.2 | 0.8 ± 0.1 |
| LCMGA160808T471RG | FB MH1608HM471-TV | 470 | $\pm 25\%$ | 750 | $\pm 40\%$ | 0.150 | 1.0 | 0.8 ± 0.1 |
| LCMGA160808T601RG | FB MH1608HM601-TV | 600 | $\pm 25\%$ | 900 | $\pm 40\%$ | 0.170 | 0.9 | 0.8 ± 0.1 |
| LCMGA160808T102RG | FB MH1608HM102-TV | 1000 | $\pm 25\%$ | 1200 | $\pm 40\%$ | 0.350 | 0.6 | 0.8 ± 0.1 |
| LCMGG160808T300RG | FB MH1608HL300-TV | 30 | $\pm 25\%$ | 120 | $\pm 40\%$ | 0.028 | 2.6 | 0.8 ± 0.1 |
| LCMGG160808T600RG | FB MH1608HL600-TV | 60 | $\pm 25\%$ | 220 | $\pm 40\%$ | 0.045 | 2.1 | 0.8 ± 0.1 |
| LCMGG160808T121RG | FB MH1608HL121-TV | 120 | $\pm 25\%$ | 540 | $\pm 40\%$ | 0.130 | 1.2 | 0.8 ± 0.1 |
| LCMGG160808T221RG | FB MH1608HL221-TV | 220 | $\pm 25\%$ | 950 | $\pm 40\%$ | 0.170 | 0.9 | 0.8 ± 0.1 |
| LCMGG160808T331RG | FB MH1608HL331-TV | 330 | $\pm 25\%$ | 1200 | $\pm 40\%$ | 0.210 | 0.8 | 0.8 ± 0.1 |
| LCMGG160808T471RG | FB MH1608HL471-TV | 470 | $\pm 25\%$ | 1500 | $\pm 40\%$ | 0.350 | 0.6 | 0.8 ± 0.1 |
| LCMGG160808T601RG | FB MH1608HL601-TV | 600 | $\pm 25\%$ | 1800 | $\pm 40\%$ | 0.450 | 0.5 | 0.8 ± 0.1 |

※) The rated current is the value of current at which the temperature of the element is increased by 40 deg.

PART NUMBER

High impedance type

● 2012 (0805) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMGA201208T800RG | FB MH2012HM800-TV | 80 | $\pm 25\%$ | 100 | 0.025 | 2.7 | 0.85 ± 0.2 |
| LCMGA201208T121RG | FB MH2012HM121-TV | 120 | $\pm 25\%$ | 100 | 0.032 | 2.5 | 0.85 ± 0.2 |
| LCMGA201208T221RG | FB MH2012HM221-TV | 220 | $\pm 25\%$ | 100 | 0.060 | 2.0 | 0.85 ± 0.2 |
| LCMGA201208T331RG | FB MH2012HM331-TV | 330 | $\pm 25\%$ | 100 | 0.080 | 1.8 | 0.85 ± 0.2 |

● 2016 (0806) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMGA201616T121NG | FB MH2016HM121NTV | 120 | $\pm 30\%$ | 100 | 0.015 | 4.5 | 1.6 ± 0.2 |
| LCMGA201616T251NG | FB MH2016HM251NTV | 250 | $\pm 30\%$ | 100 | 0.050 | 2.0 | 1.6 ± 0.2 |

● 3216 (1206) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMGA321616T221NG | FB MH3216HM221NTV | 220 | $\pm 30\%$ | 100 | 0.020 | 4.0 | 1.6 ± 0.2 |
| LCMGA321616T501NG | FB MH3216HM501NTV | 500 | $\pm 30\%$ | 100 | 0.070 | 2.0 | 1.6 ± 0.2 |

● 3225 (1210) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMGA322525T601NG | FB MH3225HM601NTV | 600 | $\pm 30\%$ | 100 | 0.042 | 3.0 | 2.5 ± 0.3 |
| LCMGA322525T102NG | FB MH3225HM102NTV | 1000 | $\pm 30\%$ | 100 | 0.100 | 2.0 | 2.5 ± 0.3 |
| LCMGA322525T202NG | FB MH3225HM202NTV | 2000 | $\pm 30\%$ | 100 | 0.130 | 1.2 | 2.5 ± 0.3 |

● 4516 (1806) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMGA451616T851NG | FB MH4516HM851NTV | 850 | $\pm 30\%$ | 100 | 0.100 | 1.5 | 1.6 ± 0.2 |

● 4525 (1810) type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|-------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMGA452525T102NG | FB MH4525HM102NTV | 1000 | $\pm 30\%$ | 100 | 0.060 | 3.0 | 2.5 ± 0.3 |
| LCMGA452525T162NG | FB MH4525HM162NTV | 1600 | $\pm 30\%$ | 100 | 0.130 | 2.0 | 2.5 ± 0.3 |

● High current type

| New part number | Old part number (for reference) | Nominal impedance (Ω) | Impedance tolerance | Measuring frequency [MHz] | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Thickness [mm] |
|--------------------|------------------------------------|-----------------------------------|---------------------|------------------------------|--------------------------------------|-----------------------------|-------------------|
| LCMCC160808T220NGR | FB MJ1608HS220NTW | 22 | $\pm 30\%$ | 100 | 0.004 | 7.5 | 0.8 ± 0.2 |
| LCMCC160808T280NGR | FB MJ1608HS280NTW | 28 | $\pm 30\%$ | 100 | 0.006 | 6.0 | 0.8 ± 0.2 |
| LCMCA160808T180NGR | FB MJ1608HM180NTW | 18 | $\pm 30\%$ | 100 | 0.004 | 7.5 | 0.8 ± 0.2 |
| LCMCA160808T230NGR | FB MJ1608HM230NTW | 23 | $\pm 30\%$ | 100 | 0.006 | 6.0 | 0.8 ± 0.2 |







※) The rated current is the value of current at which the temperature of the element is increased by 40 deg.

ELECTRICAL CHARACTERISTICS







Standard type

1608 type




2012 type



3216 type




4516 type







▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

ELECTRICAL CHARACTERISTICS





High impedance type(GHz Band)

■ 1608 type





▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

ELECTRICAL CHARACTERISTICS




High impedance type


■ 2012 type



■ 3216 type




■ 3225 type



▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).


■ ELECTRICAL CHARACTERISTICS



■ Derating of Rated Current

● LCMC/LCMG series

Derating of current is necessary for LCMC/LCMG series depending on ambient temperature. Please refer to the chart shown below for appropriate derating of current.



▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

Wire-wound Ferrite Bead Inductors for Power Lines LSMC/LSMG/LAMG/LCMC/LCMG/LBMC/LBMG/LLMC/LLMG/LMMC/LMMG series


PACKAGING

① Minimum Quantity


| Type | Standard Quantity [pcs] | |
|------------|-------------------------|---------------|
| | Paper Tape | Embossed Tape |
| 1608(0603) | 4000 | — |
| 2125(0805) | 4000 | — |
| 2012(0805) | 4000 | — |
| 2016(0806) | — | 2000 |
| 3216(1206) | — | 2000 |
| 3225(1210) | — | 1000 |
| 4516(1806) | — | 2000 |
| 4525(1810) | — | 1000 |
| 4532(1812) | — | 2000 |

② Tape Material

- Card board carrier tape




- Embossed tape



③ Taping Dimensions

- Paper tape (0.315 inches wide)




► This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

| Type | Chip Cavity | | Insertion Pitch | Tape Thickness |
|----------------|--|--|--|--|
| | A | B | | |
| 1608 (0603) | 1.0 ± 0.2 (0.039 ± 0.008) | 1.8 ± 0.2 (0.071 ± 0.008) | 4.0 ± 0.2 (0.157 ± 0.008) | 1.1max (0.043max) |
| 2012 (0805) | 1.5 ± 0.2 (0.059 ± 0.008) | 2.3 ± 0.2 (0.091 ± 0.008) | 4.0 ± 0.2 (0.157 ± 0.008) | 1.1max (0.043max) |

Unit : mm (inch)

● Embossed tape (0.315 inches wide)




| Type | Chip Cavity | | Insertion Pitch | Tape Thickness | |
|-------------------|--|--|--|--|--|
| | A | B | | K | T |
| 2016 (0806) | 1.8 ± 0.2 (0.071 ± 0.008) | 2.2 ± 0.2 (0.087 ± 0.008) | 4.0 ± 0.2 (0.157 ± 0.008) | 2.6max (0.102max) | 0.6max (0.024max) |
| 3216 *1 (1206) | 1.9 ± 0.2 (0.075 ± 0.008) | 3.5 ± 0.2 (0.138 ± 0.008) | 4.0 ± 0.2 (0.157 ± 0.008) | 1.5max (0.059max) | 0.3max (0.012max) |
| 3216 *2 (1206) | 1.9 ± 0.2 (0.075 ± 0.008) | 3.5 ± 0.2 (0.138 ± 0.008) | 4.0 ± 0.2 (0.157 ± 0.008) | 2.6max (0.102max) | 0.6max (0.024max) |
| 3225 (1210) | 2.8 ± 0.2 (0.110 ± 0.008) | 3.5 ± 0.2 (0.138 ± 0.008) | 4.0 ± 0.2 (0.157 ± 0.008) | 4.0max (0.157max) | 0.6max (0.024max) |

Unit : mm (inch)

*1 LSMC/LCMC/LBMC/LLMC/LMMC

*2 LSMG/LAMG/LCMG/LBMG/LLMG/LMMG

● Embossed tape (0.472 inches wide)




| Type | Chip Cavity | | Insertion Pitch | Tape Thickness | |
|-------------------|--|--|--|--|--|
| | A | B | | K | T |
| 4516 *1 (1806) | 1.9 ± 0.2 (0.075 ± 0.008) | 4.9 ± 0.2 (0.193 ± 0.008) | 4.0 ± 0.2 (0.157 ± 0.008) | 1.5max (0.059max) | 0.3max (0.012max) |
| 4516 *2 (1806) | 1.9 ± 0.2 (0.075 ± 0.008) | 4.9 ± 0.2 (0.193 ± 0.008) | 4.0 ± 0.2 (0.157 ± 0.008) | 2.6max (0.102max) | 0.6max (0.024max) |
| 4525 (1810) | 2.9 ± 0.2 (0.114 ± 0.008) | 4.9 ± 0.2 (0.193 ± 0.008) | 4.0 ± 0.2 (0.157 ± 0.008) | 4.0max (0.157max) | 0.6max (0.024max) |
| 4532 (1812) | 3.6 ± 0.2 (0.142 ± 0.008) | 4.9 ± 0.2 (0.193 ± 0.008) | 8.0 ± 0.2 (0.315 ± 0.008) | 4.0max (0.157max) | 0.6max (0.024max) |

Unit : mm (inch)

*1 LSMC/LCMC/LBMC/LLMC/LMMC


*2 LSMG/LAMG/LCMG/LBMG/LLMG/LMMG

④ Leader and Blank portion



Insertion leader is 400 mm or more (including 20 empty cavities)
 Empty cavities at end of reel: 40 holes or more


⑤ Reel size



| Type | ϕD | ϕd | W | t |
|--|-----------------------------|----------------------------|---------------------------|----------------------|
| 1608(0603) 2012(0805) 2016(0806) 3216(1206) 3225(1210) | 180+0/-3 (7.09+0/-0.118) | 60+1/-0 (2.36+0.039/-0) | 10.0±1.5 (0.394±0.059) | 2.5max (0.098max) |
| 4516(1806) 4525(1810) | | | 14.0±1.5 (0.551±0.059) | |
| 4532(1812) | 330±2.0 (12.99±0.080) | 100±1.0 (3.94±0.039) | 14.0±2.0 (0.551±0.080) | 3.0max (1.181max) |

Unit : mm (inch)

⑥ Top tape strength



The top tape requires a peel-off force of 0.1 to 1.0N (0.315 inches wide) / 0.1 to 1.3N (0.472 inches wide) in the direction of the arrow as illustrated below.

Wire-wound Ferrite Power Inductors LCXN/LCXP series

■ RELIABILITY DATA

1. Operating Temperature Range

| | |
|--------------------------|--|
| Specified Value | -40~+125°C (Including self-generated heat) |
| Test Methods and Remarks | Including self-generated heat |

2. Storage Temperature Range

| | |
|--------------------------|---|
| Specified Value | -40~+85°C |
| Test Methods and Remarks | -5 to 40°C for the product with taping. |

3. Rated current

| | |
|-----------------|--------------------------------|
| Specified Value | Within the specified tolerance |
|-----------------|--------------------------------|

4. Impedance

| | |
|--------------------------|---|
| Specified Value | Within the specified tolerance |
| Test Methods and Remarks | Measuring equipment : Impedance analyzer (HP4291A) or its equivalent Measuring frequency : 100±1 MHz |

5. DC Resistance

| | |
|-----------------|--------------------------------|
| Specified Value | Within the specified tolerance |
|-----------------|--------------------------------|

6. High Temperature Exposure (Storage)

| | |
|--------------------------|--|
| Specified Value | Appearance: No significant abnormality in appearance. Impedance change : Within ±30% of the initial value |
| Test Methods and Remarks | 1000 hours at 125 deg C Unpowered |

7. Temperature Cycling

| | |
|--------------------------|---|
| Specified Value | Appearance: No significant abnormality in appearance. Impedance change : Within +50/-10% of the initial value |
| Test Methods and Remarks | 1000 cycles (-40 deg C to +125 deg C) 30 min. maximum dwell time at each temperature extreme. 1 min. maximum transition time. |

8. Biased Humidity

| | |
|--------------------------|--|
| Specified Value | Appearance: No significant abnormality in appearance. Impedance change : Within ±30% of the initial value |
| Test Methods and Remarks | 1000 hours, 85 deg C/85% RH. Rated current |

9. Operational Life

| | |
|--------------------------|--|
| Specified Value | Appearance: No significant abnormality in appearance. Impedance change : Within ±30% of the initial value |
| Test Methods and Remarks | 1000 hours, 85 deg C Rated current |

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

10. Resistance to Solvents

| | |
|--------------------------|---|
| Specified Value | Appearance : No significant abnormality in appearance. |
| Test Methods and Remarks | ① Soak a test sample in isopropyl alcohol (IPA) at 25 ± 5 deg C for 3 to 3.5 minutes. ② Take the test sample out and brush 10 times using a brush soaked in IPA. ③ Repeat ① and ② twice more. |

11. Mechanical Shock

| | |
|--------------------------|---|
| Specified Value | Appearance : No significant abnormality in appearance. Impedance change : Within $\pm 30\%$ of the initial value |
| Test Methods and Remarks | Apply 3 shocks in each direction along 3 mutually perpendicular axes of the test specimen (18 shocks in total). Peak value: 100g Duration: 6ms Test pulse: Half-sine Velocity change: 3.7m/s. |

12. Vibration

| | |
|--------------------------|---|
| Specified Value | Appearance : No significant abnormality in appearance. Impedance change : Within $\pm 30\%$ of the initial value |
| Test Methods and Remarks | 5g's for 20 min., 12 cycles each of 3 orientations (36 cycles in total) Test from: 10 Hz to 2000 Hz |

13. Resistance to Soldering Heat (Reflow)

| | |
|--------------------------|--|
| Specified Value | Appearance : No significant abnormality in appearance. Impedance change : Within $\pm 30\%$ of the initial value |
| Test Methods and Remarks | Reflow peak temperature: 260 ± 5 deg C Duration time: 10 ± 1 sec. Measure after inductors are kept at room temperature for 24 ± 4 hours. |


14. ESD

| | |
|--------------------------|---|
| Specified Value | Appearance : No significant abnormality in appearance. Impedance change : Within $\pm 30\%$ of the initial value |
| Test Methods and Remarks | Per AEC-Q200-002 |

15. Solderability


| | |
|--------------------------|--|
| Specified Value | More than 90% of terminal electrode shall be covered with fresh solder. |
| Test Methods and Remarks | Per J-STD-002 a) Method B Solder at 235 ± 5 deg C for 5 sec. c) Method D Solder at 260 ± 5 deg C for 30 sec. |

16. Board Flex

| | |
|--------------------------|--|
| Specified Value | Appearance : No significant abnormality in appearance. Impedance change : Within $\pm 30\%$ of the initial value |
| Test Methods and Remarks | Solder the test samples to the test boards by the reflow soldering. Apply a force in a downward direction until amount of deflection reaches 2mm. The 2-mm deflection shall be held for 60 sec. Test board dimensions: 100mm × 40mm × 1.6mm.  |

► This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

17. Terminal Strength (SMD)

| | |
|--------------------------|---|
| Specified Value | Appearance :No significant abnormality in appearance. |
| Test Methods and Remarks | Apply a force of 17.7N for 60±5 sec.  |

18. Standard condition

| | |
|-----------------|--|
| Specified Value | Note on standard condition: "standard condition" referred to herein is defined as follows: 5 to 35°C of temperature, 45 to 85% relative humidity and 86 to 106kPa of air pressure. When there are questions concerning measurement results: In order to provide correlation data, the test shall be conducted under condition of 20±2°C of temperature, 60 to 70% relative humidity and 86 to 106kPa of air pressure. Unless otherwise specified, all the tests are conducted under the "standard condition." |
|-----------------|--|

► This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

Wire-wound Ferrite Bead Inductors for Power Lines LSMC/LSMG/LAMG/LCMC/LCMG/LBMC/LBMG/LLMC/LLMG/LMMC/LMMG series

PRECAUTIONS

1. Circuit Design

Precautions

- ◆ Verification of operating environment, electrical rating and performance
 1. A malfunction in medical equipment, spacecraft, nuclear reactors, etc. may cause serious harm to human life or have severe social ramifications. As such, any inductors to be used in such equipment may require higher safety and/or reliability considerations and should be clearly differentiated from components used in general purpose applications.
 2. When inductors are used in places where dew condensation develops and/or where corrosive gas such as hydrogen sulfide, sulfurous acid, or chlorine exists in the air, characteristic deterioration may occur. Please do not use inductors under such environmental conditions.
- ◆ Operating Current (Verification of Rated current)
 1. The operating current including inrush current for inductors must always be lower than their rated values.
 2. Do not apply current in excess of the rated value because the inductance may be reduced due to the magnetic saturation effect.
- ◆ Temperature rise

Temperature rise of power choke coil depends on the installation condition in end products.
Make sure that temperature rise of power choke coils in actual end products is within the specified temperature range.

2. PCB Design

Precautions

- ◆ Land pattern design
 1. Please refer to a recommended land pattern.

3. Considerations for automatic placement

Precautions

- ◆ Adjustment of mounting machine
 1. Excessive impact load should not be imposed on the products when mounting onto the PC boards.
 2. Mounting and soldering conditions should be checked beforehand.

Technical considerations

- ◆ Adjustment of mounting machine
 1. When installing products, care should be taken not to apply distortion stress as it may deform the products.

4. Soldering

Precautions

- ◆ Wave soldering
 1. Please refer to the specifications in the catalog for a wave soldering.
- ◆ Reflow soldering
 1. Please contact any of our offices for a reflow soldering, and refer to the recommended condition specified.
- ◆ Lead free soldering
 1. When using products with lead free soldering, we request to use them after confirming adhesion, temperature of resistance to soldering heat, etc. sufficiently.
- ◆ Preheating when soldering


Heating : The temperature difference between soldering and remaining heat should not be greater than 150°C.
Cooling : The temperature difference between the components and cleaning process should not be greater than 100°C.
- ◆ Recommended conditions for using a soldering iron

Put the soldering iron on the land-pattern.
Soldering iron's temperature – Below 350°C
Duration – 3 seconds or less
The soldering iron should not directly touch the inductor.

Technical considerations

- ◆ Wave, Reflow, Lead free soldering
 1. If products are used beyond the range of the recommended conditions, heat stresses may deform the products, and consequently degrade the reliability of the products.

【Recommended reflow condition】



- ◆ Preheating when soldering
 1. There is a case that products get damaged by a heat shock.