

Low noise and low drop voltage regulator with shutdown function

Datasheet - production data



Description

The LK112S is a low-dropout linear regulator with shutdown function. The internal switch can be controlled by TTL or CMOS logic levels. The device is ON when the control pin is pulled to a high logic level. An external capacitor can be connected to the noise bypass pin to reduce the output noise level to 30 μ Vrms. An internal PNP pass transistor is used to achieve a low-dropout voltage.

The LK112S has a very low quiescent current in ON mode while in OFF mode the I_q is reduced to 100 nA max. The internal thermal shutdown circuitry limits the junction temperature below 150 °C. The load current is internally monitored and in the presence of a short-circuit or overcurrent conditions at the output, the device shuts down.

Features

- Output current up to 200 mA
- Low-dropout voltage (500 mV max. at $I_{OUT} = 200$ mA)
- Very low quiescent current: 0.1 μ A in OFF mode and max. 250 μ A in ON mode at $I_{OUT} = 0$ mA
- Low output noise: typ. 30 μ V at $I_{OUT} = 60$ mA and 10 Hz < f < 80 kHz
- Wide range of output voltages
- Internal current and thermal limit
- V_{OUT} tolerance $\pm 2\%$ (at 25 °C)
- Operative input voltage from: $V_{OUT} + 0.5$ to 14 V (for $V_{OUT} > 2$ V) or from 2.5 V to 14 V (for $V_{OUT} < 2$ V)

Table 1. Device summary


| Part number | Output voltage |
|-------------|----------------|
| LK112SM18TR | 1.8 V |
| LK112SM33TR | 3.3 V |
| LK112SM50TR | 5.0 V |

Contents

| | | |
|---|-----------------------------------|----|
| 1 | Diagram | 3 |
| 2 | Pin configuration | 4 |
| 3 | Maximum ratings | 5 |
| 4 | Electrical characteristics | 6 |
| 5 | Typical characteristics | 7 |
| 6 | Package mechanical data | 12 |
| 7 | Packaging mechanical data | 14 |
| 8 | Revision history | 16 |


1 Diagram

Figure 1. Schematic diagram



2 Pin configuration

Figure 2. Pin connection (top view)



SC12360

Table 2. Pin description

| Pin n° | Symbol | Note |
|--------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | SHDN | Shutdown input disables the regulator when it is connected to GND or to a positive voltage lower than 0.6 V |
| 2 | GND | Ground pin: internally connected to the die attach flag to decrease the total thermal resistance and increase the package ability to dissipate power |
| 3 | Bypass | Bypass pin: 0.1 μ F bypass to improve the thermal noise performance |
| 4 | OUT | Output port |
| 5 | IN | Input port |

3 Maximum ratings

Table 3. Absolute maximum ratings

| Symbol | Parameter | Value | Unit |
|------------|--------------------------------------|--------------------|------|
| V_I | DC input voltage | 16 | V |
| V_{SHDN} | DC input voltage | 16 | V |
| I_O | Output current | Internally limited | |
| T_{STG} | Storage temperature range | -55 to 150 | °C |
| T_{OP} | Operating junction temperature range | -40 to 125 | °C |

Table 4. Thermal data

| Symbol | Parameter | SOT23-5L | Unit |
|------------|-------------------------------------|----------|------|
| R_{thJC} | Thermal resistance junction-case | 81 | °C/W |
| R_{thJA} | Thermal resistance junction-ambient | 255 | °C/W |

4 Electrical characteristics

$T_J = 25^\circ\text{C}$, $V_{IN} = V_{OUT} + 1\text{ V}$, $I_{OUT} = 0\text{ mA}$, $V_{SHDN} = 1.8\text{ V}$, $C_I = 1\text{ }\mu\text{F}$, $C_O = 2.2\text{ }\mu\text{F}$, $C_{BYPASS} = 0.1\text{ }\mu\text{F}$ unless otherwise specified.

Table 5. LK112S electrical characteristics

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|------------------|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|----------------------------|
| I_d | Quiescent current | ON mode (except I_{SHDN}) | | 175 | 250 | μA |
| | | OFF mode, $V_I = 8\text{ V}$, $V_{SHDN} = 0\text{ V}$ | | 0 | 0.1 | μA |
| V_O | Output voltage | $I_O = 30\text{ mA}$ | -2 | | +2 | % |
| ΔV_O | Line regulation | $V_I = V_O + 1\text{ V}$ to $V_O + 6\text{ V}$, $V_O \leq 5.6\text{ V}$ | | 0.7 | 20 | mV |
| | | $V_I = V_O + 1\text{ V}$ to $V_O + 6\text{ V}$, $V_O > 5.6\text{ V}$ | | 0.8 | 40 | mV |
| ΔV_O | Load regulation | $I_O = 1$ to 60 mA | | 15 | 30 | mV |
| | | $I_O = 1$ to 200 mA | | 30 | 90 | mV |
| V_d | Dropout voltage | $I_O = 60\text{ mA}$ | | 0.17 | 0.24 | V |
| | | $I_O = 200\text{ mA}^{(1)}$ | | 0.35 | 0.5 | V |
| I_{SC} | Short-circuit current | | 200 | | | mA |
| SVR | Supply voltage rejection | $V_I = V_O + 1.5\text{ V}$, $C_{BYP} = 0.1\text{ }\mu\text{F}$ $C_O = 10\text{ }\mu\text{F}$, $f = 400\text{ Hz}$, $I_O = 30\text{ mA}$ | | 55 | | dB |
| eN | Output noise voltage | $B = 10\text{ Hz}$ to 80 kHz , $C_{BYP} = 0.1\text{ }\mu\text{F}$ $C_O = 10\text{ }\mu\text{F}$, $V_I = V_O + 1.5\text{ V}$, $I_O = 60\text{ mA}$ | | 30 | | μVRms |
| I_{SHDN} | Shutdown input current | $V_{SHDN} = 1.8\text{ V}$, output ON | | 12 | 35 | μA |
| V_{SHDN} | Shutdown input logic | Output ON | 1.8 | | | V |
| | | Output OFF | | | 0.6 | |
| $\Delta V_O/T_J$ | Output voltage temperature coefficient | $I_O = 10\text{ mA}$ | | 0.09 | | $\text{mV}/^\circ\text{C}$ |

1. For versions with an output voltage higher than 2.1 V only.

Note: For versions with an output voltage lower than 2 V $V_{IN} = 2.4\text{ V}$

5 Typical characteristics

(Unless otherwise specified, $T_J = 25^\circ\text{C}$, $C_I = 1 \mu\text{F}$, $C_O = 2.2 \mu\text{F}$, $C_{\text{BYP}} = 100 \text{nF}$)

Figure 3. Output voltage vs temperature




Figure 4. Output voltage vs temperature




Figure 5. Line regulation vs temperature




Figure 6. Load regulation vs temperature










Figure 7. Dropout voltage vs temperature**Figure 8. Short-circuit current vs dropout voltage****Figure 9. Output voltage vs input voltage****Figure 10. Shutdown voltage vs temperature****Figure 11. Shutdown current vs shutdown voltage****Figure 12. Supply voltage rejection vs temperature**

Figure 13. Supply voltage rejection vs output current




Figure 14. Supply voltage rejection vs frequency




Figure 15. Supply voltage rejection vs temperature




Figure 16. Shutdown current vs temperature




Figure 17. Quiescent current vs input voltage




Figure 18. Quiescent current vs shutdown voltage
















Figure 19. Quiescent current vs temperature**Figure 20. Reverse current vs reverse voltage****Figure 21. Stability****Figure 22. Noise spectrum****Figure 23. Start-up transient $C_{BYP}=10$ nF****Figure 24. Start-up transient $C_{BYP}=100$ nF**

Figure 25. Line transient Co=100 μ FFigure 26. Line transient Co=10 μ FFigure 27. Line transient Co=1 μ FFigure 28. Load transient Vo=2.5 V, Co=2.2 μ FFigure 29. Load transient Vo=2.5 V, Co=10 μ FFigure 30. Load transient Vo=3.8 V, Co=2.2 μ F

6 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com.
ECOPACK® is an ST trademark.

Figure 31. SOT23-5L mechanical drawings





Table 6. SOT23-5L mechanical data

| Dim. | mm | | |
|------|------|------|------|
| | Min. | Typ. | Max. |
| A | 0.90 | | 1.45 |
| A1 | 0 | | 0.15 |
| A2 | 0.90 | | 1.30 |
| b | 0.30 | | 0.50 |
| c | 2.09 | | 0.20 |
| D | | 2.95 | |
| E | | 1.60 | |
| e | | 0.95 | |
| H | | 2.80 | |
| L | 0.30 | | 0.60 |
| θ | 0 | | 8 |

Figure 32. SOT23-5L recommended footprint (dimensions in mm)

7 Packaging mechanical data

Figure 33.SOT23-5L tape and reel drawings




Figure 34.SOT23-5L tape and reel mechanical data

| Dim. | mm | | |
|------|------|------|------|
| | Min. | Typ. | Max. |
| A | | | 180 |
| C | 12.8 | 13.0 | 13.2 |
| D | 20.2 | | |
| N | 60 | | |
| T | | | 14.4 |
| Ao | 3.13 | 3.23 | 3.33 |
| Bo | 3.07 | 3.17 | 3.27 |
| Ko | 1.27 | 1.37 | 1.47 |
| Po | 3.9 | 4.0 | 4.1 |
| P | 3.9 | 4.0 | 4.1 |

8 Revision history

Table 7. Document revision history

| Date | Revision | Changes |
|-------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 31-Aug-2004 | 3 | Mistake on fig. 19. |
| 31-Jan-2005 | 4 | Change maturity code. |
| 12-Jun-2006 | 5 | Order codes updated. |
| 17-Oct-2006 | 6 | The T_{OP} value on table 2 updated. |
| 20-Jul-2007 | 7 | Add Table 1 in cover page. |
| 21-Sep-2007 | 8 | Features updated. |
| 11-Dec-2007 | 9 | Modified: Table 6 . |
| 12-Feb-2008 | 10 | Modified: Table 6 . |
| 10-Jul-2008 | 11 | Modified: Table 1 and Table 6 . |
| 11-Feb-2014 | 12 | Part number LK112Sxx changed to LK112S. Updated the title and the Description in cover page, Table 2: Pin description , Section 5: Typical characteristics and Section 6: Package mechanical data . Added Section 7: Packaging mechanical data . Minor text changes. |