



# Layerscape® LX2162A Communications Processor



The Layerscape LX2162A processor features 16 Arm®v8 Cortex®-A72 cores for server-level performance in a tiny 23 x 23 mm package. With twelve SerDes lanes supporting PCIe® Gen 3 and 4 x 25 Gigabit Ethernet and the low power of 16nm FinFET process technology, this processor is ideal for space-constrained high-performance boards.

## OVERVIEW

The LX2162A processor squeezes the processing capability of the popular LX2160A device into a package that is nearly one quarter the size, making it suitable for small boards such as network interface cards, COM Express Type 7 modules, OCP3 mezzanine cards, and custom daughter cards. It retains LX2160A's 16 Cortex-A72 cores, 50 Gbit/s security engine and 88 Gbit/s data compression engine. It has 12 SerDes lanes at up to 25 Gbit/s, which can support four 25 Gbit Ethernet and x8 PCIe Gen3 simultaneously, among many other combinations.

## FEATURES

- 16 64-bit Armv8 Cortex-A72 CPU cores, running up to 2.0 GHz
- 16 MB cache
- DDR4 72b including ECC, to 2900 MT/s, maximum capacity of 32 GB
- 2 MB packet caching buffer
- 12 SerDes lanes, operating up to 25 GHz
- Up to 12 Ethernet ports
- Supported Ethernet speeds include 1, 2.5, 10, 25, 40, and 50 Gbit/s
- 105 Gbit/s Layer 2 Ethernet switch
- Up to 12 PCIe Gen3 lanes, supporting three ports, as wide as x8
- 50 Gbit/s security accelerator
- 88 Gbit/s data compression/decompression engine
- 4 x SATA3.0
- Secure boot and Arm TrustZone® technology
- 2 x SD / eMMC, 3 x SPI, one 8-bit SPI, 2 x DUART, 8 x I<sup>2</sup>C, 1 x USB3.0, 2 x CAN (FD optional)

## TARGET APPLICATIONS

The LX2162A processor targets space-constrained boards. Designers can use it on a network interface card (NIC) as the control lane to a data path ASIC or FPGA. It also can be the main processor on a 2 x 25 Gbit Ethernet NIC. For industrial applications, designers can incorporate it into standard module form factors such as COM Express, mini-ITX and OCP 3.0.




## RELATED SOFTWARE

- Linux® SDK for Layerscape Processors
- CodeWarrior® Development Software for Armv8 64-bit based Layerscape Series Processors

APPLICATION	EXAMPLES	RELEVANT FEATURES
Data center offload	<ul style="list-style-type: none"> <li>• 2 x 25 Gbit/s NIC</li> <li>• Control plane on FPGA-based NIC</li> </ul>	<ul style="list-style-type: none"> <li>• 8 x PCIe® Gen 3 with SR-IOV</li> <li>• Low power due to 16nm FinFET process technology</li> <li>• Data-center friendly 25 Gbit Ethernet ports</li> </ul>
Standard industrial module	<ul style="list-style-type: none"> <li>• COM Express Type 7</li> <li>• Mini-ITX</li> <li>• OCP 3.0 mezzanine card</li> </ul>	<ul style="list-style-type: none"> <li>• 23 x 23 mm package</li> <li>• Three PCIe Gen3 controllers</li> <li>• Flexible SerDes configs</li> </ul>

## LAYERSCAPE LX2162A BLOCK DIAGRAM



## LAYERSCAPE LX2162A FAMILY MEMBERS

	LX2162A	LX2122A	LX2082A
Cores	16	12	8
L2 Cache	8 MB	6 MB	8 MB
SerDes	12 lanes at up to 25 GHz		
PCIe®	3 x Gen3, max width of x8		
DDR	DDR4, 2900 MT/s, 32 GB capacity		
Platform cache + PEB	10 MB		
Ethernet	105 Gbit/s L2 switch, supporting combinations of 12 ports of 1, 2.5, 10, 25, 40, and 50 Gbit Ethernet		
Security	50 Gbit/s		
Data Compression Engine	88 Gbit/s		
Package	23 x 23 mm, 1150 pins		

[www.nxp.com/LX2162A](http://www.nxp.com/LX2162A)

NXP, the NXP logo, CodeWarrior and Layerscape are trademarks of NXP B.V. All other product or service names are the property of their respective owners. Arm, Cortex and TrustZone are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. The related technology may be protected by any or all patents, copyrights, designs and trade secrets. All rights reserved. © 2020 NXP B.V.

Document Number: LX2162AFSA4 REV 3  
Date of Release: October 2020