

# M-290 SERIES BATTERY DISCONNECT SWITCHES



M-290-01

## Features and Benefits

- Marine grade, brass case
- O-ring Sealed options in bushing
- UL listed P/Ns
- Compact design
- Silver plated contact options for high conductivity and low contact resistance

## Specifications Overview

<b>Max Input Current:</b>	1000A intermittent for 15 sec ON, 5 min OFF
<b>Voltage Rating:</b>	32V DC
<b>Housing:</b>	Brass
<b>Contacts:</b>	Two silver plated brass 3/8-24 studs Two brass 10-32 studs
<b>Circuitry:</b>	DPST

## Applications

- Commercial Marine
- Boating
- Emergency Vehicles
- Heavy Duty Truck
- Bus/Transit

## Recommended Products



**24505 & 24505-01  
Lockout Lever Kit**

## Description

M-290 Series Battery Disconnect Switches are marine grade, manual, master disconnect switches. The M-290 switches shown are 36V Dual Pole, Single Throw (DPST) and can be used to disconnect the battery from the vehicle electrical system. The shown switches have a 1000A intermittent current rating for 15 sec ON, 5 min OFF. Disconnecting the battery from the electrical system prevents potential thermal events and ensures system shut down during maintenance or emergency. Battery disconnect switches also prevent parasitic loads from draining the battery during inactivity.

## Web Resources

Download 2D print and technical resources at:  
[littelfuse.com/M290](http://littelfuse.com/M290)

## Ordering Information

PART NUMBER	DESCRIPTION	AMPERAGE	UL LISTED
M-290-01 *	36V Marine Grade Battery Disconnect Switch	175A	
M-290-05 *	36V Marine Grade Battery Disconnect Switch	125A	•

\* Box and Retail Blister Pack Available



Visit [Littelfuse.com](http://Littelfuse.com) for the most up-to-date product information. Littelfuse products are designed for specific applications and should not be used for any purpose (including, without limitation, automotive applications) not expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse product documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse product documentation.