


STAMP: 91836 M39012/20-0503 KC-59-419 XXXX (DATE CODE)

NOTES:

1. FOR USE WITH RG-142, 223 AND 400/U CABLE.
2. FOR CABLING INSTRUCTIONS SEE CP-465.
3. FOR CABLE TRIMMING USE KTJ-113 AND KTD-166.
4. FOR CRIMPING USE DIE KTH-2001.
5. INTERFACE PER MIL-STD-348, FIG. 301.1
6. MATERIALS:
 - INSULATORS-PTFE, ASTM-D-1710
 - GASKET-SILICONE RUBBER, A-A-59588
 - SPRING WASHER
 - CENTER CONTACT } BER. COP., ASTM-B-196
 - OUTER CONTACT }
 - ALL OTHER METAL PARTS-BRASS, ASTM-B16
7. FINISHES:
 - CENTER CONTACTS-GOLD PLATE PER ASTM B488
 - ALL OTHER METAL PARTS-SILVER PLATE PER ASTM B700
8. ELECTRICAL CHARACTERISTICS:
 - NOMINAL IMPEDANCE-50 OHMS
 - WORKING VOLTAGE-500 VRMS
 - FREQUENCY RANGE-DC TO 4 GHz

REVISIONS	
ISSUE	CHANGES
10	CN 34436 C REDRAWN JCA 02/16/93
11	CN 35406 A MJB 03/10/94
N	REVISED PER ER23216 GGR 04/12/2010
P	UPDATED PER DMF306, ER061575 CY 01/27/16
Q	REVERTED TO SHOW MIL# ER064289 JI 09/30/16
R	ADDED Q-# TO BOM ER065400 CY 01/17/17
S	ER068761 JI 06/21/17
JCA3540	
CUSTOMER SALES DRAWING	
SCALE 4:1	
APPROX SURFACE AREA	
KC-59-419	
USED ON	
REF:	
PLUG, ANGLE, BNC	
DRAWN JCA	DATE 02/16/93
DESIGN MJB	DATE 02/17/93
APPR.	DATE
 Winchester Electronics Corporation 199 Park Road Ext Suite 104 Middlebury, Connecticut 06762	
M39012/20-0503	

M39012/20-0503