



- NOTES:  
 1.) MATING END DIM'S. PER MD-121.  
 2.) PKG. ITEMS 2 & 6 LOOSE WITH CONNECTOR.  
 3.) PKG. ITEMS 4 & 5 LOOSE AS ONE UNIT WITH CONNECTOR.

SYM	DESCRIPTION	DATE	APPN	UNLESS OTHERWISE SPECIFIED 1. ALL DIMENSIONS ARE AFTER PLATING 2. BREAK ALL CORNERS & EDGES 90° R MAX 3. CHAMFER IT & LAST THREADS 45° 4. SURFACE ROUGHNESS 32 ✓ MIL STD 10 5. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.D 6. REMOVE ALL BURRS	SOLITRON/MICROWAVE PORT SALERNO, FLORIDA	REF		
—	REL. DCN Z0323	3/92	RD7	DIMENSIONS ARE IN INCHES TOLERANCES DECIMALS FRACTIONAL ANGULAR .010 .010 30° ± .1° .015 1/100 30° ± .1° .005 .005 30° ± .1°	MATERIAL —	TITLE SMB JACK TO RG 188, 4316/U CABLE.		
A	REV. DCN 20476	8/92	RD7		FINISH —		DRAWING NO M39012/68B0009	
B	REV. DCN. 20666	4-93	DWE		AREA —			SHEET 2 OF 2
				DRAWN J.B.G. DATE 3-2-92	SCALE 6/1	CODE IDENT NO 95077	SIZE A	
				CHECKED DWE DATE 3-11-92				
				APPROVED RD7 DATE 3-13-92				

# ENG. FILE COPY

M39012/ <b>68B0009</b>	MIL. REV. <b>B</b>	REV.	DESCRIPTION	DATE	APPROVAL
		—	REL. DCU 20323	3/92	RD7
		A	REV. DCN 20476	8/92	RD7
		B	REV. DCN. 20666	4-93	DWC

ITEM #	PART NUMBER	REV.	QTY.	U/M	DESCRIPTION	TROY OZ.	PLATING 400-01-	REV.	LEVEL					
									0	1	2	3	4	
1	012-23-045		1	EA	BODY	.00033	112		X					
2	033-23-034		1	EA	CONTACT	.00007	143		X					
3	244-23-036		1	EA	INSULATOR	—	—		X					
4	244-23-025		1	EA	INSULATOR	—	—		X					
5	052-23-009		1	EA	FERRULE	.00026	112		X					
6	040-23-004		1	EA	CRIMP RING	.00016	112		X					
7	300-80-508		1	EA	CABLE ASSY. INSTR.	—	—		X					

DRAWN	J.G.	DATE	3/92	MARKING: MARK BODY M39012/68B0009, 95077 PER 400-05-004, TYPE 3. MARK CABLE ASSY. INSTR. M39012/68B0009 & DATE CODE PER 400-05-004, TYPE 8.
CHECKED	DWC	DATE	3/92	
APPROVED	RD7	DATE	3/92	
<b>PARTS LIST</b>				SHEET 1 OF 2
<b>Solitron/Microwave</b>		Div. of Solitron Devices, Inc. P. O. Box 278, Port Salerno, Fla. 33492		MFR IDENT CODE 95077
			M39012/ <b>68B0009</b>	