



| M50 SERIES
POWER MODULES



Features

- Over 40KW output Capability
- 8 Different Circuits to Choose from
- 50 and 100 A outputs
- UL Recognized E72445

ORDERING OPTIONS

M50 - **50** - **1** - **2** - **F** - **V**

Series **M50**

Load Current **50**: 50 Amps
100: 100 Amps

Circuit Type **1 2 3 4 5 6 7 8**
(See schematic diagrams)

AC Line Voltage **1**: 120 VAC
2: 240 VAC
3: 280 VAC
2: 380 VAC
3: 480 VAC

Free Wheeling Diode **Blank**: Not Included
F: Included (Circuits 1 & 2 only)

External Suppressor **Blank**: Not included
V: Include (Circuits 1, 2, 3, 4, 6 & 7 only)

— Required for valid part number
□ For options only and not required for valid part number


NOTE: Not all Combinations available

ELECTRICAL SPECIFICATIONS

Description	Symbol	M5060	M50100
Maximum DC Output Current (T _c = 85°C)	I _D	60 A	100 A
Maximum Voltage Drop @ Amps Peak	V _F	1.35V @ 50A	1.2V @ 100 A
Operating Junction Temperature Range	T _J	-40 - 125°C	-40 - 125°C
		400 (120 VAC)	
		600 (240 VAC)	
Repetitive Peak Reverse Voltage (AC Line Nominal) [Vpk]	V _{RRMS}	800 (280 VAC)	
		1200 (480 VAC)	
		1400 (530 VAC)	
		1600 (600 VAC)	
Maximum Non-Repetitive Surge Current (1/2 Cycle, 60 Hz) [A]	I _{TSM}	800	1500
Maximum I ² t for Fusing (t=8.3ms)[A ² sec]	I ² T	2650	9350
Maximum Thermal Resistance, Junction to Ceramic Base per Chip [°C/W]	R _{Jc}	0.45°C/W	0.3°C/W
Insulation Voltage [Vrms]	V _{ISOL}	2500	
Weight (typical)		4.5 oz (158g)	

MECHANICAL SPECIFICATIONS

Tolerances: ±0.02 in / 0.5 mm
All dimensions are in: inches [millimeters]



CIRCUIT DIAGRAMS

