



NOTES:

- 1. MATING END DIMENSION PER MD-103
- 2. APPLY EPOXY PER 400-05-005 TO THREADS AND TORQUE TO 10 INCH OZ. MIN.

SYM	DESCRIPTION	DATE	APPR.	UNLESS OTHERWISE SPECIFIED	SOLITRON/MICROWAVE		REF.
-	REL. F-11007	11/87	<i>[Signature]</i>	1. ALL DIMENSIONS ARE AFTER PLATING 2. BREAK ALL CORNERS & EDGES .005 R MAX. 3. CHAMFER 1ST & LAST THREADS 45° 4. SURFACE ROUGHNESS 32 MIL STD-10 5. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 6. REMOVE ALL BURRS	PORT SALERNO, FLORIDA		
A	REV. DCN 20694	5-5-99	<i>[Signature]</i>	DIMENSIONS ARE IN INCHES TOLERANCES DECIMALS X ± .030 XX ± .015 XXX ± .005 FRACTIONAL 2/164 ANGULAR X' ± 1'0" X'X' ± 15"	MATERIAL _____		TITLE
B	REV. DCN 21401	8-17-94	<i>[Signature]</i>		FINISH _____ AREA _____		TNC TEE ADAPTER FEMALE-MALE-FEMALE
C	DCN 43258	03/17	STW		SCALE 4x		DRAWING NO. SH. 2 OF 2
				DRAWN <i>[Signature]</i> , DATE 11-5-87	CODE IDENT. NO.	SIZE	M55339/35-00001
				CHECKED <i>[Signature]</i> DATE 11/87	95077	A	
				APPROVED <i>[Signature]</i> DATE 11/87			