

MAX38640A μ DFN Evaluation Kit

Evaluates: MAX38640 A in μ DFN

General Description

The MAX38640A evaluation kit (EV kit) evaluates the MAX38640A, an ultra-low quiescent current step-down DC-DC converter in the μ DFN package. The EV kit operates over an input range of 1.8V to 5.5V, and provides resistor-configurable output voltages from 1.0V to 3.3V. The EV kit delivers up to 175mA of current depending on the input voltage to the output voltage ratio.

The EV kit comes with the MAX38640AELT+ installed.

Features

- Evaluates the MAX38640A IC in a 6-pin μ DFN
- 1.8V to 5.5V Input Range
- 1.0V to 3.3V Configurable Output Voltage
- Up to 175mA Output Current
- Proven 2-Layer 1oz Copper PCB Layout
- Demonstrates Compact Solution Size
- Fully Assemble and Tested

Ordering Information appears at end of data sheet.

MAX38640A EV Kit Files

FILE	DESCRIPTION
MAX38640A μ DFN EV BOM	EV Kit Bill of Material
MAX38640A μ DFN EV PCB Layout	EV Kit Layout
MAX38640A μ DFN EV Schematic	EV Kit Schematic

Quick Start

Required Equipment

- MAX38640A μ DFN EV kit
- 5.5V, 3A DC power supply
- Electronic load capable of 175mA
- Digital voltmeter (DVM)

Procedure

The EV kit is fully assembled and tested. Follow the steps below to verify board operation.

Caution: Do not turn on power supply until all connections are completed.

- 1) Verify that jumpers JU1 and JU2 are in their default positions, as shown in [Table 1](#) and [Table 2](#).
- 2) Connect the 5.5V power supply between the IN and nearest GND terminal posts.
- 3) Connect the 175mA electronic load between the OUT and nearest GND terminal posts.
- 4) Connect the DVM between the OUT and nearest GND terminal posts.
- 5) Turn on the power supply.
- 6) Enable the electronic load.
- 7) Verify that the voltage at the OUT terminal post is 1.8V, within the device and the Output Voltage Selecting Resistor (RSEL)'s accuracy specifications.

Detailed Description of Hardware

The MAX38640A EV kit evaluates the MAX38640A, an ultra-low quiescent current step-down DC-DC converter in the μ DFN package. The EV kit operates over an input range of 1.8V to 5.5V, and provides resistor-configurable output voltages from 1.0V to 3.3V. The EV kit delivers up to 175mA of current depending on the input voltage to the output voltage ratio.

The EV kit comes with the MAX38640AELT+ installed.

EN

The MAX38640A μ DFN EV kit provides a jumper JU1 to enable or disable the MAX38640A. Refer to [Table 1](#) for jumper JU1 settings.

Table 1. EN (JU1)

SHUNT POSITION	DESCRIPTION
1-2*	EV Kit Enabled
1-3	EV Kit Controlled by External (TTL) Source Connected to EXT_EN
1-4	EV Kit Disabled

*Default position.

Component Suppliers

SUPPLIER	WEBSITE
Murata	www.murata.com
Samsung Electronics	www.samsung.com
Würth Electronics	www.we-online.com

Note: Indicate that you are using the MAX38640A when contacting these component suppliers.

Output Voltage Selection

The MAX38640A μ DFN EV kit provides a jumper JU2 to select the MAX38640A output voltage. Refer to [Table 2](#) for jumper JU2 settings.

Spare Inductor

The MAX38640A μ DFN EV kit provides a spare inductor on the PCB's bottom side. This spare inductor can be used to reconfigure the EV kit with a lower inductor DC resistance.

Table 2. OUT (JU2)

SHUNT POSITION	DESCRIPTION
1-2	OUT = 1.0V
1-3	OUT = 1.5V
1-4*	OUT = 1.8V
1-5	OUT = 3.3V
Not Installed	Output Voltage can be configured to between 0.7V and 3.3V by resistor R1. Refer to the IC data sheet.

*Default position.

Ordering Information


PART	TYPE
MAX38640AEVK# μ DFN	EV Kit

#Denotes RoHS


MAX38640A μ DFN EV Kit Bill of Materials

ITEM	REF_DES	DNI/DNP	QTY	MFG PART #	MANUFACTURER	VALUE	DESCRIPTION
1	C1	—	1	C1608X5R1A106K080AC	TDK	10 μ F	CAPACITOR; SMT (0603); CERAMIC CHIP; 10 μ F; 10V; TOL = 10%; MODEL = ; TG = -55°C TO +85°C; TC = X5R
2	C2	—	1	CL10A226KQ8NRN	SAMSUNG	22 μ F	CAP; SMT (0603); 22 μ F; 10%; 6.3V; X5R; CERAMIC CHIP
3	C5	—	1	25SVPF100M	PANASONIC	100 μ F	CAP; SMT (CASE_E7); 100UF; 20%; 25V; ALUMINUM-ORGANIC
4	J1-J4	—	4	1514-2	KEYSTONE	1514-2	TERMINAL; TURRET; PIN DIA = 0.090IN; TOTAL LENGTH = 0.105IN; BOARD HOLE = 0.098IN; BRASS; TIN PLATING;
5	JU1	—	1	PEC04SAAN	SULLINS ELECTRONICS CORP.	PEC04SAAN	CONNECTOR; MALE; THROUGH HOLE; BREAKAWAY; STRAIGHT; 4PINS
6	JU2	—	1	PBC05SAAN	SULLINS ELECTRONICS CORP.	PBC05SAAN	CONNECTOR; MALE; THROUGH HOLE; BREAKAWAY; STRAIGHT; 5PINS; -65°C TO +125°C
7	L1	—	1	1285AS-H-2R2M	TOKO	2.2 μ H	INDUCTOR; SMT (2016); METAL ALLOY CHIP; 2.2UH; TOL = \pm 20%; 1.4A
8	L1A	—	1	74479276222	WURTH ELECTRONICS INC.	2.2 μ H	INDUCTOR; SMT (0806); MOLDED CHIP; 2.2 μ H; 30%; 1.40A
9	R2	—	1	CRCW0603191KFK	VISHAY DALE	191K	RESISTOR; 0603; 191K Ω ; 1%; 100PPM; 0.10W; METAL FILM
10	R3	—	1	ERJ-3EKF6343	PANASONIC	634K	RES; SMT (0603); 634K; 1%; \pm 100PPM/DEGC; 0.1W
11	R4	—	1	CRCW060320K0FK	VISHAY DALE	20K	RESISTOR; 0603; 20K Ω ; 1%; 100PPM; 0.1W; THICK FILM
12	R5	—	1	ERJ-3EKF5622	PANASONIC	56.2K	RESISTOR; 0603; 56.2K Ω ; 1%; 100PPM; 0.1W; THICK FILM
13	R6	—	1	RC1608J000CS; CR0603-JI-000ELF; RC0603JR-070RL	SAMSUNG ELECTRONICS; BOURNS;YAGEO PH	0	RESISTOR; 0603; 0 Ω ; 5%; JUMPER; 0.10W; THICK FILM
14	SU1, SU2	—	2	S1100-B;SX1100-B; STC02SYAN	KYCON;KYCON; SULLINS ELECTRONICS CORP.	SX1100-B	TEST POINT; JUMPER; STR; TOTAL LENGTH = 0.24IN; BLACK; INSULATION = PBT; PHOSPHOR BRONZE CONTACT = GOLD PLATED
15	TP5	—	1	5002	KEYSTONE	N/A	TEST POINT; PIN DIA = 0.1IN; TOTAL LENGTH = 0.3IN; BOARD HOLE = 0.04IN; WHITE; PHOSPHOR BRONZE WIRE SILVER;
16	TP6, TP7	—	2	5001	KEYSTONE	N/A	TEST POINT; PIN DIA = 0.1IN; TOTAL LENGTH = 0.3IN; BOARD HOLE = 0.04IN; BLACK; PHOSPHOR BRONZE WIRE SILVER PLATE FINISH;
17	U1	—	1	MAX38640AELT+	MAXIM	MAX38640AELT+	EVKIT PART - IC; TINY 300NANO-AMP NANOPOWER BUCK CONVERTER; PACKAGE OUTLINE: 21-0164; PACKAGE CODE: L622+1C; PACKAGE LAND PATTERN: 90-0004; DFN6
18	PCB	—	1	MAX38640AUDFN	MAXIM	PCB	PCB:MAX38640AUDFN
19	MH1-MH4	DNP	0	9032	KEYSTONE	9032	MACHINE FABRICATED; ROUND-THRU HOLE SPACER; NO THREAD; M3.5; 5/8IN; NYLON
20	R1	DNP	0	CRCW06030000Z0	VISHAY DALE	0	RESISTOR; 0603; 0 Ω ; 0%; JUMPER; 0.1W; THICK FILM
21	C4	DNP	0	N/A	N/A	OPEN	PACKAGE OUTLINE 0603 NON-POLAR CAPACITOR
TOTAL			23				


MAX38640A μ DFN EV Kit Schematic




MAX38640A μ DFN EV Kit PCB Layout Diagrams




MAX38640A μ DFN EV Kit—Top Silkscreen



MAX38640A μ DFN EV Kit—Bottom



MAX38640A μ DFN EV Kit—Top



MAX38640A μ DFN EV Kit—Bottom Silkscreen