


MBR2030CT-G Thru. MBR20150CT-G

Voltage: 30 to 150 V

Current: 20.0 A

RoHS Device




Features

- Metal of silicon rectifier, majority carrier conduction.
- Guard ring for transient protection.
- Low power loss, high efficiency.
- High current capability, low VF.
- High surge capacity.
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications.

Mechanical Data

- Case: TO-220AB, molded plastic
- Epoxy: UL 94-V0 rate flame retardant.
- Polarity: As marked on the body.
- Mounting position: Any
- Weight: 2.24 grams



Electrical Characteristics (at TA=25°C unless otherwise noted)

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load derate current by 20%.

Parameter	Symbol	MBR 2030CT-G	MBR 2040CT-G	MBR 2050CT-G	MBR 2060CT-G	MBR 2080CT-G	MBR 20100CT-G	MBR 20150CT-G	Unit	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	30	40	50	60	80	100	150	V	
Maximum RMS Voltage	V_{RMS}	21	28	35	42	56	70	105	V	
Maximum DC Blocking Voltage	V_{DC}	30	40	50	60	80	100	150	V	
Maximum Average Forward Rectified Current (See Fig.1)	$I_{(AV)}$	20.0							A	
Peak Forward Surge Current , 8.3ms Single Half Sine-Wave Super Imposed On Rated Load(JEDEC Method)	I_{FSM}	150							A	
Peak Forward Voltage (Note 1)	IF=10A@ TJ= 25°C	-		0.80		0.85		0.95	V	
	IF=10A@ TJ=125°C	0.57		0.70		0.75		0.85		
	IF=20A@ TJ= 25°C	0.84		0.95		0.95		1.05		
	IF=20A@ TJ=125°C	0.72		0.85		0.85		0.95		
Maximum DC Reverse Current at Rate DC Blocking Voltage	@ TJ= 25°C	0.10		0.10		0.10		0.10	mA	
	@ TJ= 125°C	15.0		10.0		7.50		5.00		
Typical Junction Capacitance (Note2)	C_J	400			320				pF	
Typical Thermal Resistance (Note3)	$R_{\theta JC}$	1.50				3.50				°C/W
Operating Temperature Range	T_J	-55 to +150							°C	
Storage Temperature Range	T_{STG}	-55 to +175							°C	

NOTES:

- 300us pulse width, 2% duty cycle.
- Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
- Thermal resistance junction to case.

RATING AND CHARACTERISTIC CURVES (MBR2030CT-G Thru. MBR20150CT-G)

FIG.1- Forward Current Derating Curve




FIG.2- Maximum Non-Repetitive Surge Current




FIG.3- Typical Rever Characteristics




FIG.4- Typical Forward Characteristics




FIG.5- Typical Junction Capacitance

