

Part #: 100-00277-01

Description

The MEA-2410-FAKRA connector mount Antenna is a low profile antenna solution, with a very high-performance ideal for maintaining constant network connectivity. The MEA-2410-FAKRA covers all WiFi, BT, ZigBee, and ISM standard frequencies. This is an ideal antenna for telematics systems, remote surveillance, asset tracking and any IOT system applications. The MEA-2410-FAKRA is easy to install with maximum durability offering IP67 rated housing and anti-rotation mounting. The high performance and low profile make this antenna ideal for the most challenging installations.



Electrical Specification

Parameter	Specification	
Frequency Range	2410-2490 MHz	4920-5925MHz
Band	2.4 GHz	5.0GHz
Return Loss	-17.6 dB	-5.4 dB
VSWR	1.3:1	3.8:1
Efficiency	61.1%	25.7%
Peak Gain	2.6 dBi	-0.3 dBi
Average Gain	-2.1 dB	-6.2 dB
Impendance	50 Ω	
Polarization	Linear	
Radiation Pattern	Omni-Directional	
Max Input Power	25 W	

Mechanical Specification

Parameter	Specification
Antenna Dimensions	Ø12.5 x 44.5 mm
Operating Temperature	-40°C to + 85°C
Mounting Type	Connector Mount
Connector	Fakra Beige Female (Jack)
Radome/Color	ASA/Black
Substance Compliance	RoHS

^{*}Mounted on Ground Plane 80 x 40 cm

Features

- 2.4/5.0 GHz ISM, 2410-2490MHz, 4920-5925MHz
- · Easy mounting: Connector Mount
- High performance
- High Gain
- Small Form Factor: Ø12.5 x 44.5 mm

Applications

- WIFI applications
- · Navigation and telematics systems
- IoT applications
- · Automotive connectivity
- Multimedia
- Fleet management
- · HD video and audio streaming













