



MEA-5GG-SM

5G NR AND GNSS SCREW MOUNT

Part #: 100-00236-01

Description

The MEA-5GG-SM Screw Mount Antenna is a 2-in-1 low profile antenna solution, with a very high-performance ideal for maintaining constant network connectivity. The MEA-5GG-SM covers all 5G NR, and GPS/GLONASS/QZSS/Galileo standard frequencies. This is an ideal antenna for telematics systems, remote surveillance, asset tracking and any IOT system applications. The high performance and low profile make this antenna ideal for the most challenging installations.

This screw mount antenna is easy to install with maximum durability offering IP67 rated housing and anti-rotation mounting. The MEA-5GG-SM has a two cables with a SMA-Male standard connectors, 2m standard cable length and is fully customizable by offering additional connector types, cable lengths and cable types.

Electrical Specifications

Cable 1 - 5G NR Antenna

Parameter	Specification			
Technologies	5G, 4G, 3G and 2G			
Standards	5G NR/4GLTE/FirstNet/UCBRS/LPWNCAT-X/CAT-Mx/CAT-NBx/NB-IoT/3G/2G			
Frequency (MHz)	617-960	1427-2690	3300-5000	5150-5925
Return Loss (dB)	~ -7.4	~ -9.7	~ -11.2	~ -14.2
VSWR	~ 3.3:1	~ 2.3:1	~ 2.1:1	~ 1.7:1
Efficiency (%)	~ 20.7	~ 18.5	~ 15.3	~ 15.9
Peak Gain (dB)	~ -1.7	~ -1.7	~ -1.3	~ 0.6
Average Gain (dB)	~ -8.5	~ -8.6	~ -9.4	~ -8.2
Impedance (Ω)	50			
Polarization	Linear			
Radiation Pattern	Omni-Directional			
Max Input Power (W)	25			
Connector Type	SMA-Male (other connectors available)			
Cable Length	200 cm (custom length available)			
Cable Type	LL100 (other cable type available)			



Features

- 5G NR, GPS/GLONASS/QZSS/ Galileo frequency coverage
- Easy mounting: screw mount
- Anti-rotation mounting
- Customizable cable and connector
- Low profile Ø 146 x 31.5 mm
- IK09, IP67, IP69K

Applications

- IoT applications
- Telematic
- Navigation
- LTE applications

Electrical Specifications

Cable 2 - GNSS Ceramic Active Antenna

Parameter	Specification	
Standards	GPS/QZSS/Galileo	GLONASS
Band (MHz)	1575	1602
Frequency (MHz)	1575.42	1598-1606
Patch Size (mm)	25 x 25 x 4	
Passive Gain (dBi)	~ 3.6	
Impedance (Ω)	50	
Radiation Pattern	Hemispherical	
Voltage Range (V)	1.5 - 3.6	
Active Gain (dB)	28 @ 2.7 V	
Noise Figure (dB)	1.8 @ 2.7 V	
Current Consumption (mA)	9 @ 2.7 V	
Power Consumption (mW)	24.3 @ 2.7 V	
Saw Filter Type	Pre-Filter	
Connector Type	SMA-Male Standard (other connectors available)	
Cable Length	200 cm Standard (any cable length available)	
Cable Type	LL100 Standard (other cables available)	

Antenna Measurement Conditions:

Mounted on metal plate of 30 x 30 cm

100 cm of cable LL100

Measured in certified CTIA 3D anaechoic chamber

Mechanical and Environmental Specifications

Parameter	Specification
Mounting Type	Screw Mount
Dimensions (mm)	\varnothing 146 x 31.5
Weight (g)	520
Max. Tighten Torque (Nm)	6
Radome	ABS
Radome Color	Black
Antenna Base	Zamak
Gasket	TPE
Operating Temperature (C)	-40 to +85°
Storage Temperature (C)	-40 to +85°
Substance Compliance	RoHS
Certificates	IK09, IP67, IP69K

Radiation Performance

MEA-5GG-SM

