

AUDIO COUPLING MINIATURE ENCAPSULATED TRANSFORMER DESIGNED TO OPERATE 50mW MAX IN SECONDARY AND REFLECT A PRIMARY IMPEDANCE OF APPROXIMATELY 120Ω CT WITH 3.2Ω LOAD ON SECONDARY.



MODEL NUMBER
MET-43

A. Electrical Specifications (@ 20°C)


1. Pri Source Impedance; 120Ω CT
2. Sec Load Impedance; 3.2Ω
3. Pri DC Current; 10mA MAX
4. Operating Level; 50mW MAX @ 300Hz
5. Frequency Response (relative to 1KHz);
±2.0dB @ 300Hz to 100KHz
6. Longitudinal Balance; 60dB MIN @ 1KHz
7. DC Resistance;
(1-3) 13Ω ±20%
(4-5) 0.7Ω ±20%
8. Turns Ratio; (1-3) : (4-5) = 6.12 : 1.00 ±2%
9. Dielectric Strength;
500Vrms (10mA peak MAX) 1 minute @ Pri - Sec

B. Marking; MET-43, TAMURA, Primary and Secondary Impedance, PM37-M, MICROTRAN, TF5S21ZZ, date code and country of origin

C. Schematic Diagram



D. Mechanical Specifications



PREPARED BY:

D. Kelley

ENGINEER:
T. Shiozawa

DWG CONTROL NO.
P-A1-12015
ACAD\MET\A1120151.DWG

REV
-

AUDIO COUPLING
MINIATURE ENCAPSULATED TRANSFORMER

MET-43

QUALITY CONTROL:
D. Kelley

CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

TAMURA CORPORATION OF AMERICA
43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
(909) 699-1270 FAX 9096769482

MODEL SPECIFICATION

DIM: mm(in) SCL: 2/1 SH: 1 OF 1

APPROVED:
D. Suzuki

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.